

# Parker Hydraulic Threaded Cartridge Valves

Global Core Cartridge Valve Product Offerings



ENGINEERING YOUR SUCCESS.



## **WARNING - USER RESPONSIBILITY**

**FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.**

This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.

The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.

To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

## **OFFER OF SALE**


The items described in this document are hereby offered for sale by Parker-Hannifin Corporation, its subsidiaries or its authorized distributor. This offer and its acceptance are governed by the provisions stated in the detailed "Offer of Sale" Available from your local Parker representative.

# PLEASE READ

## How to use this catalog...

### • Product Index

Each product tab has its own product index for that particular section. Basic product specifications are shown along with catalog page numbers and product symbols. Further detail can be found on the specific catalog pages.

Catalog MSG15-3504 Index						CV
SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.	
Technical Tips						CV-CV
						SH
<b>STANDARD CHECKS</b>						
D14007	25	Some Check Valve	3.8/1	350/500	CV2	
D14060	30	Check Valve Invert. Ball Type	146/159	420/600	CV2	
D18125	25	Check Valve Invert. Ball Type	360/132	420/600	CV6	
D0082	200	Cartridge Check, Ball Type	49/12	400/600	CV7	
D0081P	020-2	Cartridge Check, Ball Type	36/10	350/500	CV7	
D4109P	CH1-2	Cartridge Check, Poppet Type	48/18	350/500	CV7	
D0082	CH1-2	Cartridge Check, Ball Type	180/42	400/600	CV11	
D4121P	CH1-2	Cartridge Check, Poppet Type	127/52	350/500	CV11	
D0082P	CH1-2	Cartridge Check, Poppet Type	280/74	400/600	CV12	
D0082P	CH1-2	Cartridge Check, Poppet Type	220/60	350/500	CV11	
D1816P	CH1-2	Cartridge Check, Poppet Type				
D1816P	CH1-2	Cartridge Check, Poppet Type				
PILOT OPERATED CHECKS						

<b>Check Valves</b>	<b>CV1-CV19</b>	<b>CV</b> Check Valves
<b>Shuttle Valves</b>	<b>SH1-SH6</b>	<b>SH</b> Shuttle Valves
<b>Load and Motor Control Valves</b>	<b>LM1-LM33</b>	<b>LM</b> Load/Motor Controls
<b>Flow Control Valves</b>	<b>FC1-FC29</b>	<b>FC</b> Flow Controls
<b>Pressure Control Valves</b>	<b>PC1-PC59</b>	<b>PC</b> Pressure Controls
<b>Logic Element Valves</b>	<b>LE1-LE17</b>	<b>LE</b> Logic Elements
<b>Directional Control Valves</b>	<b>DC1-DC5</b>	<b>DC</b> Directional Controls
<b>Solenoid Valves</b>	<b>SV1-SV64</b>	<b>SV</b> Solenoid Valves
<b>Proportional Valves</b>	<b>PV1-PV32</b>	<b>PV</b> Proportional Valves
<b>Coils and Electronics</b>	<b>CE1-CE9</b>	<b>CE</b> Coils & Electronics
<b>Bodies and Cavities</b>	<b>BC1-BC39</b>	<b>BC</b> Bodies & Cavities
<b>Technical Data</b>	<b>TD1-TD4</b>	<b>TD</b> Technical Data



SERIES	DESCRIPTION	PAGE NO.
16SLC1-A.....	Normally Closed, Pilot to Close .....	LE9
20SLC1-A.....	Normally Closed, Pilot to Close .....	LE10
A04B2 .....	Direct Acting Relief, Poppet Type .....	PC16-PC17
A04J2.....	Direct Acting, Cross-over Relief .....	PC34-PC35
AP02B2YP .....	Increase Pressure/Increase Current .....	PV6-PV7
AP02B2YR .....	Decrease Pressure/Increase Current .....	PV10-PV11
AP04G2YP .....	Increase Pressure/Increase Current .....	PV8-PV9
AP04G2YR .....	Decrease Pressure/Increase Current .....	PV12-PV13
CB101 .....	Load Control Cartridge Valve .....	LM12-LM13
CDPH103.....	Dual P.O. Check Package .....	CV17-CV18
CPD084P .....	Dual P.O. Check Cartridge .....	CV19
CPH104P .....	Single P.O. Check, Pilot on Port 1 .....	CV15
CPH124P .....	Single P.O. Check, Pilot on Port 1 .....	CV16
CSH041 .....	Cartridge Shuttle .....	SH4
CSH101B .....	Cartridge Shuttle .....	SH5
CVH021 .....	Sense Check Valve .....	CV4
CVH081P .....	Cartridge Check, Poppet Type .....	CV8
CVH103P .....	Cartridge Check, Poppet Type .....	CV9
CVH121P .....	Cartridge Check, Poppet Type .....	CV11
CVH161P .....	Cartridge Check, Poppet Type .....	CV13
CVH201P .....	Cartridge Check, Poppet Type .....	CV14
D02B2 .....	Cartridge Check, Ball Type .....	CV7
D04B2 .....	Cartridge Check, Ball Type .....	CV10
D06B2P .....	Cartridge Check, Poppet Type .....	CV12
D1A060 .....	Check Valve Insert, Ball Type .....	CV5
D1B125 .....	Check Valve Insert, Ball Type .....	CV6
DH103 .....	3 Way, External Pilot, Normally Open, Vent to Atmosphere .....	DC2-DC3
DSH081 .....	2 Position, 2 Way, N.C. or N.O. ....	SV7-SV8
DSH082 .....	2 Position, 2 Way .....	SV31-SV32
DSH083 .....	2 Position, 3 Way .....	SV35-SV37
DSH084 .....	2 Position, 4 Way .....	SV41-SV42
DSH101 .....	2 Position, 2 Way, N.C. or N.O. ....	SV9-SV10
DSH102 .....	2 Position, 2 Way .....	SV33-SV34
DSH103 .....	2 Position, 3 Way .....	SV38-SV40
DSH104 .....	2 Position, 4 Way .....	SV43-SV44
DSH121 .....	2 Position, 2 Way, N.C. or N.O. ....	SV11-SV12
DSH161 .....	2 Position, 2 Way, N.C. or N.O. ....	SV13-SV14
DSH164 .....	2 Position, 4 Way .....	SV45-SV46
DSL087 <i>(NEW)</i> .....	Bi-Directional Poppet, N.C. or N.O. ....	SV17-SV18
DSL105 .....	3 Position, 4 Way .....	SV55-SV56
DSL201 .....	2 Position, 2 Way, N.C. or N.O. ....	SV15-SV16
DSP105C1 .....	3 Position, 4 Way - Closed Center .....	PV30-PV32
DSP105C4 .....	3 Position, 4 Way - Float Center .....	PV30-PV32
E2*020 .....	Load Control Cartridge Valve .....	LM16-LM17
E2*040 .....	Load Control Cartridge Valve .....	LM18-LM19
E2*060 .....	Load Control Cartridge Valve .....	LM20-LM21
E2*125 .....	Load Control Cartridge Valve .....	LM22-LM23
E2*300 .....	Load Control Cartridge Valve .....	LM24-LM25
E6B020 .....	Load Control Cartridge Valve, 4.5:1 Ratio .....	LM26-LM27
E6B040 .....	Load Control Cartridge Valve, 3:1 Ratio .....	LM30-LM31
E6B060*409 .....	Load Control Cartridge Valve, 3:1 Ratio .....	LM32-LM33
E6K020 .....	Load Control Cartridge Valve, 15:1 Ratio .....	LM28-LM29
EPR083R .....	Pressure Reducing/Relieving Valve .....	PV14-PV15
EPR111C .....	Pressure Reducing/Relieving Valve .....	PV16-PV17
E2*1 <i>(NEW)</i> .....	Load Control Cartridge Valve .....	LM6-LM7
E2*1R <i>(NEW)</i> .....	Load Control Cartridge Valve .....	LM8-LM9
E2*1S <i>(NEW)</i> .....	Load Control Cartridge Valve .....	LM10-LM11
FA101 .....	Restrictive Flow Control, Reverse Check, Adjustable .....	FC16-FC17
FC101 .....	Restrictive Flow Control, Reverse Check, Tuneable .....	FC18-FC19
FV101 .....	Needle Valve with Reverse Check, 1 to 2 Free Flow .....	FC10-FC11
FV102 .....	Needle Valve with Reverse Check, 1 to 2 Free Flow .....	FC10-FC11

SERIES	DESCRIPTION	PAGE NO.
GP02 51 .....	4 Way, 3 Pos - Closed Center .....	PV26-PV27
GP02 52 .....	4 Way, 3 Pos - Closed Center .....	PV26-PV27
GP02 53 .....	4 Way, 3 Pos - Closed Center .....	PV28-PV29
GP02 54 .....	4 Way, 3 Pos - Closed Center .....	PV28-PV29
GS02 51 .....	3 Position, 4 Way .....	SV47-SV48
GS02 53 .....	3 Position, 4 Way .....	SV49-SV50
GS02 57 .....	3 Position, 4 Way .....	SV51-SV52
GS02 59 .....	3 Position, 4 Way .....	SV53-SV54
GS02 81 .....	Bi-Directional Poppet N.C. ....	SV19-SV20
GS02 86 .....	Bi-Directional Poppet N.O. ....	SV25-SV26
GS04 52D .....	3 Position, 4 Way .....	SV57-SV58
GS04 54D .....	3 Position, 4 Way .....	SV59-SV60
GS04 57D .....	3 Position, 4 Way .....	SV61-SV62
GS04 59D .....	3 Position, 4 Way .....	SV63-SV64
GS04 81 .....	Bi-Directional Poppet N.C. ....	SV21-SV22
GS04 86 .....	Bi-Directional Poppet N.O. ....	SV27-SV28
GS06 81 .....	Bi-Directional Poppet N.C. ....	SV23-SV24
GS06 86 .....	Bi-Directional Poppet N.O. ....	SV29-SV30
J02D3 .....	Priority Type, with Bypass .....	FC20-FC21
J02E2 .....	Restrictive Flow Control, Adjustable .....	FC12-FC13
J04D3 .....	Priority Type, with Bypass .....	FC22-FC23
J04E2 .....	Restrictive Flow Control, Adjustable .....	FC14-FC15
J1A125 .....	Priority Type, with Bypass .....	FC24-FC25
JP02C .....	Flow Control, N.C. ....	PV18-PV19
JP02P .....	Flow Control, N.O. ....	PV22-PV23
JP04C 21 .....	Flow Control, N.C. ....	PV20-PV21
JP04C 31 .....	Priority Flow Control, N.C. ....	PV24-PV25
K04C3 .....	Spool Type, Spring Centered, All Ports Closed .....	SH6
KSWA3 .....	Ball Insert Type .....	SH3
L04A3 .....	Flow Divider/Combiner .....	FC26-FC27
L06A3 .....	Flow Divider/Combiner .....	FC28-FC29
LE101A <i>(NEW)</i> .....	Normally Closed, Pilot to Close .....	LE8
LE102A <i>(NEW)</i> .....	Normally Closed, Pilot to Close .....	LE11
LE102B <i>(NEW)</i> .....	Normally Closed, Vent to Open .....	LE14
LE103A <i>(NEW)</i> .....	Normally Open, Vent to Close .....	LE15
LE103B <i>(NEW)</i> .....	Normally Open, Vent to Close .....	LE17
MHC-010-S*** .....	Load Control Cartridge Valve .....	LM14-LM15
N5A125 .....	3 Way, 2 Position, External Drain, Open Transition .....	DC4
N5A300 .....	3 Way, 2 Position, External Drain, Open Transition .....	DC5
NVH081 .....	Needle Valve, Cartridge Type .....	FC6-FC7
NVH101 .....	Needle Valve, Cartridge Type .....	FC8-FC9
PR103 .....	Direct Acting Reducing/Relieving .....	PC48-PC49
PRH081 .....	Pilot Operated Reducing/Relieving .....	PC54-PC55
PRH082 .....	Pilot Operated Reducing .....	PC50-PC51
PRH101 .....	Pilot Operated Reducing/Relieving .....	PC56-PC57
PRH102 .....	Pilot Operated Reducing .....	PC52-PC53
PRH161 .....	Pilot Operated Reducing/Relieving .....	PC58-PC59
R06E3 .....	Normally Closed, Pilot to Close .....	LE12
R06H3 .....	Normally Open, Vent to Close .....	LE16
R08E3 .....	Normally Closed, Pilot to Close .....	LE13
RAH081 .....	Pilot Operated Spool Type .....	PC24-PC25
RAH101 .....	Pilot Operated Spool Type .....	PC26-PC27
RAH121 .....	Pilot Operated Spool Type .....	PC28-PC29
RAH161 .....	Pilot Operated Spool Type .....	PC30-PC31
RAH201 .....	Pilot Operated Spool Type .....	PC32-PC33
RD102 .....	Direct Acting Relief, Poppet Type .....	PC14-PC15
RD163 .....	Direct Acting Differential Area Relief .....	PC22-PC23
RDH081 .....	Direct Acting Relief, Ball Type .....	PC8-PC9
RDH082 .....	Direct Acting Relief, Poppet Type .....	PC10-PC11
RDH083 .....	Direct Acting Differential Area Relief .....	PC18-PC19
RDH101 .....	Direct Acting Relief, Ball Type .....	PC12-PC13
RDH103 .....	Direct Acting Differential Area Relief .....	PC20-PC21
RU104 .....	Direct Acting Unloading .....	PC36-PC37

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

SERIES	DESCRIPTION	PAGE NO.
SVH081	Pilot Operated, Int. Pilot, Ext. Drain.....	PC38-PC39
SVH101	Pilot Operated, Int. Pilot, Ext. Drain.....	PC40-PC41
SVH102	Pilot Operated, Ext. Pilot, Int. Drain.....	PC44-PC45
SVH161	Pilot Operated, Int. Pilot, Ext. Drain.....	PC42-PC43
SVH162	Pilot Operated, Ext. Pilot, Int. Drain.....	PC46-PC47

**Cartridge Valve Coils**

CC	1/2" Solenoid Tubes .....	CE4-CE5
CA	5/8" Solenoid Tubes .....	CE6-CE7
SW7L	1/2" Proportional Tube - Short.....	CE8-CE9

**Standard Bodies and Cavities**

C04-3	04 Size, 3 Way .....	BC4
C08-2	08 Size, 2 Way .....	BC5
C08-3	08 Size, 3 Way .....	BC6
C08-3L	08 Size, 3 Way, Long .....	BC7
C08-4	08 Size, 4 Way .....	BC8
C10-2	10 Size, 2 Way .....	BC9
C10-3	10 Size, 3 Way .....	BC10
C10-3L	10 Size, 3 Way, Long .....	BC11
C10-3S	10 Size, 3 Way, Short.....	BC12
C10-4	10 Size, 4 Way .....	BC13
C12-2	12 Size, 2 Way .....	BC14
C12-3	12 Size, 3 Way .....	BC15
C16-2	16 Size, 2 Way .....	BC16
C16-3	16 Size, 3 Way .....	BC17
C16-3S	16 Size, 3 Way, Short.....	BC18
C16-4	16 Size, 4 Way .....	BC19
C20-2	20 Size, 2 Way .....	BC20
C20-3S	20 Size, 3 Way, Short.....	BC21

**Counterbalance Cavities and Bodies**

MHC-010	Single and Dual Counterbalance Bodies .....	BC22
---------	---	------

**Pilot Piston Cavities**

10 Size	10 Size Cavity for Dual Check and Pilot Piston.....	BC23
---------	---	------

**Special Bodies and Cavities**




CAVOW-2	2 Port.....	BC24
CAVSW-3	3 Port.....	BC25
CAVT11A	3 Port.....	BC26
2C	2 Port.....	BC27
2R	2 Port.....	BC28
2U	2 Port.....	BC29
3A	3 Port.....	BC30
3C	3 Port.....	BC31
3K	3 Port.....	BC32
3M	3 Port.....	BC33
3X	3 Port.....	BC34
4C	4 Port.....	BC35
5A	5 Port.....	BC36
53-1	3 Port.....	BC37
68-1	3 Port.....	BC38
100-1	5 Port.....	BC39

**Technical Data**

Basic Hydraulic Formulas.....	TD2
Ratings and Testing.....	TD2
Temperature Ratings.....	TD2
Viscosity .....	TD2
Pressure Ratings.....	TD2
Thermal Shock .....	TD2
Service and Components .....	TD2
Limitations in Use .....	TD2
Seal Material Selection .....	TD3
Hydraulic Fluids .....	TD4
Hydraulic Filtration.....	TD4
Application of Product.....	TD4

<b>CV</b>	Check Valves
<b>SH</b>	Shuttle Valves
<b>LM</b>	Load/Motor Controls
<b>FC</b>	Flow Controls
<b>PC</b>	Pressure Controls
<b>LE</b>	Logic Elements
<b>DC</b>	Directional Controls
<b>SV</b>	Solenoid Valves
<b>PV</b>	Proportional Valves
<b>CE</b>	Coils & Electronics
<b>BC</b>	Bodies & Cavities
<b>TD</b>	Technical Data

Check Valves

SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
Technical Tips.....					CV2-CV3
<div></div> <div><b>STANDARD CHECKS</b> CVH021 .....Sense Check Valve.....3.8/1 ..... 350/5000 ..... CV4 D1A060 ..... 2U.....Check Valve Insert, Ball Type.....145/38 ..... 420/6000 ..... CV5 D1B125 ..... 2C.....Check Valve Insert, Ball Type.....500/132 ..... 420/6000 ..... CV6 D02B2 ..... C08-2 .....Cartridge Check, Ball Type .....45/12 ..... 420/6000 ..... CV7 CVH081P ..... C08-2 .....Cartridge Check, Poppet Type .....38/10 ..... 350/5000 ..... CV8 CVH103P ..... C10-2 .....Cartridge Check, Poppet Type .....60/16 ..... 350/5000 ..... CV9 D04B2 ..... C10-2 .....Cartridge Check, Ball Type .....160/42 ..... 420/6000 ..... CV10 CVH121P ..... C12-2 .....Cartridge Check, Poppet Type .....121/32 ..... 350/5000 ..... CV11 D06B2P ..... C16-2 .....Cartridge Check, Poppet Type .....280/74 ..... 420/6000 ..... CV12 CVH161P ..... C16-2 .....Cartridge Check, Poppet Type .....226/60 ..... 350/5000 ..... CV13 CVH201P ..... C20-2 .....Cartridge Check, Poppet Type .....303/80 ..... 350/5000 ..... CV14</div>					
<div></div> <div><b>PILOT OPERATED CHECKS</b> CPH104P ..... C10-3 .....Single P.O. Check, Pilot on Port 1.....30/8 ..... 350/5000 ..... CV15 CPH124P ..... C12-3 .....Single P.O. Check, Pilot on Port 1.....75/20 ..... 350/5000 ..... CV16</div>					
<div></div> <div><b>DUAL PILOT OPERATED CHECKS</b> CDPH103 .....Dual P.O. Check Package .....60/16 ..... 350/5000 .....CV17-CV18 CPD084P ..... C08-4 .....Dual P.O. Check Cartridge .....19/5 ..... 207/3000 ..... CV19</div>					


CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

**INTRODUCTION:**

This technical tips section is designed to help familiarize you with the Parker line of Check Valves. In this section we present the products that are new to this catalog as well as some design features of our check valves. In addition, we present common options available to help you in selecting products for your application. Finally we give a brief synopsis of the operation and applications of the various product offered in this section.

**NEW PRODUCTS:**

There are several new additions and product improvements to our Check Valve product line.

**COMMON OPTIONS:**

Since check valves and shuttles are fairly simple components, there are very few options. Here are the standard options you will find.

**Seals:** Valves feature a 4301 Polyurethane "D"-Ring. The "D"-Ring eliminates the need for back-up rings. The majority of the products are also available in Nitrile or Fluorocarbon seals. Contact factory for availability.

You should match the seal compatibility to the temperature and fluid being used in your application.

**Crack Pressure:** Parker offers a number of standard crack pressure options for each valve. Check the model code pages for these options. The crack pressure is defined as the minimum amount of pressure that is needed to unseat the poppet. In pilot operated check applications, you may want to go with a slightly higher cracking pressure to keep the piston weight, friction, and drag from accidentally unseating the poppet.

**Pilot Piston Seal:** On the pilot piston style pilot operated check valves, Parker offers the option to place a seal on the piston to reduce the leakage across the piston.

**Note:** Sealing the pilot piston does not decrease the leakage across the poppet. In other words, if you are trying to reduce the leakage from the actuator port, sealing the piston will not help. While most applications do not require a seal on the piston, it can be advantageous in applications with very small pump flows where the lost fluid would have a high impact on actuator speed.





## PRODUCT TYPES / APPLICATIONS

**Check Valve - Poppet Type**

Check valves are poppet style elements that allow free flow in one direction while preventing flow in the reverse direction.



They can be used to isolate portions of a hydraulic circuit or to provide a free flow path around a restrictive valve.

**OPERATION** - Pressure on the inlet (port 1) of the check valve creates a force against the poppet, pushing it off its seat and permitting free flow to port 2. Reverse flow through the check is blocked by the poppet.

**Check Valve - Ball Type**



Ball type check valves are check valves that use a hardened steel ball to seal against the valve seat as opposed to a poppet. They are simple in their design and provide low leakage over the life of the system.

**OPERATION** - Pressure on the inlet (port 1) of the check valve creates a force on the steel ball pushing it off of its seat and permitting free flow to port 2. Reverse flow through the check is blocked by the steel ball on the seat.

**Pilot Operated Check Valve**

Parker's reliable pilot piston style P.O. check valves are designed for critical applications where safety and load holding is required and flows from 19 to 150 lpm (5 to 40 gpm) and pressures up to 420 bar (6,000 psi) are needed. These valves are available with pilot supply to either the 1st port or 3rd port depending on circuit need, and are generally used in conjunction with linear actuators across several markets within mobile or industrial hydraulics, such as aeriels, material handling, and construction where durable and low leak valves are necessary to keep the machinery and operators safe.

**OPERATION** - Pilot operated check valves, also known as P.O. checks, are used to lock a cylinder in a holding position with minimal leakage or drift. P.O. check valves that can be opened to allow flow in the reverse direction with an external signal to the pilot port. The valves work best when used in conjunction with a control valve that vents the valve ports to tank when centered. Pilot pressure to open the checks for reverse flow is a ratio of the holding pressure, and are typically 3:1 or 4:1. A 3:1 ratio with a 3000psi load requires a 1000psi signal to the pilot port.



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description

Cartridge Style Sense Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Rapid response to load direction changes
- Hardened precision parts for durability
- **Insert style design for location within manifolds under SAE-6 or larger port**



## Performance Curve

### Pressure Drop vs. Flow




## Specifications

Rated Flow	3.8 LPM (1 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	15 ml/min.
Cartridge Material	Steel operating parts hardened steel ball.
Operating Temp. Range/Seals	-26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.02 kg (0.045 lbs.)



## Dimensions

Millimeters (Inches)



## Ordering Information

**CVH021**

Size 02 Sense Check Valve

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description


Ball Type, Check Valve Insert.  
 For additional information see Technical Tips on pages CV2-CV3.

## Features

- For inserting inside manifold blocks
- High flow capacity
- Minimal leakage - less than 3 drops/min.
- Simple construction - extremely cost effective
- Good contamination tolerance



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	145 LPM (38 GPM)
Nominal Flow @ 7 Bar (100 PSI)	90 LPM (24 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	Less than 3 drops/min.
Cartridge Material	Steel operating parts hardened steel ball.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.85 kg (0.19 lbs.)
Cavity	2U (See BC Section for more details)



## Dimensions

Millimeters (Inches)



## Ordering Information

**D1A060**

Check Valve  
Insert

**0.2**

Cracking  
Pressure

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
0.2	0.2 Bar (3 PSI) Std.

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30019N-1
Fluorocarbon Seal	SK30019V-1

## General Description

Poppet Type, Check Valve Insert.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- For inserting inside manifold blocks
- High Stable flow capacity (Contact the Factory for Highly dynamic application)
- Minimal leakage - less than 3 drops/min.
- Simple construction - extremely cost effective
- Good contamination tolerance
- Alternative 1"SAE or 1"BSP Retainer available separately


## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	500 LPM (132 GPM)
Nominal Flow @ 7 Bar (100 PSI)	300 LPM (79GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	Less than 3 drops/min.
Cartridge Material	Steel operating parts hardened steel poppet.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.6 kg (0.13 lbs.)
Cavity	2C (See BC Section for more details)




Free Flow →



## Dimensions

Millimeters (Inches)



Retaining Clip #8010977 Included.

## Ordering Information

**D1B125**

Check Valve  
Insert



Cracking  
Pressure



Seals


**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
<b>0.2</b>	<b>0.2 Bar (3 PSI)</b>
<b>1.0</b>	<b>1.0 Bar (15 PSI) Std.</b>
<b>5.0</b>	<b>5.0 Bar (72 PSI)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Threaded Retainer (1"SAE)	RT10002
Threaded Retainer (1"BSP)	RT10001
Nitrile Seal	SK30014N-1
Fluorocarbon Seal	SK30014V-1

## Retainer





## General Description

Ball Type Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Low leakage - less than 3 drops/min.
- Ball type construction for cost effective design
- Single and dual pilot pistons available to create pilot to open check
- Range of cracking pressures available - up to 25 Bar (362 PSI)
- Good contamination tolerance
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	80 LPM (21 GPM)
Nominal Flow @ 7 Bar (100 PSI)	45 LPM (12GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	Less than 3 drops/min.
Cartridge Material	Steel operating parts hardened steel ball.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.05 kg (0.11 lbs.)
Cavity	C08-2 (See BC Section for more details)



## Dimensions



## Ordering Information

<b>D02B2</b>	—	<b>N</b>
Ball Type Check Valve	Cracking Pressure	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
<b>0.2</b>	<b>0.2 Bar (3 PSI) Std.</b>
<b>1.0</b>	<b>1.0 Bar (15 PSI)</b>
<b>2.1</b>	<b>2.1 Bar (30 PSI)</b>
<b>3.4</b>	<b>3.4 Bar (50 PSI)</b>
<b>6.0</b>	<b>6.0 Bar (87 PSI)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Nitrile Seal	SK30515N-1
Fluorocarbon Seal	SK30515V-1

Order Bodies Separately  
 See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Porting / Body Material
<b>6T</b>	<b>SAE-6 / Steel (5000 PSI)</b>

## General Description

Cartridge Style Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Spherical poppet for low leakage
- "D"-Ring eliminates back-up rings
- Dual sense paths for reduced  $\Delta P$
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	38 LPM (10 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	2 drops/min. (0.13 cc/min) at 350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.10 kg (0.2 lbs.)
Cavity	C08-2 (See BC Section for more details)



## Dimensions

Millimeters (Inches)



## Ordering Information

**CVH081P**

08 Size  
Check Valve

Cracking  
Pressure

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	0.3 Bar (5 PSI)
30	2.1 Bar (30 PSI)
65	4.5 Bar (65 PSI)
100	6.9 Bar (100 PSI)

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Order Bodies Separately  
 See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description

Cartridge Style Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Spherical poppet for low leakage
- "D"-Ring eliminates back-up rings
- Dual sense paths for reduced  $\Delta P$
- All external parts zinc plated



## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)




## Specifications

Rated Flow	60 LPM (16 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	2 drops/min. (0.13 cc/min) at 350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.9 kg (2.0 lbs.)
Cavity	C10-2 (See BC Section for more details)



## Dimensions



## Ordering Information

**CVH103P**

10 Size  
Check Valve

Cracking  
Pressure

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	0.3 Bar (5 PSI)
20	1.4 Bar (20 PSI)
50	3.5 Bar (50 PSI)
100	6.9 Bar (100 PSI)

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
 See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description

Ball Type Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Low leakage - less than 3 drops/min.
- Ball type construction for cost effective design
- Single and dual pilot pistons available to create pilot to open check
- Range of cracking pressures available
- Good contamination tolerance
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	160 LPM (42 GPM)
Nominal Flow @ 7 Bar (100 PSI)	90 LPM (24 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	3 drops/min.
Cartridge Material	Steel operating parts, hardened steel ball.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile, Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.18 lbs.)
Cavity	C10-2 (See BC Section for more details)



## Dimensions



## Ordering Information

<b>D04B2</b>	—	<b>N</b>
Ball Type Check Valve	Cracking Pressure	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
<b>0.2</b>	<b>0.2 Bar (3 PSI) Std.</b>
<b>2.1</b>	<b>2.1 Bar (30 PSI)</b>

Kit	Part Number
Nitrile Seal	SK30516N-1
Fluorocarbon Seal	SK30516V-1

Code	Seals
<b>N</b>	<b>Nitrile</b>

Order Bodies Separately  
 See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
<b>8T</b>	<b>SAE-8 / Steel (5000 PSI)</b>



## General Description

Cartridge Style Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Hardened, precision ground parts for durability
- Fully guided poppet for smooth operation
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	121 LPM (32 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) at 350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.14 kg (0.30 lbs.)
Cavity	C12-2 (See BC Section for more details)



## Dimensions



## Ordering Information

**CVH121P**

12 Size  
 Check Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	1.7 Bar (25 PSI)

Code	Seals
Omit	Nitrile

Kit	Part Number
Nitrile Seal	SK12-2
Fluorocarbon Seal	SK12-2V

Order Bodies Separately  
 See section BC

<b>B12</b>	—	<b>2</b>	—	<b>12T</b>
12 size		2-Way Cavity		Port Size

Code	Porting / Body Material
12T	SAE-12 / Steel (5000 PSI)

## General Description

Poppet Type Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Extra low pressure drop capability for systems up to 250 Bar
- Poppet type construction for minimal leakage - less than 3 drops/min.
- Hardened poppet for maximum durability
- Good contamination tolerance
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	500 LPM (132 GPM)
Nominal Flow @ 7 Bar (100 PSI)	280 LPM (74 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	Less than 3 drops/min.
Cartridge Material	Steel operating parts, hardened steel poppet.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile, Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.27 kg (0.60 lbs.)
Cavity	C16-2 (See BC Section for more details)



## Dimensions



## Ordering Information

**D06B2P**

16 Size  
Check Valve

**0.1**

Cracking  
Pressure

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
0.1	0.1 Bar (1.5 PSI) Std.

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30507N-1
Fluorocarbon Seal	SK30507V-1

Order Bodies Separately  
 See section BC

<b>B16</b>	<b>2</b>	<b>16T</b>
16 size	2-Way Cavity	Port Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

## General Description

Cartridge Style Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Hardened, precision ground parts for durability
- Fully guided poppet for smooth operation
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	225 LPM (60 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) at 350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.27 kg (0.60 lbs.)
Cavity	C16-2 (See BC Section for more details)



## Dimensions



## Ordering Information

**CVH161P**

16 Size  
Check Valve



Cracking  
Pressure

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	0.3 Bar (5 PSI)
20	1.4 Bar (20 PSI)

Code	Seals
Omit	Nitrile

Kit	Part Number
Nitrile Seal	SK16-2
Fluorocarbon Seal	SK16-2V

Order Bodies Separately  
 See section BC

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 size		2-Way Cavity		Port Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

## General Description

Cartridge Style Check Valve.


For additional information see Technical Tips on pages CV2-CV3.

## Features

- Hardened, precision ground parts for durability
- Fully guided poppet for smooth operation
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	303 LPM (80 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) at 350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.27 kg (0.60 lbs.)
Cavity	C20-2 (See BC Section for more details)



## Dimensions



## Ordering Information

**CVH201P**

20 Size  
Check Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	0.3 Bar (5 PSI)

Code	Seals
Omit	Nitrile

Kit	Part Number
Nitrile Seal	SK20-2
Fluorocarbon Seal	SK20-2V

Order Bodies Separately  
See section BC

<b>B20</b>	—	<b>2</b>	—	<b>20T</b>
20 size		2-Way Cavity		Port Size

Code	Porting / Body Material
20T	SAE-20 / Steel (5000 PSI)



## General Description


Cartridge Style Pilot Operated Check Valve. For additional information see Technical Tips on pages CV2-CV3.

## Features

- Hardened, precision ground parts for durability
- Internal pilot position simplifies manifold design
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	30 LPM (8 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	2 drops/min. (0.13 cc/min) at 350 Bar (5000 PSI)
Pilot Ratio	4:1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.9 kg (2.0 lbs.)
Cavity	C10-3 (See BC Section for more details)



## Dimensions

Millimeters (Inches)



## Ordering Information

**CPH104P**

10 Size  
Check Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	<b>1.4 Bar (20 PSI)</b>

Code	Seals
Omit	<b>"D"-Ring</b>

Kit	Part Number
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description


Cartridge Style Pilot Operated Check Valve.  
 For additional information see Technical Tips on pages CV2-CV3.

## Features

- Hardened, precision ground parts for durability
- Internal pilot position simplifies manifold design
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	75 LPM (20 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) at 350 Bar (5000 PSI)
Pilot Ratio	3:1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.2 kg (0.44 lbs.)
Cavity	C12-3 (See BC Section for more details)



## Dimensions



## Ordering Information

**CPH124P**

12 Size  
 P.O. Check Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Cracking Pressure
Omit	1.7 Bar (25 PSI)

Code	Seals
Omit	Nitrile*

Kit	Part Number
Nitrile Seal	SK12-3
Fluorocarbon Seal	SK12-3V

\* 2.5 size b/u rings

Order Bodies Separately  
 See section BC

<b>B12</b>	<b>3</b>	<b>12T</b>
12 size	3-Way Cavity	Port Size

Code	Porting / Body Material
12T	SAE-12 / Steel (5000 PSI)



## General Description

Pilot Piston Style Dual Pilot Operated Check Valve.

For additional information see Technical Tips on pages CV2-CV3.

## Features

- Spherical poppet for low leakage
- “D” -Ring eliminates back-up rings
- Optional sealed pilot piston




## Specifications


Maximum Flow	60 LPM (16 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI) - CDPH103
Leakage Across Check 150 SSU (32 cSt)	2 drops/min. (0.13 cc/min.)
Leakage Across Pilot Piston (No Seals)	312 cc/min. 0.3 LPM (.08 GPM)
Pilot Ratio	4:1
Pilot Piston Part Numbers	No Seal - 717917 Nitrile Seal - 717917N Fluorocarbon Seal - 717917V
Cartridge Material	All parts steel. All operating parts hardened steel.
Body Material	Steel - CDPH103
Operating Temp. Range (Ambient)	-45°C to +132°C (“D”-Ring) (-50°F to +270°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	1.59 kg (3.5 lbs.)

## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

CDP	H103			8T
10 Size Dual Pilot Piston P.O. Check Valve	Model Desc.	Piston Type	Cracking Pressure	Port Size

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Model Description
H103	5000 PSI Series

Code	Cracking Pressure
*Omit	0.3 Bar (5 PSI)
20	1.4 Bar (20 PSI)

*\*Not available with "A" option.*

Code	Seals
Omit	"D"-Ring

Code	Port Size / Body Material
8T	SAE-8 Steel (5000 PSI)

Code	Piston Type
P	Pilot Piston without seal
A	Pilot Piston with seal Note: Requires 1.4 Bar (20 PSI) crack minimum.

Kit	Part Number
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description


Cartridge Style Dual Pilot Operated Check Valve.  
 For additional information see Technical Tips on pages CV2-CV3.

## Features

- Hardened, precision ground parts for durability
- Cost effective-replaces two cartridges
- Internal pilot position
- Common cavity
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	19 LPM (5 GPM)
Maximum Inlet Pressure	207 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) at 350 Bar (5000 PSI)
Pilot Ratio	3:1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.05 kg (0.11 lbs.)
Cavity	C08-4 (See BC Section for more details)



## Dimensions



## Ordering Information

**CPD084P**

**08 Size**

**Dual P.O. Check Valve**

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Seals
Omit	<b>Nitrile</b>

Kit	Part Number
Nitrile Seal	SK08-4
Fluorocarbon Seal	SK08-4V



*Order Bodies Separately  
 See section BC*

<b>B08</b>	—	<b>4</b>	—	<b>6T</b>
08 size		4-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)



Shuttle Valves

SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.	
Technical Tips.....					SH2	
	KSWA3 .....	SW-3 .....	Ball Insert Type .....	9.5/2.5 .....	420/6000.....	SH3
	CSH041 .....	C04-3 .....	Cartridge Shuttle .....	3.8/1.0 .....	345/5000.....	SH4
	CSH101B.....	C10-3 .....	Cartridge Shuttle .....	38/10 .....	207/3000.....	SH5
	K04C3.....	C10-4.....	Spool Type, Spring Centered, All Ports Closed.....	100/26 .....	420/6000.....	SH6



CV	Check Valves
SH	Shuttle Valves
LM	Load/Motor Controls
FC	Flow Controls
PC	Pressure Controls
LE	Logic Elements
DC	Directional Controls
SV	Solenoid Valves
PV	Proportional Valves
CE	Coils & Electronics
BC	Bodies & Cavities
TD	Technical Data

**INTRODUCTION:**



Shuttle valves accept flow from two different sources and divert the highest pressure to a single outlet port. Shuttle valves are commonly used in Load Sensing circuits as well as Brake circuits. Parker offers a selection of ball and spool type Shuttle valves. There are both cartridge and insert type configurations available.

**Ball Type - Cartridge Style**

The valve consists of a steel ball that can seal against one of two adjacent seats, providing a path from the highest pressure signal to another function. When one inlet port is pressurized, the ball or poppet is forced against the opposite seat, blocking that inlet and providing a flow path to the outlet port.



**3 Way 2 Position** Spool type shuttles are designed to direct flow in such a way as to allow higher pressure signals to open the lower pressure port and connect it to the common outlet port. These spring centered valves will shift when pressure at either end of the spool exceeds the spring setting. These are typically used in transmission hot oil shuttle circuits.

**CV**Check  
Valves**SH**Shuttle  
Valves**LM**Load/Motor  
Controls**FC**Flow  
Controls**PC**Pressure  
Controls**LE**Logic  
Elements**DC**Directional  
Controls**SV**Solenoid  
Valves**PV**Proportional  
Valves**CE**Coils &  
Electronics**BC**Bodies &  
Cavities**TD**Technical  
Data

## General Description


Ball Type, Two Position, Three Way Shuttle Valve.  
 For additional information see Technical Tips on page SH2.

## Features

- Compact, cost efficient design
- Ball type construction for maximum durability
- Minimal leakage - less than 10 drops/min.
- Contamination tolerant
- Hardened working parts for maximum durability
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications


Rated Flow	9.5 LPM (2.5 GPM)
Nominal Flow @ 7 Bar (100 PSI)	5 LPM (1.32 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Cartridge Material	All parts steel. All operating parts, hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile, Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.1 kg (0.02 lbs.)
Cavity	CAVSW-3 (See BC Section for more details)



## Dimensions



## Application



## Ordering Information

**KSWA3**

Shuttle Valve

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30523N-1
Fluorocarbon Seal	SK30523V-1

## General Description

Cartridge Style Shuttle Valve.


For additional information see Technical Tips on page SH2.

## Features

- Hardened working parts for maximum durability
- Rapid response to load direction changes
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	3.8 LPM (1 GPM)
Maximum Pressure Inlet	345 Bar (5000 PSI)
Leakage at 150 SSU (32cSt)	5 drops/min. (0.33 cc/min.)
Cartridge Material	All parts steel. All operating parts, hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile, Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.2 kg (0.04 lbs.)
Cavity	C04-3 (See BC Section for more details)



## Dimensions



## Ordering Information

**CSH041**

04 Size Shuttle Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Seals
Omit	<b>Nitrile</b>

Kit	Part Number
Nitrile Seal	SK04-3
Fluorocarbon Seal	SK04-3V

Order Bodies Separately  
 See section BC

<b>B04</b>	—	<b>3</b>	—	<b>4T</b>
04 size		3-Way Cavity		Port Size

Code	Porting / Body Material
4T	SAE-8 / Steel (5000 PSI)

## General Description

Cartridge Style Shuttle Valve.


For additional information see Technical Tips on page SH2.

## Features

- Hardened precision ground parts for durability
- 5000 PSI rated
- All external parts zinc plated




## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	38 LPM (10 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32cSt)	10 drops/min. (0.67 cc/min.) at 350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts, hardened steel.
Operating Temp. Range/Seals	-45°C to +93.3°C ("D"-Ring) (-50°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.38 kg (0.85 lbs.)
Cavity	C10-3 (See BC Section for more details)



## Dimensions



## Ordering Information

### CSH101B

10 Size Shuttle Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Seals
Omit	'D' Ring

Kit	Part Number
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

Order Bodies Separately  
 See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size
Code	Porting / Body Material			
8T	SAE-8 / Steel (5000 PSI)			



## General Description


Two Position, Three Way, Spring Centered Shuttle Valve. For additional information see Technical Tips on page SH2.

## Features


- High flow capacity
- Various switching pressures available
- Use as purge valve in transmission systems
- Hardened working parts for maximum durability
- All external parts zinc plated

## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)





## Application



Purge valve in transmission circuit


## Specifications

Rated Flow	100 LPM (26 GPM)
Nominal Flow @ 7 Bar (100 PSI)	55 LPM (15 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Cartridge Material	All parts steel. All operating parts, hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile, Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.17 kg (0.37 lbs.)
Cavity	C10-4 (See BC Section for more details)



## Dimensions

Millimeters (Inches)



## Ordering Information

<b>K04C3</b>	<b>10.0</b>	<b>N</b>
Shuttle Valve	Switching Pressure	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Switching Pressure
10.0	10.0 Bar (145 PSI)

**Note:** Port 1 on the Line Body must be plugged



Code	Seals
N	Nitrile

Order Bodies Separately  
 See section BC

Kit	Part Number
Nitrile Seal	SK30504N-1
Fluorocarbon Seal	SK30504V-1

<b>B10</b>	<b>4</b>	<b>8T</b>
10 size	4-Way Cavity	Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

	SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
			Technical Tips.....			LM2-LM5
			<b>STANDARD PILOT ASSISTED</b> E2*1 <b>(NEW)</b> ..... CAVT11A.....load Control Cartridge Valve .....60/16 ..... 350/5000 ..... LM6-LM7 E2*1R <b>(NEW)</b> .... CAVT11A.....load Control Cartridge Valve .....60/16 ..... 350/5000 ..... LM8-LM9 E2*1S <b>(NEW)</b> .... CAVT11A.....load Control Cartridge Valve .....60/16 ..... 350/5000 ..... LM10-LM11 CB101 ..... C10-3 .....load Control Cartridge Valve .....45/12 ..... 380/5500 ..... LM12-LM13 MHC-010-S*** .... CDD-1010.....Load Control Cartridge Valve .....37/10 ..... 350/5000 ..... LM14-LM15 E2*020 ..... 53-1 .....Load Control Cartridge Valve .....20/5.3 ..... 420/6000 ..... LM16-LM17 E2*040 ..... 68-1 .....Load Control Cartridge Valve .....60/16 ..... 350/5000 ..... LM18-LM19 E2*060 ..... 3C.....Load Control Cartridge Valve .....120/32 ..... 350/5000 ..... LM20-LM21 E2*125 ..... 3M.....Load Control Cartridge Valve .....200/53 ..... 350/5000 ..... LM22-LM23 E2*300 ..... 3K Flange .....Load Control Cartridge Valve .....350/92 ..... 350/5000 ..... LM24-LM25			
			<b>INDEPENDENT OF BACK-PRESSURE, VENTED TO ATMOSPHERE</b> E6B020 ..... 53-1 .....Load Control Cartridge Valve, 4.5:1 Ratio .....20/5.3 ..... 350/5000 ..... LM26-LM27 E6K020..... 53-1 .....Load Control Cartridge Valve, 15:1 Ratio .....20/5.3 ..... 420/6000 ..... LM28-LM29 E6B040 ..... 68-1 .....Load Control Cartridge Valve, 3:1 Ratio .....60/16 ..... 350/5000 ..... LM30-LM31 E6B060*409 ..... 3C.....Load Control Cartridge Valve, 3:1 Ratio .....180/48 ..... 350/5000 ..... LM32-LM33			

CV Check Valves
SH Shuttle Valves
LM Load/Motor Controls
FC Flow Controls
PC Pressure Controls
LE Logic Elements
DC Directional Controls
SV Solenoid Valves
PV Proportional Valves
CE Coils & Electronics
BC Bodies & Cavities
TD Technical Data

## Introduction

Counterbalance valves are one of the most misunderstood products in the hydraulic industry. Many people tend to complicate the task of selecting a counterbalance valve and as such avoid opportunities. The goal of this Technical Tips Section is to hopefully eliminate some of this confusion and help you choose the correct valve for your application. It is only a guide! It is not meant to be your only method of input, nor is it meant to replace good hydraulic common sense and reasoning.

## Application

### DO I NEED A COUNTERBALANCE VALVE?


A counterbalance is generally used for one or more of the following purposes:

**Control an Overrunning Load** – It restricts the flow from an actuator, thus forcing the load to be pushed through the restriction and providing control of the potential runaway load. This also helps in the prevention of cavitation.

**Control in Critical Metering Applications** – The outward restriction also helps to gain control of systems with varying loads and speeds.

**Holding a Load** – Much like a pilot operated check valve, a load is held in one direction until the appropriate pilot pressure is available unseat the check and pass fluid.

**Help Protect Against Hose Failures** – Since the fluid must be pushed through a restriction, hose failures result in a controlled movement of the actuator and not a runaway load.




**NOTE:** Counterbalance Valves are only needed if the application calls for varying loads or varying speeds. If the load and speed are fixed, flow control valves and pilot operated check valves may be substituted at generally a lower cost.

## Operation

An understanding of the general operation of a counterbalance valve is required before proceeding further into valve selection.

The counterbalance valve is a pressure control device and functions as follows: Pressure is developed at the Work Port of the holding valve when the actuator is pressurized. This pressure acts on the differential area, and the force generated is counteracted by the bias spring. When there is sufficient pressure present to overcome the spring setting, the poppet begins to shift, allowing fluid to pass through the valve port to tank via the control valve.

To assist in the shifting of the poppet, an external pressure source (generally the opposite side of the actuator) is connected to the pilot port of the counterbalance valve. This pressure is applied to the pilot area and assists the differential area in opening the valve. The pilot assist reduces load pressure required to open the valve, and allows for a reduction in the horsepower required to move the load. If the load attempts to “run away” (move faster than the pump can supply flow), the pilot signal will diminish and the piston will begin to close restricting flow to tank and thus controlling the load. The counterbalance piston will maintain a position that maintains a positive pilot signal and will control the descent of the load.



An added feature of the counterbalance valve is its built-in thermal relief characteristic. A temperature rise can cause thermal expansion of the hydraulic fluid trapped between the actuator and the counterbalance valve's poppet. As the pressure increases and reaches the bias spring setting, the poppet unseats and a few drops of oil are allowed to escape through the valve port of the counterbalance valve. This relieves the thermal expansion of oil, allowing the counterbalance valve to continue holding the load in the same position.

When the flow is reversed to the actuator, then pressure unseats the built-in bypass check portion of the counterbalance valve allowing flow to pass from the valve port to the work port. When no pressure is applied to either port of the counterbalance valve, the load is held in place.

## Technical Tips

### Valve Series

Parker offers the four series of products outlined below:

**MHC** – The MHC series is a threaded cartridge style counterbalance valve. This series is ideal for incorporating into an integrated manifold or for installation directly into the port of the actuator. There are various flow rates and pilot ratios available for the MHC Series.

**CB101** – The CB101 is also a threaded cartridge style counterbalance valve. It also is ideal for incorporating into an integrated manifold or for installation directly into the port of the actuator. The CB101 has an industry common cavity (C10-3) and is available in three pilot ratios.

**E2 Series** – The E2 Series valves are threaded cartridge style counterbalance valves. They are available in standard and Vented configurations. In the Vented configurations, the valves maintain their settings regardless of backpressure. There are various flow rates and pilot ratios available.


### Selecting Options

Below is a brief description of the options available on the ordering information pages and a brief explanation of when each would be used.

**Flow Selection** – Generally the counterbalance valve is sized according to the actual flow the valve will see and not the system flow. Note that the ordering information callout is the nominal flow rate and not the maximum. In other words, refer to the pressure drop curves when sizing the valves. For example: A MHC-010 can flow 25 GPM, but is rated as a 10 GPM valve. It is possible to oversize a counterbalance valve! If the counterbalance is oversized, the annulus between the poppet and the seat is too large, thus the poppet opens too far causing instability. Remember you are gaining control by causing a restriction. If you oversize the counterbalance valve, the restriction is reduced and so is the control.

**Vented versus Non-Vented** – With a standard counterbalance valve, the bias spring is internally vented to tank. This means any pressure on the tank line is sensed in the bias spring chamber and additive to the setting. Thus, the pressure at the work port now must be greater than the bias spring plus the tank

## Load and Motor Control Valves




pressure before the counterbalance poppet will shift allowing flow.


A vented style counterbalance valve relieves the bias spring chamber to atmosphere. Thus, the spring chamber is in no way related to the tank chamber of the counterbalance valve. So, if the pressure on the tank line is high, or if the pressure setting is critical, then a vented style counterbalance valve would be required.

Parker's counterbalance valves are externally vented. This means no extra porting or manifold costs are incurred when a vented counterbalance is needed.

**MHC-010-S\*S\*** Non-Vented Counterbalance Adjustable



**MHC-010-V\*S\*** Vented Counterbalance Adjustable




CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## Technical Tips

### Selection Options (Continued)

**Pilot Ratio** – The pilot ratio is the ratio of the pilot area versus the differential area poppet. Thus, the higher the pilot ratio, the less pressure that is needed to assist the load pressure in unseating the poppet. This means there is less restriction to the overrunning load, resulting in less horsepower required and more control of the load. So higher pilot ratio equates to less restriction to the overrunning load, less control and less horsepower required. Lower ratio equates to more restriction to the overrunning load, more control and more horse-power required. The pilot ratio decision is one of Horsepower versus Control. For reference the most popular ratio is 3:1.



#### Sample Ratios:

##### 10:1

Primary function is motor control and hose break protection  
Loads moving at fast speeds and positioning is not critical

##### 7.5:1, 6:1 and 5:1

**Most popular starting ratio**

##### 4:1 and 3:1

Positioning is critical such as a pick and place application  
Greater stability

##### 1:1 Motor control application

### ADJUSTMENT TYPE

Parker offers counterbalance valves with adjustable and non-adjustable pressure settings. The non-adjustable or shimmed version is recommended for most applications as it prevents tampering or improper adjustment by uneducated end users.

### SELECTING SETTINGS

There are three basic settings to consider before finalizing a counterbalance valve for your application.

**Holding Setting** – The holding setting is sometimes referred to as the counterbalance setting. It is the maximum load setting you expect the counterbalance to hold. Note that the counterbalance valve should be set for the absolute maximum hold pressure required. Also note that counterbalance valves are restrictive type devices and as such are not ideal for low pressure applications, such as those below 750 psi. The holding setting is the setting you choose when selecting a counterbalance valve.

## Load and Motor Control Valves

**Thermal Setting** – Counterbalance valves have a built-in thermal relief valve that compensates for the expansion of oil, due to temperature, by bleeding off excess pressure. In other words, the thermal setting is the pressure that the counterbalance will unload at if no pressure is present at the pilot port. Obviously, this setting should be above the holding setting. The Parker **MHC** counterbalance valves are automatically set 1000 psi above the holding setting of the valve.

**You do not specify this setting, only the holding setting.**

For the **CB101** Series, you do specify the Thermal/Crack setting in the model code. The holding setting (maximum load induced pressure) is 70% of that specified setting. Example: Hold at 3000 psi, crack at 4285 psi. For the **E2** Series, you specify the Thermal/Crack setting in the model code. The crack setting (maximum load induced pressure) should be 1.3 times the hold. Example: Hold at 210 Bar, crack at 273 Bar.

**Pilot Area** – The pilot pressure required to lower the cylinder when fully loaded and unloaded can also be determined before applying the valve. The pilot pressure can be determined by the below equation:

$$P_p = (T_s - L) / R_p$$

$P_p$  = Pilot Pressure

$T_s$  = Thermal Setting


$L$  = Induced Load

$R_p$  = Pilot Ratio

#### Example:

The maximum load is 3000 psi. A 6:1 Pilot Ratio was chosen and the thermal relief setting is the standard 1000 psi over load setting. What is the pilot pressure required to retract the cylinder if it is fully loaded?

What pilot pressure is required to retract the cylinder if there is no load?



#### FULLY LOADED:

$$P_p = (4000 \text{ psi} - 3000 \text{ psi}) / 6$$

$$P_p = 1000 \text{ psi} / 6$$

$$P_p = 167 \text{ psi}$$

Thus, any time the pilot line sees at least 167 psi, the cylinder could lower the load.

#### UNLOADED:

$$P_p = (4000 \text{ psi} - 0 \text{ psi}) / 6$$

$$P_p = 4000 \text{ psi} / 6$$

$$P_p = 667 \text{ psi Bar}$$

Thus, at least 667 psi will be needed to lower the cylinder when it is unloaded.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data



## Technical Tips


### Motor Controls

Counterbalance valves are used in motor circuits to stop overrunning loads and prevent cavitation. Since hydraulic motors leak internally, the counterbalance valve by itself cannot be used to hold the load. So, a mechanical brake is used to hold the load on the motor in place, as shown below. Some typical applications include winches, swing drives, conveyor control and traction drives. For applications in closed loop motor circuits, vented spring cavities are required.

### Operation

Free flow to the motor is allowed through the internal check valve. In the controlled flow direction, the oil passes across a metering poppet. The position of the metering poppet is determined by an external pilot signal from the other side of the motor. In an open loop motor circuit, this pilot signal will be a 1:1 ratio. The reason an equal ratio pilot signal is utilized is to provide positive control as well as to release mechanical brakes (when used in a braking circuit). In applications where the motor will see overrunning loads in both directions (such as a traction drive circuit), a dual MMB or two single MMB valves must be used.

### Brake Applications



When the directional control valve is shifted, hydraulic pressure (usually 300 psi) releases the mechanical brake and allows the load to be moved. The counterbalance valve needs to provide adequate back pressure to open the brake, then immediately counterbalance the load. Ideally, the brake will be disengaged before the motor begins to rotate. If this sequence is not achieved, the motor will try to rotate against the applied brake reducing the life of the brake. This would be the equivalent of trying to drive with your emergency brake applied. Remember that hydraulic motors are equal area devices. So, in an effort to avoid the

## Load and Motor Control Valves

movement of the motor prior to the release of the brake, an equal area ratio counterbalance is used. To demonstrate let's look again at the above example with a 10:1 Ratio Counterbalance valve installed and a maximum thermal setting of 3000 psi.

### 10:1 Example

#### NO LOAD

$$P_p = (T_s - L) / R_p$$

$$P_p = (3000 \text{ psi} - 0 \text{ psi}) / 10$$

$$P_p = 3000 \text{ psi} / 10$$

$$P_p = 300 \text{ psi}$$

#### 2000 PSI LOAD

$$P_p = (T_s - L) / R_p$$

$$P_p = (3000 \text{ psi} - 2000 \text{ psi}) / 10$$

$$P_p = 1000 \text{ psi} / 10$$

$$P_p = 100 \text{ psi}$$

Thus, when there is no load on the motor, the counterbalance opens at 300 psi, or just as the brake is being released. When there is a 2000 psi load on the motor, the counterbalance will start to open with a pilot pressure of 100 psi. The brake requires 300 psi, so the motor can start to rotate before the brake is released, causing wear on the brake. To offset this problem, you could increase the maximum thermal setting to 5000 psi, but this is very inefficient.

### 1:1 (Equal Area) Example

Equal area counterbalance valves are used primarily in brake applications to avoid the wear problem described above. With an Equal Area counterbalance valve, there is no thermal relief valve, and there is no differential area to work on. In other words, the counterbalance valve only opens when the pilot pressure is greater than the valve setting. The applied load has nothing to do with the pilot pressure required. Thus you will want to choose a pressure setting for the equal area counterbalance valve that is just slightly above the brake release pressure (usually 350 psi).

In our example, the valve would be set at 350 psi. This would allow the brake to release before the counterbalance allows the load to move. Since the equal counterbalance valve always opens at 350 psi pilot pressure and is not dependent on the load, it is the best valve for brake applications.

**Large Pressure Spike Application** – Keep in mind that equal area counterbalance valves do not have a built-in thermal relief valve. As such, if there are large pressure spikes caused by the stopping of heavy loads, then a ratioed counterbalance, such as a 10:1 should be used. In most cases these are non-brake type applications.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data

## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications.




For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Fully sealed pilot for high efficiency and accurate pilot ratio
- Three pilot ratios available, 1.5 : 1, 3 : 1, and 4.5 : 1
- Hardened working parts for maximum durability
- All external parts zinc plated


## Specifications

Rated Flow	60 LPM (16 GPM)
Pressure	40-350 Bar (580-5000 PSI)
Sensitivity: Pressure/Turn	104 Bar (1508 PSI)
Pilot Ratio	E2E1 - 1.5 : 1 E2K1 - 3 : 1 E2M1 - 4.5 : 1
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) @ 75% of thermal crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.17 kg (0.37 lbs.)
Cavity	CAVT11A (See BC Section for more details)




## Performance Curves

### Relief Performance 1 to 2




## Pressure Drop vs Flow



## Required Piloted Pressure Calculation


$$P_3 = \left( \frac{P_C - P_1}{P_R} \right) + P_2 * \left( \frac{1}{P_R} + 1 \right)$$

$P_C$  = Crack Pressure Setting  
 $P_R$  = Pilot Ratio





Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>1</b>	<b>Z</b>	<b>N</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
E	1.5 : 1
K	3 : 1
M	4.5 : 1

Code	Adjustment Style
Z	Screw Adjust (standard)

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>825</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
825	1/2" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30008N-1
Fluorocarbon Seal	SK30008V-1

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Threaded Cartridge Style Counterbalance Valve, Restrictive Ports 2 to 3. Pilot assisted, designed for motion control applications.




For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Fully sealed pilot for high efficiency and accurate pilot ratio
- Two pilot ratios available, 3:1 for cylinders and 4.5:1 for motion control
- Hardened working parts for maximum durability
- All external parts zinc plated


## Specifications

Rated Flow	Free flow 60 LPM (16 GPM) Piloted open flow 38 LPM (10 GPM)
Pressure	90-350 Bar (1305-5000 PSI)
Sensitivity: Pressure/Turn	104 Bar (1508 PSI)
Pilot Ratio	E2K1R - 3 : 1 E2M1R - 4.5 : 1
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) @ 75% of thermal crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.17 kg (0.37 lbs.)
Cavity	CAVT11A (See BC Section for more details)




## Performance Curves

### Relief Performance 1 to 2




## Pressure Drop vs. Flow



## Required Piloted Pressure Calculation

$$P_3 = \left( \frac{P_C - P_1}{P_R} \right) + P_2 * \left( \frac{1}{P_R} + 1 \right)$$

$P_C$  = Crack Pressure Setting  
 $P_R$  = Pilot Ratio



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics

**BC**


Bodies &  
Cavities

**TD**

Technical  
Data



Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>1R</b>	<b>Z</b>	<b>N</b>
Load Control Valve	Pilot Ratio	Adjustment Style	Seals	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
<b>K</b>	<b>3 : 1</b>
M	4.5 : 1

Code	Seals
<b>N</b>	<b>Nitrile</b>

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (standard)</b>

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>825</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
825	1/2" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30008N-1
Fluorocarbon Seal	SK30008V-1

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



## General Description




Threaded Cartridge Style Counterbalance Valve, Semi-Restrictive Ports 2 to 3. Pilot assisted, designed for motion control applications. For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Excellent control and very good stability
- Fully sealed pilot for high efficiency and accurate pilot ratio
- Three pilot ratios available, 1.5:1, 3:1 and 4.5:1
- Hardened working parts for maximum durability
- All external parts zinc plated


## Specifications

Rated Flow	Free flow 60 LPM (16 GPM) Piloted open flow 38 LPM (10 GPM)
Pressure	40-350 Bar (580-5000 PSI)
Sensitivity: Pressure/Turn	104 Bar (1508 PSI)
Pilot Ratio	E2E1S - 1.5 : 1 E2K1S - 3 : 1 E2M1S - 4.5 : 1
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) @ 75% of thermal crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.17 kg (0.37 lbs.)
Cavity	CAVT11A (See BC Section for more details)




## Performance Curves

### Relief Performance 1 to 2




### Pressure Drop vs. Flow



### Required Piloted Pressure Calculation


$$P_3 = \left( \frac{P_C - P_1}{P_R} \right) + P_2 * \left( \frac{1}{P_R} + 1 \right)$$

$P_C$  = Crack Pressure Setting  
 $P_R$  = Pilot Ratio





Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>1S</b>	<b>Z</b>	<b>N</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
E	1.5 : 1
K	3 : 1
M	4.5 : 1

Code	Adjustment Style
Z	Screw Adjust (standard)

Code	Seals
N	Nitrile

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30008N-1
Fluorocarbon Seal	SK30008V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>825</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
825	1/2" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.






<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Cartridge Style Counterbalance Valve.  
 For additional information see Technical Tips  
 on pages LM2-LM5.

## Features

- Sealed spool type design for improved stability and accuracy as well as low leakage
- Low leakage poppet-type check valve for reliable load holding
- All external parts zinc plated
- Parker cartridge design for ease of installation and maintenance
- Compact size for reduced space requirements




## Specifications


Rated Flow	45 LPM (12 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI) - Steel 210 Bar (3000 PSI) - Aluminium
Maximum Setting Pressure	350 Bar (5000 PSI) - Steel 210 Bar (3000 PSI) - Aluminium
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) @ 80% of thermal crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.5 lbs.)
Cavity	C10-3 (See BC Section for more details)

## Performance Curve

**Flow vs. Pressure Drop**  
 (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

<b>CB101</b>		<b>S</b>	
Counterbalance Cartridge Valve	Pilot Ratio	Adjustment Style	Pressure Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
A	3 : 1
B	4.5 : 1
C	7 : 1

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Pressure Range
<b>10</b>	<b>34.5 to 103.4 Bar (500 to 1500 PSI)</b> <b>Standard Setting:</b> <b>69 Bar (1000 PSI) @ 11.3 LPM (3 GPM)</b>
20	69 to 172.4 Bar (1000 to 2500 PSI) Standard Setting: 138 Bar (2000 PSI) @ 11.3 LPM (3 GPM)
<b>30</b>	<b>166 to 350 Bar (2400 to 5000 PSI)</b> <b>Standard Setting:</b> <b>210 Bar (3000 PSI) @ 11.3 LPM (3 GPM)</b>

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717785
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

## General Description



Threaded Cartridge Style Counterbalance Valve.  
 For additional information see Technical Tips  
 on pages LM2-LM5.

## Features

- Conical Poppet design provides longer metering stroke for stable operation
- Hardened seat provides reliable load holding
- External vent option available for high back pressure applications
- Tamper resistant cap for added safety and security
- Various pilot ratios available for application flexibility
- Unique cavity prevents other valves from being “accidentally” installed

## Specifications


Rated Flow	37.5 LPM (10 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min) @ 80% of thermal crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.38 kg (0.88 lbs.)
Cavity	CDD-1010 (See BC Section for more details)




**MHC-010-S\*S\*** Non-Vented Counterbalance Adjustable

## Construction


**MHC-010-V\*S\*** Vented Counterbalance Adjustable



**MHC-010-S\*N\*** Non-Vented Counterbalance Non-Adjustable




**MHC-010-V\*N\*** Vented Counterbalance Non-Adjustable




## Performance Curve

**Flow vs. Pressure Drop (Through cartridge only)**



**Dimensions** Millimeters (Inches)



**Torque Values**  
 68-75 Nm (50-55 lb. ft.)  
*Typical for all*

**Ordering Information**

<b>MHC</b>	—	<b>010</b>	—					—	<b>00B</b>
Counterbalance Cartridge Valve		Nominal Flow Rating		Vent Type	Pilot Ratio	Design	Holding Pressure		Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Nominal Flow Rating
010	37.5 LPM (10 GPM)

Code	Vent Type
S	Standard (non-vented)
V	Vented

Code	Pilot Ratio
F	7 : 1 (Standard)
J	10 : 1

Code	Design
S	Standard (adjustable)
N	Shimmed (non-adjustable)

Code	Holding Pressure
H	210 Bar (3000 PSI) Standard version
K	350 Bar (5000 PSI) Standard Setting: 7:1 and 10:1 only Shim version only

Code	Seals
00B	Nitrile

Kit	Part Number
Nitrile Seal	711922
Fluorocarbon Seal	711825

*Order Bodies Separately*  
 See section BC

<b>MHC</b>	—	<b>010</b>	—	<b>A</b>	—	<b>53</b>
Counterbalance Cartridge Valve		Nominal Flow Rating		Body Type		Port Size

Code	Body Type
A	Single

Code	Port Size
53	SAE-10 through port





## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications

For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Can be directly mounted into cylinder eliminating requirement for manifold block
- Fully sealed pilot for high efficiency and accurate pilot ratio
- Two pilot ratios available, 4.5:1 for cylinders and 8:1 for motor control
- All external parts zinc plated




## Specifications


Rated Flow	<b>E2A020</b> 14 LPM (3.7 GPM) <b>E2B020</b> 20 LPM (5.3 GPM)
Pressure	50 to 420 Bar (725 to 6000 PSI)
Sensitivity: Pressure / Turn	<b>E2A020</b> 113 Bar (1640 PSI) <b>E2B020</b> 84 Bar (1220 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.17 lbs.)
Cavity	53-1 (See BC Section for more details)

## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>020</b>	<b>Z</b>	<b>N</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
A	8 : 1
B	4.5 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30087N-1
Fluorocarbon Seal	SK30087V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>318</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
318	3/8" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control  
applications

For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Two pilot ratios available, 3:1 for cylinders and 8:1 for motor control
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications


Rated Flow	60 LPM (15.9 GPM)
Pressure	50 - 350 Bar (725 - 5000 PSI)
Sensitivity: Pressure / Turn	99 Bar (1435 PSI)
Pilot Ratio	<b>E2A040</b> - 8 : 1 <b>E2B040</b> - 3 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.27 kg (0.6 lbs.)
Cavity	68-1 (See BC Section for more details)

## Performance Curves


## Relief & Pilot Performance 1 to 2



## Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>040</b>	<b>Z</b>	<b>N</b>	<b>MK3</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
A	8 : 1
B	3 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30059N-1
Fluorocarbon Seal	SK30059V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>253</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
253	1/2" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.



## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications

For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Excellent control and very good stability
- Three pilot ratios available, 1.75:1 and 3:1 for cylinders and 8:1 for motor control
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications


Rated Flow	120 LPM (32 GPM)
Pressure	50 - 350 Bar (725 - 5000 PSI)
Sensitivity: Pressure / Turn	44 Bar (640 PSI)
Pilot Ratio	<b>E2A060</b> - 8 : 1 <b>E2B060</b> - 3 : 1 <b>E2H060</b> - 1.75 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.54 kg (1.19 lbs.)
Cavity	3C (See BC Section for more details)

## Performance Curves


Relief & Pilot Performance 1 to 2



Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>060</b>	<b>Z</b>	<b>N</b>	<b>MK2</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
A	8 : 1
B	3 : 1
H	1.75 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30008N-1
Fluorocarbon Seal	SK30008V-1

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>069</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
069	1" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data





## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications

For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection, and reverse check valve, saving space and minimizing installation cost
- Two pilot ratios available, 3:1 for cylinders and 8:1 for motor control
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications


Rated Flow	200 LPM (53 GPM)
Pressure	50 - 350 Bar (725 - 5000 PSI)
Sensitivity: Pressure / Turn	34 Bar (493 PSI)
Pilot Ratio	<b>E2A125</b> - 8 : 1 <b>E2E125</b> - 3 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.75 kg (1.65 lbs.)
Cavity	3M (See BC Section for more details)

## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>125</b>	<b>Z</b>	<b>N</b>	<b>MK2</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
A	8 : 1
E	3 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30035N-1
Fluorocarbon Seal	SK30035V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>078</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
078	1" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data




## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications

For additional information see Technical Tips on pages LM2-LM5.

## Features

- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection, and reverse check valve, saving space and minimizing installation cost
- Two pilot ratios available, 3:1 for cylinders and 8:1 for motor control
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications


Rated Flow	350 LPM (92 GPM)
Pressure	50 to 350 Bar (725 to 5000 PSI)
Sensitivity: Pressure / Turn	45 Bar (653 PSI)
Pilot Ratio	<b>E2A300</b> - 8 : 1 <b>E2C300</b> - 3 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	1.44 kg (3.17 lbs.)
Cavity	3K (See BC Section for more details)

## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E2</b>		<b>300</b>	<b>Z</b>	<b>N</b>	<b>MK2</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
A	8 : 1
C	3 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30022N-1
Fluorocarbon Seal	SK30022V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>089</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
089	1-1/4" BSP (main) 1/4" BSP (aux)

Code	Body Material
S	Steel /(5000PSI)

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.

## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications



For additional information see Technical Tips on pages LM2-LM5.

## Features

- Spring chamber isolated from system backpressure by double seal, eliminating vent port leakage and need for separate drain line
- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body
- Small and compact, can be fitted directly into cylinder
- All external parts zinc plated


## Specifications

Rated Flow	20 LPM (5.3 GPM)
Pressure	50 to 420 Bar (725 to 6000 PSI)
Sensitivity: Pressure / Turn	84 Bar (1220 PSI)
Pilot Ratio	4.5 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.18 lbs.)
Cavity	53-1 (See BC Section for more details)




## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E6</b>	<b>B</b>	<b>020</b>	<b>Z</b>	<b>N</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
B	4.5 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30087N-1
Fluorocarbon Seal	SK30087V-1

*\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.*

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>318</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
318	3/8" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data





## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications  
For additional information see Technical Tips on pages LM2-LM5.

## Features

- Spring chamber isolated from system backpressure by double seal, eliminating vent port leakage and need for separate drain line
- Poppet construction for minimal leakage
- Suitable for remote pilot controlled boomlock applications as per ISO8463
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications


Rated Flow	20 LPM (5.3 GPM)
Pressure	100 - 350 Bar (1450 - 5075 PSI)
Sensitivity: Pressure / Turn	114 Bar (1650 PSI)
Pilot Ratio	15 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.18 lbs.)
Cavity	53-1 (See BC Section for more details)

## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E6</b>	<b>K</b>	<b>020</b>	<b>Z</b>	<b>N</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
K	15 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30087N-1
Fluorocarbon Seal	SK30087V-1

*\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.*

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>318</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
318	3/8" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel /(5000PSI)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Threaded Cartridge Style Counterbalance Valve.  
Pilot assisted, designed for motion control applications  
For additional information see Technical Tips on pages LM2-LM5.

## Features

- Spring chamber isolated from system backpressure by double seal, eliminating vent port leakage and need for separate drain line
- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications


Rated Flow	60 LPM (15.9 GPM)
Pressure	50 to 350 Bar (725 to 5075 PSI)
Sensitivity: Pressure / Turn	92 Bar (1335 PSI)
Pilot Ratio	3 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.33 kg (0.73 lbs.)
Cavity	68-1 (See BC Section for more details)

## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E6</b>	<b>B</b>	<b>040</b>	<b>Z</b>	<b>N</b>	<b>MK3</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
B	3 : 1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30059N-1
Fluorocarbon Seal	SK30059V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>253</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
253	1/2" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description




Threaded Cartridge Style Counterbalance Valve.  
 Pilot assisted, designed for motion control applications  
 For additional information see Technical Tips on pages LM2-LM5.

## Features

- High flow design with extra dampening
- Spring chamber isolated from system backpressure by double seal, eliminating vent port leakage and need for separate drain line
- Poppet construction for minimal leakage
- Incorporates direct acting relief valve for overload protection
- Includes reverse check valve within body, saving space and minimizing installation cost
- Hardened working parts for maximum durability
- All external parts zinc plated


## Specifications

Rated Flow	180 LPM (48 GPM)
Pressure	50 to 350 Bar (725 to 5000 PSI)
Sensitivity: Pressure / Turn	50 Bar (725 PSI)
Pilot Ratio	3 : 1
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.53 kg (1.17 lbs.)
Cavity	3C (See BC Section for more details)




## Performance Curves


### Relief & Pilot Performance 1 to 2



### Pressure Drop vs Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>E6</b>	<b>B</b>	<b>060</b>	<b>Z</b>	<b>N</b>	<b>409</b>
Load Control Valve	Pilot Ratio		Adjustment Style	Seals	Suffix Number

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pilot Ratio
B	3:1

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust (Standard)</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Code	Suffix Number
409	High flow design with extra dampening

Kit	Part Number
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30008N-1
Fluorocarbon Seal	SK30008V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>069</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
069	1" SAE (main) 1/4" SAE (aux)







Code	Body Material
S	Steel /(5000PSI)

\*Standard valve is set to crack at 215 Bar (3120 PSI). Valve to be set to 1.3 times maximum load induced pressure.



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



	SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
	Technical Tips.....					FC2-FC5
	<b>NEEDLE VALVES</b>					
	NVH081	C08-2	Needle Valve, Cartridge Type	38/10	380/5500	FC6-FC7
	NVH101	C10-2	Needle Valve, Cartridge Type	60/16	380/5500	FC8-FC9
	FV101	C10-2	Needle Valve with Reverse Check, to 2 Free Flow	45/12	210/3000	FC10-FC11
	FV102	C10-2	Needle Valve with Reverse Check, 1 to 2 Free Flow	23/6	210/3000	FC10-FC11
	<b>PRESSURE COMPENSATED FLOW CONTROLS</b>					
	J02E2	C08-2	Restrictive Flow Control, Adjustable	20/5.3	420/6000	FC12-FC13
	J04E2	C10-2	Restrictive Flow Control, Adjustable	40/10	420/6000	FC14-FC15
	FA101	C10-2	Restrictive Flow Control, Reverse Check, Adjustable	21/5.5	210/3000	FC16-FC17
	FC101	C10-2	Restrictive Flow Control, Reverse Check, Tuneable	56/15	210/3000	FC18-FC19
	<b>PRESSURE COMPENSATED PRIORITY FLOW CONTROLS</b>					
	J02D3	C08-3	Priority Type, with Bypass	15/4	420/6000	FC20-FC21
	J04D3	C10-3	Priority Type, with Bypass	70/18	420/6000	FC22-FC23
	J1A125	3A	Priority Type, with Bypass	150/40	420/6000	FC24-FC25
	<b>FLOW DIVIDERS/COMBINERS</b>					
	L04A3	C10-4	Flow Divider/Combiner	60/16	420/6000	FC26-FC27
	L06A3	C16-4	Flow Divider/Combiner	180/47	420/6000	FC28-FC29

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## INTRODUCTION


This technical tips section is designed to help familiarize you with the Parker line of Flow Control Valves. In this section we present common options available as well as a brief synopsis of the operation and applications of the various product offered in this section. The intent of this section is to help you in selecting the best products for your application.

## COMMON OPTIONS


As you will see, Parker offers a variety of Flow Control products. As such, some of the options mentioned below may not be available on all valve models. Consult the model coding and dimensions of each valve for specifics. Here are some of the common options available.

**Adjustment Types:** Parker offers four primary types of adjustments for most of the flow control products. Samples of these types are shown below. Please note all options may not be available for all valves. Consult the individual catalog pages for more details.


**Screw Adjustment** - Valve can be adjusted with an allen wrench. Lock nut included to maintain desired setting after adjustment. This is the most common adjustment option available on most Parker products.




**Knob Adjustment** - An aluminum knob is added to the standard screw adjustment. A lock knob is provided to help maintain the desired setting after adjustment. Parker offers knob conversion kits for most flow control valves. For kit numbers consult the individual valve pages.



**Fixed Style** - In most cases, the Fixed Style product is a screw adjustable product with a steel collet threaded over the adjustment. These valves are preset at the factory. Should the valve need to be adjusted, the star washer and aluminum plate can be removed from the top of the assembly exposing the adjustment.




**Tamper Resistant** - The tamper resistant option is a screw adjustable valve with a steel cap installed to conceal the adjustment. The cap is designed so the internal edges clamp into the groove of the valve adapter. Once the cap is installed, it cannot be removed without damaging the cap and the valve. When a valve is ordered with the tamper resistant option, it will be preset at the factory, and the cap will be included in a separate plastic bag to allow for fine tuning at the customer site. Parker offers tamper re-sistant cap conversion kits for most flow control valves. For kit numbers consult the individual valve pages.




**Seals:** Valves feature either a 4301 Polyurethane “D”-Ring. The “D”-Ring eliminates the need for backup rings. The majority of the products are also available in Nitrile or Fluorocarbon seals. Contact factory for availability. You should match the seal compatibility to the temperature and fluid being used in your application.

**Fine Meter Options:** Fine meter needles are offered on some needle valve series. When this option is specified, the standard needle is replaced by a slotted needle. The slotted needle restricts substantially more flow giving you finer control in the small flow ranges. Obviously, the maximum flow capacity of the needle valve is decreased with the fine meter option.

Coarse Needle



Fine Needle



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD



Technical  
Data

## PRODUCT TYPES / APPLICATIONS

**Needle Valve**

Needle valves provide uncompensated adjustable flow control of a desired function. They are ideal for applications where general control of hydraulic flow is needed, like in a bleed off circuit.



When used with a compensator spool, a pressure compensated system can be obtained.



**OPERATION** - The valve acts as a fixed orifice in a hydraulic circuit. The effective size of the orifice increases as the tapered needle is opened. Shutoff is provided when fully closed. While a needle valve will meter flow regardless of the flow path, flow from port 2 to 1 is preferred. When you flow in the reverse direction (1 to 2), pressure forces work on the nose of the needle in an effort to drive it off of its seat. As such, all leakage conditions found in the catalog are based on flow from side to nose (port 2 to port 1). In addition, the adjustment will be harder to turn due to the added force.

**Needle with a Reverse Check**


Needle valves with reverse check functions are sometimes also referred to as flow control valves. As the name implies, these valves provide uncompensated adjustable speed control in one direction and allow free flow in the opposite direction. When used with a compensator spool, a pressure compensated system can be obtained.



**OPERATION** - With flow entering the side of the cartridge (port 2), the needle acts as a fixed orifice. The effective size of this orifice is increased as the needle is opened controlling the output flow to port 1. With flow entering the nose (port 1), the check ball inside the needle is unseated allowing free flow to port 2.

**P.C. Flow Regulator**

Pressure compensated flow regulators maintain a regulated flow regardless of changes in load or inlet pressure. They are commonly used to accurately control an actuator function. They can be used in meter-in or meter-out applications.



**OPERATION** - The valve consists of a control orifice within a normally open, spring biased compensator spool. Flow through the control orifice produces a pressure drop across the compensator spool. When inlet flow exceeds the flow setting of the valve, the force produced by the pressure differential across the spool exceeds the spring force and shifts the compensator spool to throttle or restrict flow; thus maintaining consistent flow through the valve. In the reverse direction, flow is metered, but not pressure compensated.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC



Bodies &  
Cavities

TD

Technical  
Data

**P.C. Flow Control**

Pressure compensated flow controls are pressure compensated regulators with a reverse flow check valve. They provide constant regulated flow in the one direction regardless of changes in load pressure. Flow in the reverse direction is non-regulated, free flow. They can be used in meter-in or meter-out applications.



**Adjustable Flow Controls**

Most adjustable pressure compensated flow controls have a limited adjustment range. You will see in our catalog that we use the term "tuneable" for the FR101 and FC101 valves.

This means they are only adjustable within a pre-set range.

The FA101, J02E2, J04E2 and J04C2 are fully adjustable.



Keep this adjustment capability in mind when you select a flow control.



**OPERATION** - When flow enters the nose (port 1) of the cartridge, it passes through a control orifice. This control orifice creates a pressure differential across the regulating spool. As the inlet flow increases, the pressure differential across the regulating spool increases, allowing the regulating spool to overcome its spring force and begin to shift. As it shifts, it throttles to maintain a constant flow. When used in conjunction with a fixed displacement pump, a relief valve between pump and valve is needed. Full flow is allowed in the reverse direction (port 2 to 1).

**Priority Style P.C. Flow Regulator**

Priority style pressure compensator regulators maintain constant priority flow to one leg of the circuit regardless of changes in load or inlet pressure. Once this priority flow requirement is satisfied, the excess flow is diverted and can be used in another leg of the circuit. These valves are usually used in meter-in applications.



**OPERATION** - The valve consists of a control orifice within a spring biased compensator spool. The priority port is normally open while the bypass port is normally closed. As flow enters the inlet of the cartridge and passes through the control orifice, a pressure differential is created across the compensator spool. When the inlet flow exceeds the setting of the valve, the force produced by this pressure differential exceeds the spring force and shifts the compensator spool; opening up the bypass port, and bypassing the excess flow. If load pressure at the bypass port is greater than the load pressure at the priority port, the compensator spool will further shift restricting the priority flow to that of the valve setting. **Caution:** If the priority line is blocked so that no flow can pass through the control orifice, the compensator spool will shift, blocking the bypass port and allowing inlet pressure to go to full system relief pressure. These valves do not provide a pressure relieving function, so it is common to place an external relief valve downstream of port 3 to prevent a no flow condition.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data



**Flow Divider / Combiner**

Flow divider / combiner valves are used to proportion the flow from a single source into two actuators. In the reverse mode, the valve takes the flow from the two sources and combines it into one flow.

When attempting to synchronize two cylinders

with a flow/divider combiner valve, please consider that the flow accuracy is +10%.

A crossover relief can be used to help re-synchronize the cylinders by bottoming them out after several cycles.



**OPERATION** - When flow enters the divider inlet port, it will pass through orifices in each of the interconnected spools. The flow passing through the orifices creates a pressure drop which pulls the two spools away from each other. The flow then passes to the two divider outlet ports. The division of flow (i.e. 50-50, 60-40, 66-33, etc.) is determined by the orifice sizes in the two spools. When flow is being combined, it enters the valve through two combiner inlets. The pressure drop across the orifices pulls the two spools together. The combined flow then passes through the combiner outlet.

**CV**Check  
Valves**SH**Shuttle  
Valves**LM**Load/Motor  
Controls**FC**Flow  
Controls**PC**Pressure  
Controls**LE**Logic  
Elements**DC**Directional  
Controls**SV**Solenoid  
Valves**PV**Proportional  
Valves**CE**Coils &  
Electronics**BC**Bodies &  
Cavities**TD**Technical  
Data

## General Description

Cartridge Style Needle Valve.



For additional information see Technical Tips on pages FC2-FC5.

## Features

- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- Fine adjustment needle option available for precise adjustment
- Polyurethane "D"-Ring eliminates backup rings and prevents hydrolysis
- Valve meters flow in either direction, but (2 to 1) is the preferred direction for lowest leakage at shut off
- All external parts zinc plated



## Specifications

Rated Flow	37.9 LPM (10 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.10 kg (0.20 lbs.)
Cavity	C08-2 (See BC Section for more details)




## Performance Curves

Flow vs. Inlet Pressure (Through cartridge only)






Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

NVH081

08 Size  
Needle Valve

Flow  
Needle

S

Adjustment  
Style

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Flow Needle
Omit	Coarse
F	Fine

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	"D"-Ring

Order Bodies Separately  
See section BC

B08

—

2

—

6T

08 size

2-Way  
Cavity

Port  
Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description

Cartridge Style Needle Valve.



For additional information see Technical Tips on pages FC2-FC5.

## Features

- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- Fine adjustment needle option available for precise adjustment
- Polyurethane "D"-Ring eliminates backup rings and prevents hydrolysis
- Valve meters flow in either direction, but (2 to 1) is the preferred direction for lowest leakage at shut off
- All external parts zinc plated



## Specifications

Rated Flow	60 LPM (16 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.18 kg (0.40 lbs.)
Cavity	C10-2 (See BC Section for more details)




## Performance Curves


Flow vs. Inlet Pressure (Through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

NVH101

10 Size  
Needle Valve

Flow  
Needle

S

Adjustment  
Style

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Flow Needle
Omit	Coarse
F	Fine

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	"D"-Ring

Order Bodies Separately  
See section BC

B10

10 size

—

2

2-Way  
Cavity

—

8T

Port  
Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V




CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description

Needle Valve with a Reverse Check. Also known as a Flow Control Valve.  
 For additional information see Technical Tips on pages FC2-FC5.

## Features

- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- Fine thread needle option available for precise adjustment
- All external parts zinc plated




## Specifications

Rated Flow	<b>FV101</b> 45 LPM (12 GPM) <b>FV102</b> 23 LPM (6 GPM)
Maximum Inlet Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.50 lbs.)
Cavity	C10-2 (See BC Section for more details)

## Dimensions


Millimeters (Inches)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data


## Performance Curves

### Metered Flow vs. Pressure Drop (Through cartridge only)



□ = No. of Turns CCW From Fully Closed.

The number on each curve indicates the number of complete turns of the knob or screw adjustment from fully closed. When the metered flow is 22.5 LPM (6 GPM) and the adjustment is two complete turns from closed, the pressure drop will be 13.8 Bar (200 PSI). When the metered flow is 22.5 LPM (6 GPM) and the adjustment is five complete turns from closed, the pressure drop will be 3.5 Bar (50 PSI).



□ = No. of Turns CCW From Fully Closed.

The number on each curve indicates the number of complete turns of the knob or screw adjustment from fully closed (non-metered flow). When the metered flow is 7.5 LPM (2 GPM) and the adjustment is two complete turns from closed, the pressure drop will be 156.9 Bar (2275 PSI). When the metered flow is 7.5 LPM (2 GPM) and the adjustment is 3.75 turns from closed, the pressure drop will be 56.6 Bar (820 PSI).

## Ordering Information

<b>FV10</b>		<b>S</b>
10 Size Flow Control Valve	Style	Adjustment Style

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Style
1	Coarse Flow
2	Fine Flow

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Kit	Part Number
Knob	840208K
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
 See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description

Restrictive Style, Pressure Compensated Flow Control Valve.



For additional information see Technical Tips on pages FC2-FC5.

## Features

- Minimal flow change with pressure variation
- Reverse flow function
- Full adjustment from 1-20 LPM (0.3-5.3 GPM)
- Hardened working parts for maximum durability
- All external parts zinc plated

## Specifications


Rated Flow	20 LPM (5.3 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.13 kg (0.29 lbs.)
Cavity	C08-2 (See BC Section for more details)




## Performance Curves

**Flow vs. Inlet Pressure** (Through cartridge only)

### Flow Regulating Performance




### Reverse Flow Pressure Drop vs. Flow



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



Dimensions    Millimeters (Inches)



Ordering Information

<b>J02E2</b>	<b>Z</b>	<b>N</b>
08 Size Pressure Compensated Flow Control Valve	Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
Z	Screw Adjust

Code	Seals
N	Nitrile

Standard valve has a flow setting of 10 LPM.

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Knob	ASV014975
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30501N-1
Fluorocarbon Seal	SK30501V-1

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Restrictive Style, Pressure Compensated Flow Control Valve.




For additional information see Technical Tips on pages FC2-FC5.

## Features

- Minimal flow change with pressure variation
- Reverse flow function
- Full adjustment from 1-40 LPM (0.3-10.6 GPM)
- Hardened working parts for maximum durability
- All external parts zinc plated

## Specifications


Rated Flow	40 LPM (10.6 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.20 kg (0.44 lbs.)
Cavity	C10-2 (See BC Section for more details)




## Performance Curves

**Flow vs. Inlet Pressure** (Through cartridge only)

### Flow Regulating Performance




### Reverse Flow Pressure Drop vs. Flow



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>J04E2</b>	<b>Z</b>	<b>N</b>
10 Size Pressure Compensated Flow Control Valve	Adjustment Style	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>Z</b>	<b>Screw Adjust</b>

Code	Seals
<b>N</b>	<b>Nitrile</b>

Standard valve has a flow setting of 20 LPM.

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	ASV014975
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30503N-1
Fluorocarbon Seal	SK30503V-1



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Fully Adjustable, Pressure Compensated Flow Control Valve. For additional information see Technical Tips on pages FC2-FC5.

## Features

- Fully adjustable from 0.75 LPM (0.2 GPM) to 20.6 LPM (5.5 GPM)
- Hardened, precision ground parts for durability
- All external parts are zinc plated
- Compact size for reduced space requirements




## Specifications

Rated Flow	20.6 LPM (5.5 GPM)
Maximum Inlet Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.50 lbs.)
Cavity	C10-2 (See BC Section for more details)



## Performance Curves

**Regulated Flow vs. Pressure Drop**  
 (Through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**FA101**

**S**

10 Size  
Pressure  
Compensated Flow  
Control Valve

Adjustment  
Style

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717785
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description




Pressure Compensated Flow Control.  
 For additional information see Technical Tips on pages FC2-FC5.

## Features

- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- Free flow in reverse condition
- All external parts zinc plated


## Specifications

Rated Flow	56 LPM (15 GPM)
Maximum Inlet Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.50 lbs.)
Cavity	C10-2 (See BC Section for more details)




## Performance Curves

### Regulated Flow vs. Pressure Drop (Through cartridge only)




### Pressure Drop vs. Flow (Through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



Dimensions    Millimeters (Inches)



Ordering Information

**FC101**  
10 Size  
Pressure  
Compensated Flow  
Control

**S**  
Adjustment  
Style

Flow  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Flow Range and Standard Setting
300	7.5-16.9 LPM (2.0-4.5 GPM) (11.3 LPM (3 GPM) @ 69 Bar (1000 PSI) ΔP)
600	15-30 LPM (4.0-8.0 GPM) (22.5 LPM (6 GPM) @ 69 Bar (1000 PSI) ΔP)

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

Kit	Part Number
Knob	840208K
Tamper Resistant Cap	717783
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
See section BC

**B10**  
10 size

—

**2**  
2-Way  
Cavity

—

**8T**  
Port  
Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

<b>CV</b> Check Valves
<b>SH</b> Shuttle Valves
<b>LM</b> Load/Motor Controls
<b>FC</b> Flow Controls
<b>PC</b> Pressure Controls
<b>LE</b> Logic Elements
<b>DC</b> Directional Controls
<b>SV</b> Solenoid Valves
<b>PV</b> Proportional Valves
<b>CE</b> Coils & Electronics
<b>BC</b> Bodies & Cavities
<b>TD</b> Technical Data

## General Description

Priority Type, Pressure Compensated Flow Regulator Valve.




For additional information see Technical Tips on pages FC2-FC5.

## Features

- Good adjustment from 1-15 LPM (0.3-4 GPM)
- Used for systems requiring priority flow such as steering systems
- Reverse flow function 3 to 1
- Hardened working parts for maximum durability
- All external parts zinc plated

## Specifications


Rated Flow	15 LPM (4 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.18 lbs.)
Cavity	C08-3 (See BC Section for more details)




## Performance Curves

**Flow vs. Inlet Pressure** (Through cartridge only)

### Flow Regulating Performance




## Application



Priority flow on steering circuit

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**J02D3**

Pressure  
Compensated  
Priority Flow  
Control Valve

**Z**

Adjustment  
Style

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
Z	Screw Adjust

Code	Seals
N	Nitrile

Standard valve has a flow setting of 7 LPM.

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Knob	ASV014975
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30501N-1
Fluorocarbon Seal	SK30501V-1

**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics

**BC**

Bodies &  
Cavities

**TD**

Technical  
Data

## General Description

Priority Type, Pressure Compensated Flow Regulator Valve.



For additional information see Technical Tips on pages FC2-FC5.

## Features

- High flow capacity
- Good adjustment from 2-45 LPM (0.5-12 GPM)
- Used for systems requiring priority flow such as steering systems
- Reverse flow function 3 to 1
- Hardened working parts for maximum durability
- All external parts zinc plated

## Specifications


Rated Flow	70 LPM (18 GPM)
Maximum Regulated Flow	45 LPM (12 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.18 kg (0.40 lbs.)
Cavity	C10-3 (See BC Section for more details)




## Performance Curves

**Flow vs. Inlet Pressure** (Through cartridge only)

### Flow Regulating Performance




## Application



Priority flow on steering circuit

Dimensions    Millimeters (Inches)



Ordering Information

**J04D3**

Pressure  
Compensated  
Priority Flow  
Control Valve

**Z**

Adjustment  
Style

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
Z	Screw Adjust

Code	Seals
N	Nitrile

Standard valve has a flow setting of 20 LPM.

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	ASV014975
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30505N-1
Fluorocarbon Seal	SK30505V-1

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Priority Style, Pressure Compensated Flow Regulator Valve With Bypass.




For additional information see Technical Tips on pages FC2-FC5.

## Features

- Free reverse flow function
- High flow capacity
- Used for systems requiring priority flow such as steering systems
- Hardened working parts for maximum durability
- All external parts zinc plated

## Specifications


Rated Flow	150 LPM (40 GPM)
Maximum Regulated Flow	90 LPM (24 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.45 kg (1.0 lbs.)
Cavity	3A (See BC Section for more details)




## Performance Curves

**Flow vs. Inlet Pressure** (Through cartridge only)

### Flow Regulating Performance




## Application



Priority flow on steering circuit



Dimensions    Millimeters (Inches)



Ordering Information

**J1A125**

Pressure  
Compensated  
Priority Flow  
Control Valve

**Z**

Adjustment  
Style

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>Z</b>	Screw Adjust

Code	Seals
<b>N</b>	Nitrile

Standard valve has a flow setting of 25 LPM and an Inlet flow setting of 45 LPM.

Order Bodies Separately  
See section BC

**LB10**

Line Body

**066**

Porting

**S**

Body  
Material

Code	Porting
066	SAE16 /Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30011N-1
Fluorocarbon Seal	SK30011V-1

## General Description



Spool Type, Flow Divider/Combiner Valve.  
 For additional information see Technical Tips on pages FC2-FC5.

## Features

- Interlocking spools for equal control dividing or combining
- Range of flow settings available for optimising control
- Pressure compensated control in both directions
- 50/50 ratio standard, other ratios available on request
- Commonly used for differential lock in transmission applications
- Hardened working parts for maximum durability
- All external parts zinc plated


## Specifications

Rated Flow	60 LPM (16 GPM)
Maximum Inlet Pressure	420 LPM (6000 PSI)
Flow Rating and Ratio	See Ordering Information
Accuracy Per Leg	±10%
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.12 kg (0.26 lbs.)
Cavity	C10-4 (See BC Section for more details)




## Performance Curves

Flow vs. Inlet Pressure (Through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**L04A3** —  **N**

Size 10      Flow Rating      Seals  
Flow Divider      and Ratio  
Combiner Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Total Flow Rating - Port 3 (Flow Ratio)
10-10	8-20 LPM (2.1-5.3 GPM) (50/50 Ratio)
20-20	12-40 LPM (3.2-10.6 GPM) (50/50 Ratio)
30-30	14-60 LPM (3.7-15.9 GPM) (50/50 Ratio)

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

**B10** — **4** — **8T**

10 size      4-Way      Port  
Cavity      Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30506N-1
Fluorocarbon Seal	SK30506V-1

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description



Spool Type, Flow Divider/Combiner Valve.  
 For additional information see Technical Tips on pages FC2-FC5.

## Features

- Interlocking spools for equal control dividing or combining
- Range of flow settings available for optimising control
- Pressure compensated control in both directions
- 50/50 ratio standard, other ratios available on request
- Commonly used for differential lock in transmission applications
- Hardened working parts for maximum durability
- All external parts zinc plated


## Specifications

Rated Flow	180 LPM (47 GPM)
Maximum Inlet Pressure	420 LPM (6000 PSI)
Flow Rating and Ratio	See Ordering Information
Accuracy Per Leg	±10%
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.40 kg (0.86 lbs.)
Cavity	C16-4 (See BC Section for more details)




## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**L06A3**

16 Size  
Flow Divider/  
Combiner Valve

Flow Rating  
and Ratio

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Total Flow Rating - Port 3 (Flow Ratio)
<b>60-60</b>	35-120 LPM (9.2-31.7 GPM) (50/50 Ratio)
<b>90-90</b>	65-180 LPM (17.2-47.8 GPM) (50/50 Ratio)

Code	Seals
<b>N</b>	Nitrile

Order Bodies Separately  
See section BC

**B16**

16 size

**4**

4-Way  
Cavity

**16T**

Port  
Size


Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30510N-1
Fluorocarbon Seal	SK30510V-1

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
Technical Tips .....					PC3-PC7

## RELIEF VALVES



## DIRECT ACTING


RDH081	C08-2	Direct Acting Relief, Ball Type	1.9/5	380/5500	PC8-PC9
RDH082	C08-2	Direct Acting Relief, Poppet Type	30/8	380/5500	PC10-PC11
RDH101	C10-2	Direct Acting Relief, Ball Type	1.9/5	380/5500	PC12-PC13
RD102	C10-2	Direct Acting Relief, Poppet Type	38/10	250/3600	PC14-PC15
A04B2	C10-2	Direct Acting Relief, Poppet Type	100/26	420/6000	PC16-PC17

## DIFFERENTIAL AREA

RDH083	C08-2	Direct Acting Differential Area Relief	45/12	350/5000	PC18-PC19
RDH103	C10-2	Direct Acting Differential Area Relief	75/20	350/5000	PC20-PC21
RD163	C16-2	Direct Acting Differential Area Relief	151/40	210/3000	PC22-PC23


## PILOT OPERATED

RAH081	C08-2	Pilot Operated Spool Type	75.8/20	350/5000	PC24-PC25
RAH101	C10-2	Pilot Operated Spool Type	113/30	350/5000	PC26-PC27
RAH121	C12-2	Pilot Operated Spool Type	190/50	350/5000	PC28-PC29
RAH161	C16-2	Pilot Operated Spool Type	303/80	380/5500	PC30-PC31
RAH201	C20-2	Pilot Operated Spool Type	379/100	350/5000	PC32-PC33



## CROSS-OVER


A04J2	C10-2	Direct Acting Cross-over Relief	120/32	350/5000	PC34-PC35
-------	-------	---------------------------------	--------	----------	-----------



## UNLOADING


RU104	C10-4	Direct Acting Unloading	1/0.25	250/3600	PC36-PC37
-------	-------	-------------------------	--------	----------	-----------

## SEQUENCE VALVES



## PILOT OPERATED

SVH081	C08-3	Pilot Operated, Int. Pilot, Ext. Drain	45/12	350/5000	PC38-PC39
SVH101	C10-3	Pilot Operated, Int. Pilot, Ext. Drain	56.3/15	350/5000	PC40-PC41
SVH161	C16-3	Pilot Operated, Int. Pilot, Ext. Drain	151.6/40	350/5000	PC42-PC43



SVH102	C10-3	Pilot Operated, Ext. Pilot, Int. Drain	56.3/15	350/5000	PC44-PC45
SVH162	C16-3	Pilot Operated, Ext. Pilot, Int. Drain	151.6/40	350/5000	PC46-PC47

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC




Bodies &  
Cavities

TD

Technical  
Data



Pressure Control Valves

	SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
<b>REDUCING VALVES</b>	<b>DIRECT ACTING</b>					
	PR103 ..... C10-3 .....Direct Acting Reducing/Relieving .....56/15 ..... 210/3000 ..... PC48-PC49					
	<b>PILOT OPERATED</b>					
	PRH082 ..... C08-3 .....Pilot Operated Reducing .....30/8 ..... 350/5000 ..... PC50-PC51					
	PRH102 ..... C10-3 .....Pilot Operated Reducing .....56.3/15 ..... 350/5000 ..... PC52-PC53					
	PRH081 ..... C08-3 .....Pilot Operated Reducing/Relieving .....30/8 ..... 350/5000 ..... PC54-PC55					
	PRH101 ..... C10-3 .....Pilot Operated Reducing/Relieving .....56.3/15 ..... 350/5000 ..... PC56-PC57					
	PRH161 ..... C16-3 .....Pilot Operated Reducing/Relieving .....150/40 ..... 350/5000 ..... PC58-PC59					


<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## INTRODUCTION

This technical tips section is designed to help familiarize you with the Parker line of Pressure Controls. In this section we highlight new products to this catalog as well as some design features of our pressure control line. In addition we present common options available to help you in selecting products for your application. Finally we give a brief synopsis of the operation and applications of the various product offered in this section.

## NEW PRODUCTS

There are several new additions and product improvements to our Pressure Controls product line.



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data

COMMON OPTIONS


As you will see, Parker offers a variety of Pressure Control products. As such, some of the options mentioned below may not be available on all valves. Consult the model coding and dimensions for each valve for specifics. Here are some of the common options available.

**Adjustment Types:** Parker offers three primary types of adjustments for most of the pressure control products. Samples of these types are shown below. Please note all options may not be available for all valves. Consult the individual catalog pages for more details.


**Screw Adjustment** - Valve can be adjusted with an allen wrench. Lock nut included to maintain desired setting after adjustment. This is the most common adjustment option available on most Parker products.



**Knob Adjustment** - An aluminum knob is added to the standard screw adjustment. A lock knob is provided to help maintain the desired setting after adjustment. Parker offers knob conversion kits for most pressure control valves. For kit numbers consult individual valve pages.



**Tamper Resistant** - The tamper resistant option is a screw adjustable valve with a steel cap installed to conceal the adjustment. The cap is designed so that the internal edges clamp into the groove of the valve adapter. Once the cap is installed, it cannot be removed without damaging the cap and the valve. When a valve is ordered with the tamper resistant option, it will be preset at the factory, and the cap will be included in a separate plastic bag to allow for fine tuning at the customer site. Parker offers tamper resistant cap conversion kits for most pressure control valves. For kit numbers consult individual valve pages.



**Seals:** Valves feature either a 4301 Polyurethane “D”-Ring. The “D”-Ring eliminates the need for backup rings. The majority of the products are also available in Nitrile or Fluorocarbon seals. Contact factory for availability. You should match the seal compatibility to the temperature and fluid being used in your application.


**Pressure Range:** Parker offers a range of spring settings for the Pressure Control product line. You want to choose the setting that best meets the operating range. The model callout is equivalent to the maximum setting (in psi) of the spring divided by 100 (i.e. 50 = 5000 psi).

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## PRODUCT TYPES / APPLICATIONS

### Direct Acting Relief Valves

Direct acting relief valves are designed for fast response in intermittent duty applications. They are often used as an economical solution to clip pressure spikes. The poppet design allows for low leakage.




**OPERATION** - The valve poppet is held against the seat by the spring force. Inlet pressure on the nose (port 1) of the poppet acts against the spring force to unseat the poppet at the valve setting and allow flow to pass to tank. Since the pressure is working directly on the spring, this valve is very fast responding. It is not the best choice for system pressure regulation as it is slightly noisier than pilot operated relief valves and has higher pressure rise.

*Note:* Any backpressure on port 2 would be additive to the spring setting.

### Differential Area Relief Valves

Differential area relief valves also are also best suited for intermittent applications where fast response is critical. These valves are often used as cross-over relief valves to chop pressure spikes. Due to their design, they generally can handle a larger flow rate and have a lower pressure rise than the standard directing acting relief. The poppet design allows for low leakage.




**OPERATION** - Pressure on the inlet (port 2) of the valve acts on the differential area of the poppet (difference between the O.D. of the poppet and the seat diameter) to produce a force which is opposed by the spring force. When pressure reaches the valve setting, the poppet is pushed off its seat, permitting flow to tank.

*Note:* Any backpressure on port 1 would be additive to the spring setting.

### Pilot Operated Relief

Pilot operated relief valves are designed for continuous duty applications. Due to their stability and low pressure rise, the pilot operated relief is the best option for setting the pressure of a hydraulic system.



**OPERATION** - When inlet pressure at the nose (port 1) exceeds the valve setting, the pilot ball unseats. The pilot flow creates a pressure imbalance across the main spool causing the spool to move and allowing flow from inlet (port 1) to tank (port 2.) *Note:* Any backpressure on port 2 would be additive to the spring setting.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD



Technical  
Data

**Dual Crossover Relief Valves**

Dual crossover relief valves provide pressure surge protection for double acting hydraulic actuators. For best results, you always want to install the valve as close to the actuator as possible.

The dual crossover feature can be achieved in two different methods. One way is to manifold two Differential Area Relief Valves into a single body.



The advantage gained is higher flows can be pushed through this arrangement. The second method is to combine this dual function into a single cartridge. The single cartridge arrangement reduces cost considerably of the total package. In addition, a standard common cavity line body can be used instead of a special two body arrangement. The operation for the single cartridge style is shown below.



**OPERATION** - Pressure at port 1 acts on the spool to produce a force which is opposed by the spring setting. When pressure reaches the valve setting, the spool and poppet move relieving flow from port 1 to port 2. When port 2 is pressurized, the pressure acts on the differential area poppet to produce a force which is opposed by the spring force. When the pressure reaches the valve setting, the poppet is pushed off of its seat, relieving flow from port 2 to port 1. *Note:* Due to the construction and flow paths through the valve, the relief pressure settings may vary by approximately 300 psi from one direction to the other.

**Differential Area Unloading Relief Valve**



Unloading valves are differential area relief valves that can also be fully dumped or unloaded via a remote signal. They are best suited for low flow accumulator unloading circuits. They provide a fixed percentage between load and unload pressures. This pilot valve would generally be used in conjunction with a logic element.



**OPERATION** - The fixed differential is provided by the pilot piston which has greater area than the dart seat. With its greater area, the piston is able to hold the dart off its seat, permitting flow from pressure to tank, until pressure on the pilot piston falls below the fixed percentage of the valve settings.

**Pilot Operated Reducing Valve**

Pilot operated pressure reducing valves can be used to reduce the pressure in a leg of the circuit lower than system pressure. Thus, they can be used to provide protection to downstream components from higher pressures.





**OPERATION** - The pilot section controls the valve setting when reducing. As pressure at the regulated port exceeds the valve setting, the pilot ball is unseated. The pilot flow creates a pressure imbalance across the main spool causing the spool to throttle in order to maintain constant downstream pressure. The normally open design will allow flow to pass from inlet to reduced port with the only restriction being the pressure drop.

**Pressure Reducing / Relieving Valves**

Pressure reducing / relieving valves can be used to reduce the pressure in a leg of the circuit lower than system pressure. The valve also acts as a relief valve, relieving any shocks or surges that occur between the regulated port and the actuator. When the valve is in the relieving mode, the inlet port is blocked. Parker offers pressure reducing/relieving valves in both pilot operated and directing acting styles. The direct acting version is generally used in static applications where response is critical, or leakage is a concern.

**Pilot Operated**


**OPERATION** - The pilot section controls the valve setting when reducing. As pressure at the regulated port exceeds the valve setting, the pilot ball is un-seated. The pilot flow creates a pressure imbalance across the main spool causing the spool to throttle in order to maintain constant downstream pressure.



A shock or surge at the regulated port shifts the spool, relieving flow to tank.

**Direct Acting**


**OPERATION** - As pressure at the regulated port exceeds the valve setting, the valve throttles or closes in order to maintain constant downstream pressure. A shock or surge at the regulated port further shifts the spool, relieving flow to tank. This valve is not intended for rapidly changing flows which could lead to instability.

**Pilot Operated Sequence Valves**


Sequence valves are used to control the sequence of operation of two or more hydraulic actuators. The sequence valve pressure is set higher than the first actuator operation pressure. Once the first actuator has completed its cycle, the sequence valve opens allowing the second actuator to move. Parker's line of pilot operated sequence valves include a series of internally piloted, externally drained valves and a series of externally piloted, internally vented valves. Parker also offers a line of direct acting sequence valves which are ideal for piloting logic elements in steady state applications.

**P.O. Sequence (Internally Piloted, Externally Drained)**

**OPERATION** - For this valve, the pilot pressure is sensed from the inlet of the valve (port 1). When the pilot pressure exceeds the valve setting, the pilot section opens creating a pressure imbalance across the main spool. This causes the spool to move allowing the flow to pass from the nose of the cartridge (port 1) to the actuator port (port 2). By externally draining the pilot flow directly to tank (port 3), the valve is insensitive to back pressure at the sequence port.

**P.O. Sequence (Externally Piloted, Internally Vented)**

**OPERATION** - For this valve, the pilot pressure is obtained from an external source and not from the pressure port. When the external pilot pressure (port 1) exceeds the valve setting, the pilot section opens creating a pressure imbalance across the main spool. This causes the spool to move allowing the flow to pass from the side of the cartridge (port 2) to the actuator port (port 3). Any pressure at port 3 is additive to the pressure setting. It is most common for port 3 to be connected to tank.







## General Description

Direct Acting Relief Valve. This valve is designed for pilot flow circuits.

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided pilot for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis




## Specifications

Rated Flow	1.9 LPM (0.5 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.09 kg (0.20 lbs.)
Cavity	C08-2 (See BC Section for more details)

## Performance Curve


### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**Dimensions** Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

**Ordering Information**

**RDH081**

08 Size  
 Direct Acting  
 Relief Valve

**S**

Adjustment  
 Style



Pressure  
 Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	Screw Adjust

Code	Seals
<b>Omit</b>	D-Ring

Code	Pressure Range
<b>10</b>	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately 100 cc/min (6.1 in <sup>3</sup> /min)
<b>30</b>	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately 100 cc/min (6.1 in <sup>3</sup> /min)
<b>50</b>	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately 100 cc/min (6.1 in <sup>3</sup> /min)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Order Bodies Separately  
 See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size



Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description

Direct Acting Poppet-Type Relief Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Fast response
- Spherical poppets for low leakage
- Internal mechanical stop limits poppet travel eliminating spring solidification
- All external parts zinc plated
- Polyurethane "D"-Ring eliminates backup rings and prevents hydrolysis




## Specifications

Rated Flow	30 LPM (8 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>15</b> 19.3 Bar (280 PSI) <b>30</b> 35 Bar (508 PSI) <b>50</b> 54 Bar (787 PSI)
Reseat Pressure	85% of crack pressure
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.18 kg (0.40 lbs.)
Cavity	C08-2 (See BC Section for more details)

## Performance Curve


### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**RDH082**  
08 Size  
Direct Acting  
Relief Valve

**S**  
Adjustment  
Style

Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Order Bodies Separately  
See section BC

**B08**  
08 size

**2**  
2-Way  
Cavity

**6T**  
Port  
Size

Code	Pressure Range
15	6.9 - 103 Bar (100 - 1500 PSI) Standard Setting: 51.7 Bar (750 PSI) @ crack pressure approximately .95 LPM (.25 GPM)
30	17.2 - 207 Bar (250 - 3000 PSI) Standard Setting: 103 Bar (1500 PSI) @ crack pressure approximately .95 LPM (.25 GPM)
50	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure approximately .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)





CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description

Direct Acting Relief Valve. This valve is designed for pilot flow circuits. For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis




## Specifications

Rated Flow	1.9 LPM (0.5 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.18 kg (0.40 lbs.)
Cavity	C10-2 (See BC Section for more details)


## Performance Curve

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**RDH101**

10 Size  
Direct Acting  
Relief Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately 100 cc/min (6.1 in <sup>3</sup> /min)
30	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately 100 cc/min (6.1 in <sup>3</sup> /min)
50	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately 100 cc/min (6.1 in <sup>3</sup> /min)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	718083
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V





## General Description

Direct Acting Poppet-Type Relief Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Internal mechanical stop limits poppet travel eliminating spring solidification
- Spherical poppets for low leakage
- “D”-Ring eliminates backup rings
- All external parts zinc plated
- Fast response




## Specifications

Rated Flow	38 LPM (10 GPM)
Maximum Inlet Pressure	250 Bar (3600 PSI)
Maximum Pressure Setting	210 Bar (3000 PSI)
Sensitivity: Pressure/Turn	<b>09</b> 7.2 Bar (104 PSI) <b>18</b> 16 Bar (234 PSI) <b>30</b> 103.4 Bar (1500 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Reseat Pressure	85% of crack pressure
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.5 lbs.)
Cavity	C10-2 (See BC Section for more details)

## Performance Curve


### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**Dimensions** Millimeters (Inches)



Screw/Knob Version

Tamper Resistant Version

**Ordering Information**

**RD102**

10 Size  
 Direct Acting  
 Relief Valve

**S**

Adjustment  
 Style



Pressure  
 Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>D-Ring</b>

Code	Pressure Range
09	7 - 62 Bar (100 - 900 PSI) Standard Setting: 31.0 Bar (450 PSI) @ .95 LPM (.25 GPM)
18	13.8 - 124 Bar (200 - 1800 PSI) Standard Setting: 62.1 Bar (900 PSI) @ .95 LPM (.25 GPM)
<b>30</b>	<b>41.4 - 207 Bar (600 - 3000 PSI)</b> <b>Standard Setting:</b> <b>103.4 Bar (1500 PSI)</b> <b>@ .95 LPM (.25 GPM)</b>

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
 See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size



Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description

Direct Acting Poppet-Type Relief Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Fast response with good stability
- Virtually leak free
- Hardened working parts for maximum durability
- All external parts zinc plated




## Specifications

Rated Flow	100 LPM (26 GPM)
Maximum Inlet Pressure	<b>H-</b> 5-210 Bar (72-3000 PSI) <b>P-</b> 5-420 Bar (72-6000 PSI)
Maximum Pressure Setting	420 Bar (6000 PSI)
Sensitivity: Pressure/Turn	<b>H-</b> 21 Bar (305 PSI) <b>P-</b> 43.4 Bar (630 PSI)
Maximum Tank Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. @100 Bar (1450 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.28 kg (0.62 lbs.)
Cavity	C10-2 (See BC Section for more details)


## Performance Curves

(Pressure rise through cartridge only)

### Flow vs. Inlet Pressure




### Flow vs. Inlet Pressure



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**A04B2**

10 Size  
Direct Acting  
Relief Valve



Pressure  
Adjustment  
Range



Adjustment  
Style



Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pressure Range
H	5 - 210 Bar (72 - 3000 PSI)
P	5 - 420 Bar (72 - 6000 PSI)

Code	Adjustment Style
Z	Screw Adjust

Code	Seals
N	Nitrile

Standard Pressure Setting
<b>A04B2H</b> Standard Setting: 100 Bar (1450 PSI) @ 15 LPM (4.0 GPM)
<b>A04B2P</b> Standard Setting: 200 Bar (2900 PSI) @ 15 LPM (4.0 GPM)

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	ASV014975
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30503N-1
Fluorocarbon Seal	SK30503V-1



## General Description

Differential Area Relief Valve.

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Spherical poppets for low leakage
- High flow capacity
- Internal mechanical stop limits poppet travel eliminating spring solidification
- All external parts zinc plated




## Specifications

Rated Flow	45 LPM (12 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>15</b> 15 Bar (218 PSI) <b>30</b> 27 Bar (396 PSI) <b>50</b> 42 Bar (614 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Reseat Pressure	75% of crack pressure
Leakage at 150 SSU (32 cSt)	10 drops/min. (.67 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.19 kg (0.43 lbs.)
Cavity	C08-2 (See BC Section for more details)

## Performance Curve


### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**RDH083**

08 Size  
Differential Area  
Relief Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Porting / Body Material
<b>6T</b>	<b>SAE-6 / Steel (5000 PSI)</b>

Code	Pressure Range
<b>15</b>	6.9 - 103 Bar (100 - 1500 PSI) Standard Setting: 51.7 Bar (750 PSI) @ crack pressure approximately .95 LPM (.25 GPM)
<b>30</b>	69 - 207 Bar (1000 - 3000 PSI) Standard Setting: 103 Bar (1500 PSI) @ crack pressure approximately .95 LPM (.25 GPM)
<b>50</b>	138 - 345 Bar (2000 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure approximately .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	718083
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data





## General Description

Differential Area Relief Valve.

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Internal mechanical stop limits poppet travel eliminating spring solidification
- Spherical poppets for low leakage
- “D”-Ring eliminates backup rings
- All external parts zinc plated
- High flow capacity




## Specifications

Rated Flow	75 LPM (20 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 9.8 Bar (143 PSI) <b>30</b> 25.8 Bar (375 PSI) <b>50</b> 40.6 Bar (589 PSI)
Reseat Pressure	85% of crack pressure
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.50 lbs.)
Cavity	C10-2 (See BC Section for more details)


## Performance Curve

### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

<b>RDH103</b>	<b>S</b>	
10 Size Differential Area Relief Valve	Adjustment Style	Pressure Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>D-Ring</b>

Code	Pressure Range
<b>10</b>	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ .95 LPM (.25 GPM)
<b>30</b>	34.5 - 207 Bar (500 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ .95 LPM (.25 GPM)
<b>50</b>	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)



## General Description

Differential Area Relief Valve.

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- Low leakage design
- Fast response
- All external parts zinc plated




## Specifications

Rated Flow	151 LPM (40 GPM)
Maximum Inlet Pressure	240 Bar (3500 PSI)
Maximum Pressure Setting	210 Bar (3000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 7 Bar (104 PSI) <b>30</b> 14 Bar (204 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Reseat Pressure	80% of crack pressure
Leakage at 150 SSU (32 cSt)	10 drops/min. (.66 cc/min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.50 lbs.)
Cavity	C16-2 (See BC Section for more details)

## Performance Curve


### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions



Ordering Information

<b>RD163</b>	<b>S</b>	
16 Size Differential Area Relief Valve	Adjustment Style	Pressure Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 size		2-Way Cavity		Port Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

Code	Pressure Range
10	13.8 - 69 Bar (200 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ 11.3 LPM (3 GPM)
30	41.4 - 207 Bar (600 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ 11.3 LPM (3 GPM)

Kit	Part Number
Knob	840208K
Tamper Resistant Cap	717783
Nitrile Seal	SK16-2
Fluorocarbon Seal	SK16-2V





<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Pilot Operated Spool-Type Relief Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided pilot for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris





## Specifications

Rated Flow	75.8 LPM (20 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	5 cc per 6.8 Bar (100PSI) setting
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.09 kg (0.20 lbs.)
Cavity	C08-2 (See BC Section for more details)


## Performance Curves

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**RAH081**

08 Size  
Pilot Operated  
Relief Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>D-Ring</b>

Code	Pressure Range
<b>10</b>	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
<b>30</b>	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
<b>50</b>	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Order Bodies Separately  
See section BC

<b>B08</b>	<b>2</b>	<b>6T</b>
08 size	2-Way Cavity	Port Size



Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description

Pilot Operated Spool-Type Relief Valve.  
 For addition information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris





## Specifications

Rated Flow	113 LPM (30 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	5 cc per 6.8 Bar (100 PSI) setting
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.50 lbs.)
Cavity	C10-2 (See BC Section for more details)

## Performance Curves


### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)






Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**RAH101**

10 Size Pilot  
Operated Relief Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
30	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
50	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717083
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size



Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description

Pilot Operated Spool-Type Relief Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Low override curve
- Ball-type pilot for added stability
- High accuracy - pilot operated design
- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- All external parts zinc plated




## Specifications

Rated Flow	189.5 LPM (50 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 23 Bar (334 PSI) <b>30</b> 59.7 Bar (867 PSI) <b>50</b> 118 Bar (1711 PSI)
Reseat Pressure	80% of crack pressure
Leakage at 150 SSU (32 cSt)	82 cc/min. (5 cu. in./min.) @75% of crack pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.22 kg (0.48 lbs.)
Cavity	C12-2 (See BC Section for more details)


## Performance Curve

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**RAH121**

12 Size  
Pilot Operated  
Relief Valve

**S**

Adjustment  
Style

Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

Code	Pressure Range
<b>10</b>	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ 11.3 LPM (3 GPM)
<b>30</b>	20.7 - 207 Bar (300 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ 11.3 LPM (3 GPM)
<b>50</b>	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ 11.3 LPM (3 GPM)

Kit	Part Number
Knob	717784-15
Tamper Resistant Cap	717785
Nitrile Seal	SK12-2
Fluorocarbon Seal	SK12-2V

Order Bodies Separately  
See section BC

<b>B12</b>	-	<b>2</b>	-	<b>12T</b>
12 size		2-Way Cavity		Port Size



Code	Porting / Body Material
12T	SAE-12 / Steel (5000 PSI)

## General Description

Pilot Operated Spool-Type Relief Valve. For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Internal screening protects pilot seat from debris
- Steel adapters are zinc plated




## Specifications

Rated Flow	302.8 LPM (80 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>20</b> 39.3 Bar (570 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	5 cc per 6.8 Bar (100 PSI) setting
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.34 kg (0.75 lbs.)
Cavity	C16-2 (See BC Section for more details)

## Performance Curve

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)




## Performance Curve

### Regulated Pressure vs. Flow

(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

**RAH161**

16 Size  
Pilot Operated  
Relief Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 size		2-Way Cavity		Port Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ .95 LPM (25 GPM)
30	20.7 - 207 Bar (300 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ .95 LPM (25 GPM)
50	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ .95 LPM (25 GPM)



Kit	Part Number
Knob	717784-15
Tamper Resistant Cap	717785
Nitrile Seal	SK16-2
Fluorocarbon Seal	SK16-2V

## General Description

Pilot Operated Spool-Type Relief Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Low override curve
- Ball-type pilot for added stability
- High accuracy - pilot operated design
- Hardened, precision ground parts for durability
- Compact size for reduced space requirements
- All external parts zinc plated




## Specifications

Rated Flow	379 LPM (100 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 23 Bar (334 PSI) <b>30</b> 59.7 Bar (867 PSI) <b>50</b> 118 Bar (1711 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Reseat Pressure	80% of crack pressure
Leakage at 150 SSU (32 cSt)	5 cc per 6.8 Bar (100 PSI) setting
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.9 kg (2.0 lbs.)
Cavity	C20-2 (See BC Section for more details)

## Performance Curve

### Flow vs. Inlet Pressure

(Pressure rise through cartridge only)



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics


**BC**

Bodies &  
Cavities


**TD**

Technical  
Data

Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**RAH201**

20 Size  
Pilot Operated  
Relief Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ 37.5 LPM (10 GPM)
30	20.7 - 207 Bar (300 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ 37.5 LPM (10 GPM)
50	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ 37.5 LPM (10 GPM)

Kit	Part Number
Knob	717784-15
Tamper Resistant Cap	717785
Nitrile Seal	SK20-2
Fluorocarbon Seal	SK20-2V

Order Bodies Separately  
See section BC

<b>B20</b>	—	<b>2</b>	—	<b>20T</b>
------------	---	----------	---	------------

20 size

2-Way  
Cavity

Port  
Size

Code	Porting / Body Material
20T	SAE-20 / Steel (5000 PSI)

**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics

**BC**

Bodies &  
Cavities

**TD**

Technical  
Data



## General Description

Direct Acting, Dual Poppet-Type, Cross-over Relief Valve.




For additional information see Technical Tips on pages PC3-PC7.

## Features

- Compact space saving design
- Cost effective - only requires one cavity
- Poppet-type construction for lower leakage
- Full 350 Bar, 5000 PSI pressure capability
- High flow capability for the size of valve
- Minimal pressure variation with flow change
- Hardened working parts for maximum durability
- All external parts zinc plated

## Specifications


Rated Flow	120 LPM (32 GPM)
Maximum Inlet Pressure	<b>M-</b> 10-350 Bar (144-5000 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>M-</b> 34 Bar (493 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	10 drops/min. @100 Bar (1450)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.29 kg (0.64 lbs.)
Cavity	C10-2 (See BC Section for more details)




## Performance Curves

(Pressure rise through cartridge only)

### Flow vs. Inlet Pressure 1 to 2 and 2 to 1




## Application



Motor protection in both directions

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**A04J2**

10 Size  
Direct Acting  
Relief Valve

**M**

Pressure  
Adjustment  
Range

**Z**

Adjustment  
Style

**N**

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Pressure Range
M	10 - 350 Bar (144 - 5000 PSI)

Code	Adjustment Style
Z	Screw Adjust

Code	Seals
N	Nitrile

Standard Pressure Setting

**A04J2M** Standard Setting:  
200 Bar (2900 PSI)  
@ 15 LPM (4.0 GPM)

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Knob	ASV014975
Tamper Resistant Cap	TC1130
Nitrile Seal	SK30529N-1
Fluorocarbon Seal	SK30529V-1

## General Description

### Pressure Unloading Valve Assembly

This valve is best suited for accumulator unloading circuits or can be used as a remote to pilot valves. They provide a fixed percentage between load and unload pressures.



For additional information see Technical Tips on pages PC3-PC7.

## Features


- Low hysteresis
- Cartridge design
- Hardened, precision ground parts for durability
- All external parts zinc plated
- “D”-Ring eliminates backup rings

## Specifications

Rated Flow	1 LPM (.25 GPM)
Maximum Inlet Pressure	250 Bar (3600 PSI)
Maximum Pressure Setting	250 Bar (3600 PSI)
Pressure Sensitivity	12 = 112 PSI/Turn 24 = 214 PSI/Turn 36 = 367 PSI/Turn
Maximum Tank Pressure	210 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	Port 1 leakage 48 ml/min. @207 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.45 kg (1.0 lbs.)
Cavity	C10-4 (See BC Section for more details)






## Typical Unloading Application



## Performance Curve

### Pump and Accumulator Pressure vs. Time





Ordering Information

<b>RU104</b>	<b>S</b>		<b>B</b>
10 Size Pressure Unloading Valve	Adjustment Style	Pressure Range	Reload

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Reload
B	80% $\pm$ 5% of Pressure Setting

Code	Pressure Range
12	55.2 - 82.7 Bar (800 - 1200 PSI) Standard Setting: 68.9 Bar (1000 PSI) @ 1.1 LPM (.3 GPM)
24	68.9 - 165.5 Bar (1000 - 2400 PSI) Standard Setting: 117.2 Bar (1700 PSI) @ 1.1 LPM (.3 GPM)
36	120.7 - 248.2 Bar (1750 - 3600 PSI) Standard Setting: 184.4 Bar (2675 PSI) @ 1.1 LPM (.3 GPM)

Code	Seals
Omit	D-Ring

Kit	Part Number
Tamper Resistant Cap	717943
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Pilot Operated Sequence Valve (Internally Piloted, Externally Vented).



For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided pilot for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris

## Specifications



Rated Flow	45 LPM (12 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	0.56 LPM (0.15 GPM)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	82 cc/min. (5 cu. in./min.) @ 210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.11 kg (0.25 lbs.)
Cavity	C08-3 (See BC Section for more details)




## Performance Curves

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**SVH081**

08 Size  
P.O. Sequence Valve  
(Internal Pilot)

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
30	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
50	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-3
Nitrile Seal	SK08-3
Fluorocarbon Seal	SK08-3V

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)



## General Description

Pilot Operated Sequence Valve (Internally Piloted, Externally Drained).

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris





## Specifications

Rated Flow	56.3 LPM (15 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow (Port 3)	0.94 LPM (0.25 GPM)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	82 cc/min. (5 cu. in./min.) @ 210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.45 kg (1.0 lbs.)
Cavity	C10-3 (See BC Section for more details)

## Performance Curves

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

<b>SVH101</b>	<b>S</b>	
10 Size P.O. Sequence Valve (Internal Pilot)	Adjustment Style	Pressure Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>D-Ring</b>

Code	Pressure Range
<b>10</b>	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
<b>30</b>	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)
<b>50</b>	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	718083
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

Order Bodies Separately  
See section BC

<b>B10</b>	<b>3</b>	<b>8T</b>
10 size	3-Way Cavity	Port Size

Code	Porting / Body Material
<b>8T</b>	SAE-8 / Steel (5000 PSI)





<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Pilot Operated Sequence Valve (Internally Piloted, Externally Drained). For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- High accuracy, pilot operation design
- Ball-type pilot for added stability
- All external parts zinc plated




## Specifications

Rated Flow	151.6 LPM (40 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 23 Bar (334 PSI) <b>30</b> 59.7 Bar (867 PSI) <b>50</b> 118 Bar (1711 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	1.9 LPM (0.5 GPM)
Reseat Pressure	80% of crack pressure
Leakage at 150 SSU (32 cSt)	5 cc per 6.8 Bar (100PSI) setting
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.45 kg (1.0 lbs.)
Cavity	C16-3 (See BC Section for more details)


## Performance Curve

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**SVH161**

16 Size  
P.O. Sequence Valve  
(Internal Pilot)

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>3</b>	—	<b>16T</b>
16 size		3-Way Cavity		Port Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ 11.3 LPM (3 GPM)
30	20.7 - 207 Bar (300 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ 11.3 LPM (3 GPM)
50	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ 11.3 LPM (3 GPM)

Kit	Part Number
Knob	717784-15
Tamper Resistant Cap	717785
Nitrile Seal	SK16-3
Fluorocarbon Seal	SK16-3V

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data




## General Description

Pilot Operated Sequence Valve (Externally Piloted, Internally Vented).

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris




## Specifications

Rated Flow	56.3 LPM (15 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	See maximum drain flow chart (Lower right)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32 cSt)	82 cc/min. (5 cu. in./min.) @ 210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.45 kg (1.0 lbs.)
Cavity	C10-3 (See BC Section for more details)

## Performance Curve

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)




## Maximum Drain Flow

$P_{PILOT} - P_{SETTING}$	Drain Flow
6.9 Bar (100 PSI)	0.34 LPM (0.09 GPM)
35 Bar (500 PSI)	0.76 LPM (0.20 GPM)
69 Bar (1000 PSI)	1.08 LPM (0.29 GPM)
138 Bar (2000 PSI)	1.53 LPM (0.40 GPM)
207 Bar (3000 PSI)	1.87 LPM (0.50 GPM)

Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**SVH102**

10 Size  
P.O. Sequence Valve  
(External Pilot)

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Code	Pressure Range
10	20.7 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ crack pressure, approximately 11.3 LPM (3 GPM)
30	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ crack pressure, approximately 11.3 LPM (3 GPM)
50	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ crack pressure, approximately 11.3 LPM (3 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	718083
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)



## General Description

Pilot Operated Sequence Valve (Externally Piloted, Internally Vented).

For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- High accuracy, pilot operation design
- Ball-type pilot for added stability
- All external parts zinc plated




## Specifications

Rated Flow	151.6 LPM (40 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 23 Bar (334 PSI) <b>30</b> 59.7 Bar (867 PSI) <b>50</b> 118 Bar (1711 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	See maximum drain flow chart (Lower right)
Reseat Pressure	80% of crack pressure
Leakage at 150 SSU (32 cSt)	82 cc/min. (5 cu. in./min.) @ 75% of Crack Pressure
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.45 kg (1.0 lbs.)
Cavity	C16-3 (See BC Section for more details)

## Performance Curve

### Flow vs. Inlet Pressure


(Pressure rise through cartridge only)



## Maximum Drain Flow

$P_{PILOT} - P_{SETTING}$	Drain Flow
6.9 Bar (100 PSI)	0.69 LPM (0.18 GPM)
35 Bar (500 PSI)	1.55 LPM (0.41 GPM)
69 Bar (1000 PSI)	2.19 LPM (0.58 GPM)
138 Bar (2000 PSI)	3.10 LPM (0.82 GPM)
207 Bar (3000 PSI)	3.79 LPM (1.00 GPM)

Dimensions    Millimeters (Inches)



Screw/Knob Version

Tamper Resistant Version

Ordering Information

<b>SVH162</b>	<b>S</b>	
16 Size P.O. Sequence Valve (External Pilot)	Adjustment Style	Pressure Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI) @ 11.3 LPM (3 GPM)
30	20.7 - 207 Bar (300 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI) @ 11.3 LPM (3 GPM)
50	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI) @ 11.3 LPM (3 GPM)

Kit	Part Number
Knob	717784-15
Tamper Resistant Cap	717785
Nitrile Seal	SK16-3
Fluorocarbon Seal	SK16-3V

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>3</b>	—	<b>16T</b>
16 size		3-Way Cavity		Port Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



## General Description

Direct Acting Pressure Reducing/ Relieving Valve.  
 For additional information see Technical Tips on pages PC3-PC7.



**Note:** The differential between system pressure and pressure setting of the valve can greatly affect the stability of this valve. For best performance, the inlet pressure setting should not exceed 69 Bar (1000 PSI) above the reducing valve setting.

## Features

- Hardened, precision ground parts for durability
- Internal mechanical stop limits spool travel eliminating spring solidification
- “D”-Ring eliminates backup rings
- All external parts zinc plated

## Specifications


Rated Flow	56 LPM (15 GPM)
Maximum Inlet Pressure	210 Bar (3000 PSI) 69 Bar (1000 PSI) maximum differential above valve setting for best stability
Maximum Pressure Setting	124 Bar (1800 PSI)
Sensitivity: Pressure/Turn	<b>12</b> 11.4 Bar (165 PSI) <b>21</b> 17.2 Bar (250 PSI)
Maximum Tank Pressure	124 Bar (1800 PSI)
Maximum Drain Flow	120 ml/min. (0.03 GPM)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.5 lbs.)
Cavity	C10-3 (See BC Section for more details)




## Performance Curves

(Pressure rise through cartridge only)


### Flow vs. Regulated Pressure



### Pressure vs. Flow



Dimensions    Millimeters (Inches)



Ordering Information

PR103

S

10 Size  
D.A. Pressure  
Reducing/Relieving Valve

Adjustment  
Style

Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Order Bodies Separately  
See section BC

B10	—	3	—	8T
10 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Code	Pressure Range
12	39.3 - 83 Bar (570 - 1200 PSI) Standard Setting: 41.4 Bar (600 PSI) @ .95 LPM (.25 GPM)
21	41.4 - 124.1 Bar (600 - 1800 PSI) Standard Setting: 69 Bar (1000 PSI) @ .95 LPM (.25 GPM)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD



Technical  
Data

## General Description

Pilot Operated Pressure Reducing Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided pilot for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris




## Specifications


Rated Flow	30 LPM (8 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 25 Bar (362 PSI) <b>30</b> 64.2 Bar (932 PSI) <b>50</b> 137 Bar (1987 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	0.56 LPM (0.15 GPM)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.11 kg (0.25 lbs.)
Cavity	C08-3 (See BC Section for more details)

## Performance Curves


### Flow vs. Pressure (Through cartridge only)




### Flow vs. Pressure Drop (Through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**PRH082**

08 Size  
P.O. Pressure  
Reducing Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI)
30	13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI)
50	13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI)

NOTE: For settings below 20.7 Bar (300 PSI), flow rating is limited to 11.3 LPM (3 GPM).

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-3
Nitrile Seal	SK08-3
Fluorocarbon Seal	SK08-3V

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size



Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description

Pilot Operated Pressure Reducing Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris




## Specifications


Rated Flow	56.3 LPM (15 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 25.4 Bar (369 PSI) <b>30</b> 64.9 Bar (942 PSI) <b>50</b> 137.6 Bar (1996 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	0.94 LPM (0.25 GPM)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.5 lbs.)
Cavity	C10-3 (See BC Section for more details)

## Performance Curves


### Flow vs. Pressure (Through cartridge only)




### Pressure vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**PRH102**

10 Size  
P.O. Pressure  
Reducing Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	D-Ring

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Code	Pressure Range
10	13.7 - 69 Bar (200 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI)
30	41.4 - 207 Bar (600 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI)
50	82.8 - 345 Bar (1200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI)

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717083
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V



NOTE: For settings below 20.7 Bar (300 PSI), flow rating is limited to 11.3 LPM (3 GPM).

## General Description

Pilot Operated Pressure Reducing/ Relieving Valve.  
 For additional information see Technical Tips on  
 pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided pilot for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris




## Specifications


Rated Flow	30 LPM (8 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	0.56 LPM (0.15 GPM)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.11 kg (0.25 lbs.)
Cavity	C08-3 (See BC Section for more details)

## Performance Curves

### Flow vs. Regulated Pressure (Through cartridge only)




### Flow vs. Pressure Drop (Through cartridge only)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**PRH081**

08 Size  
P.O. Pressure  
Reducing/Relieving  
Valve

**S**

Adjustment  
Style

Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>D-Ring</b>

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Code	Pressure Range
<b>10</b>	<b>6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI)</b>
<b>30</b>	<b>13.8 - 207 Bar (200 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI)</b>
<b>50</b>	<b>13.8 - 345 Bar (200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI)</b>

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	717943
D-Ring Seal	SK08-3
Nitrile Seal	SK08-3
Fluorocarbon Seal	SK08-3V



NOTE: For settings below 20.7 Bar (300 PSI), flow rating is limited to 11.3 LPM (3 GPM).

## General Description

Pilot Operated Pressure Reducing / Relieving Valve.  
 For additional information see Technical Tips on pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- Steel adapters are zinc plated
- Polyurethane “D”-Ring eliminates backup rings and prevents hydrolysis
- Internal screening protects pilot spring from debris




## Specifications


Rated Flow	56.3 LPM (15 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Maximum Drain Flow	0.94 LPM (0.25 GPM)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.23 kg (0.5 lbs.)
Cavity	C10-3 (See BC Section for more details)

## Performance Curves

### Flow vs. Regulated Pressure (Through cartridge only)




### Pressure vs. Flow (Through cartridge only)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Screw/Knob Version



Tamper Resistant Version

Ordering Information

**PRH101**

10 Size  
P.O. Pressure  
Reducing / Relieving  
Valve

**S**

Adjustment  
Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
<b>S</b>	<b>Screw Adjust</b>

Code	Seals
<b>Omit</b>	<b>D-Ring</b>

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Code	Pressure Range
<b>10</b>	13.7 - 69 Bar (200 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI)
<b>30</b>	41.4 - 207 Bar (600 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI)
<b>50</b>	82.8 - 345 Bar (1200 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI)

NOTE: For settings below 20.7 Bar (300 PSI), flow rating is limited to 11.3 LPM (3 GPM).

Kit	Part Number
Knob	717784-10
Tamper Resistant Cap	718083
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V

## General Description



Pilot Operated Pressure Reducing/Relieving Valve.  
 For additional information see Technical Tips on  
 pages PC3-PC7.

## Features

- Hardened, precision ground parts for durability
- Low profile adapter for minimal space requirements
- Fully guided poppet for more consistent reseal
- All external parts zinc plated

## Specifications


Rated Flow	151.4 LPM (40 GPM)
Maximum Inlet Pressure	380 Bar (5500 PSI)
Maximum Pressure Setting	350 Bar (5000 PSI)
Sensitivity: Pressure/Turn	<b>10</b> 19.6 Bar (285 PSI) <b>30</b> 58.9 Bar (859 PSI) <b>50</b> 131.7 Bar (1910 PSI)
Maximum Tank Pressure	350 Bar (5000 PSI)
Reseat Pressure	90% of crack pressure
Leakage at 150 SSU (32cSt)	5cc per 6.8 Bar (100 PSI) setting
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.34kg (0.75 lbs.)
Cavity	C16-3 (See BC Section for more details)



## Performance Curve


### Flow vs. Regulated Pressure

(Pressure rise through cartridge only)



### Pressure Drop vs. Flow

(Through cartridge only)



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics


**BC**

Bodies &  
Cavities

**TD**

Technical  
Data

**Dimensions** Millimeters (Inches)



**Ordering Information**

**PRH161**  
 16 Size  
 P.O. Pressure  
 Reducing/Relieving  
 Valve

**S**  
 Adjustment  
 Style

[Blank Box]  
 Pressure  
 Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Adjustment Style
S	Screw Adjust

Code	Seals
Omit	Nitrile

Code	Pressure Range
10	6.9 - 69 Bar (100 - 1000 PSI) Standard Setting: 34.5 Bar (500 PSI)
30	20.7 - 207 Bar (300 - 3000 PSI) Standard Setting: 103.5 Bar (1500 PSI)
50	34.5 - 345 Bar (500 - 5000 PSI) Standard Setting: 172.4 Bar (2500 PSI)

Kit	Part Number
Knob	717784-15
Tamper Resistant Cap	717785
Nitrile Seal	SK16-3
Fluorocarbon Seal	SK16-3V

Order Bodies Separately  
 See section BC






**B16**  
 16 size

**3**  
 3-Way  
 Cavity

**16T**  
 Port  
 Size

Code	Porting / Body Material
16T	SAE-16 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
Technical Tips .....					LE2-LE7
					
<b>POPPET TYPE</b>					
LE101A (NEW)	C10-3S	Normally Closed, Pilot to Close	57/15	350/5000	LE8
16SLC1-A	C16-3S	Normally Closed, Pilot to Close	189/50	240/3500	LE9
20SLC1-A	C20-3S	Normally Closed, Pilot to Close	303/80	240/3500	LE10
					
<b>SPOOL TYPE</b>					
LE102A (NEW)	C10-3S	Normally Closed, Pilot to Close	57/15	350/5000	LE11
R06E3	C16-3S	Normally Closed, Pilot to Close	400/106	420/6000	LE12
R08E3	C20-3S	Normally Closed, Pilot to Close	500/132	420/6000	LE13
					
LE102B (NEW)	C10-3S	Normally Closed, Vent to Open	57/15	350/5000	LE14
					
LE103A (NEW)	C10-3S	Normally Open, Vent to Close	57/15	350/5000	LE15
R06H3	C16-3S	Normally Open, Vent to Close	160/42	420/6000	LE16
					
LE103B (NEW)	C10-3S	Normally Open, Vent to Close	57/15	350/5000	LE17

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data


**INTRODUCTION:**

Parker's logic valves offer system designers a versatile range of screw-in elements that, when used in the proper combinations, can provide flexible design solutions for many common cartridge valve applications. They offer system designers the advantage of applying cartridge valve technology in applications where the flow and pressure conditions may exceed the limits of typical cartridge valves. Logic valves are essentially high flow poppet or spool elements that are controlled by small pilot devices. They can be used to control flow, pressure, or direction, and when applied in the proper arrangements, can perform multi-task control functions. Parker's logic valves offer system designers alternative products that can help reduce the size, cost, and complexity of integrated manifold systems.



**NEW PRODUCTS:**

Parker Logic Valves are offered in two basic categories: Poppet and Spool.

**Poppet Type** - Used for flow switching directional control applications.



**Spool Type** - Used for pressure sensing in modulating applications to regulate flow and pressure.



**PRODUCT TYPES / APPLICATIONS**  
**POPPET TYPE**

Poppet type logic valves are 3 ported, 2-way on/off valves that switch flow between port 1 and port 2. The poppet's on/off action is operated by controlling pilot oil at port 3 of the valve. A small low flow solenoid or pilot valve is an ideal control for this purpose. Parker offers vent-to-open and pilot-to-close style poppet logic valves.

**Note:** Poppet logic valves are an unbalanced 2:1 ratio poppet design. The opening and closing of the poppet is dependent on the force balances on the areas of the poppet at port 1, port 2, and port 3.

**Vent-to-open logic valves:**

Vent-to-open logic valves are primarily used for uni-directional switching applications. The poppet in the vent-to-open logic valve is spring biased to the closed condition. The pilot oil source that operates the logic element is generated internally by direct pressure from either work port 1 or 2, depending on the option chosen. Venting the pilot oil at port 3 allows the valve to open and pass flow between port 1 and 2 at the bias spring setting. Blocking the pilot at port 3 causes the valve to close. When closed, the 2:1 ratio poppet design provides a positive low leak seal. Because the pilot source is generated internally within the valve, vent-to-open logic valves are best suited for uni-directional applications.






## Technical Tips

### POPPET TYPE *Continued*

#### **Pilot-to-close logic valve:**

Pilot-to-close logic elements are primarily used for bi-directional flow switching applications. The poppet in the pilot-to-close logic valve is spring biased to the closed condition. With no pilot signal at port 3, the valve will open allowing flow in either direction between work ports 1 and 2 once pressure at one of the work ports reaches the biased spring setting. Applying a sufficient externally generated pilot force to port 3 of the valve closes the poppet creating a low leak seal between port 1 and port 2.



#### **Pilot-to-close**

External pilot required  
Bi-directional flow, port 1 to 2.

## Logic Elements

### **2-way, 3-way, and 4-way Directional Control:**

Poppet logic valves are typically used to perform high flow directional switching operations using small low power pilot valves to control the sequence of the directional operation.

- A single logic valve can be used to control 2-way, on/off switching.
- Multiple elements in a bridge arrangement can control 3-way or 4-way directional switching.
- Since each logic valve is individually controlled, the timing, sequence, and overlap of directional functions can be controlled very precisely.
- Uni-directional or bi-directional flow can be achieved, depending on the valve selected.
- Flows in excess of 80 gpm can be controlled through a single logic element, and more than one logic valve can be used in parallel to control flow in excess of the rated flow of a single element.
- Poppet construction provides a low leak directional control.

(See circuit examples on pages LE5-LE6)

### SPOOL TYPE


Spool type logic valves can also be used for directional switching, however, they are typically used in modulating applications to control flow or regulate pressure. Virtually any pressure or flow control function can be achieved with a spool type logic valve including; restrictive or priority flow control, pressure relief, pressure reducing, sequencing, and unloading.

The spools in this category of logic valves are balanced designs; the spool area at the work port (port 1) and the pilot port (port 3) are equal (1:1). The spool is held in a biased condition by a spring. Venting the pilot at port 3 creates an unbalanced condition causing the valve spool to modulate open or close, depending on the valve chosen. This spool design makes the valve vary stable because the forces acting to open and close the valve are in balance.


#### **Flow Control / Compensators:**

Parker offers two types of logic valves for flow control functions.

- 1) Normally open spools function as a restrictive type compensator.
- 2) Normally closed spools function as a priority or by-pass compensator.



**Normally open spool**




**Normally closed spool**

## Technical Tips

### Restrictive Flow Regulator:


Normally open spool type logic elements can be used with an external orifice or valve as a compensator to regulate flow. Used as restrictive compensator, a normally open spool senses the upstream and downstream pressure across an orifice or valve. The spool modulates closed to maintain a constant pressure drop across the controlled device equal to the bias spring in the logic valve, thus maintaining a constant flow rate regardless of changes in upstream or downstream pressure.



## Logic Elements


### Priority / Bypass Flow Regulator:

A logic valve with a normally closed spool can be used as a priority or by-pass compensator. In this case, the spool modulates open to maintain a constant pressure drop across the controlled orifice or valve, thereby maintaining a constant priority flow regardless of upstream or downstream pressure changes. In a priority arrangement, any oil that doesn't saturate the controlled device is by-passed at load pressure plus the value of the bias spring in the logic valve.



### Pressure Control:

Spool type logic valves can be used as the main stage spool in high flow pressure control applications with the logic valve handling the high flow, and a small pilot valve controlling the action of the logic valve spool. Normally open, and normally closed spool options are available enabling virtually all pressure control functions to be achieved. When used in pressure control applications, the logic valve spool modulates open or closed to maintain the pressure setting of the pilot valve communicated to port 3. Pressure control applications require a pilot connection between the control port (port 1 or 2), and the pilot port (port 3). In order to simplify the design, Parker offers spool type logic valves with internal piloting options that can help minimize the number of connections needed. When used in manifold systems, the internal piloting options help to simplify the manifold design by reducing the number of construction drillings in the block. Multiple functions such as relief, pump unloading, and pressure compensation can be performed with one logic valve by communicating multiple pilot devices to the same logic element.



(See circuit examples on page LE7)

### Application Note:


This section is as an application guide, and it is intended to illustrate the various ways that logic elements can be used to create a variety of hydraulic control functions. For additional help applying logic valves, contact your Parker Sales Engineer.

CV	Check Valves
SH	Shuttle Valves
LM	Load/Motor Controls
FC	Flow Controls
PC	Pressure Controls
LE	Logic Elements
DC	Directional Controls
SV	Solenoid Valves
PV	Proportional Valves
CE	Coils & Electronics
BC	Bodies & Cavities
TD	Technical Data

## DIRECTIONAL CONTROL EXAMPLES

**2-position, 2-way  
normally open example.**


Switched by 2-position, 3-way pilot valve and external pilot pressure.



Direction of Flow

**2-position, 2-way  
normally open example.**


Switched by external pilot pressure and vented through 2-position, 2-way pilot valve.



Direction of Flow

**2-position, 2-way  
normally open example.**


Internal pilot generation.



Direction of Flow

**2-position, 2-way  
normally open example.**


Internal pilot generation.



Direction of Flow

**2-position, 2-way  
normally open example.**


Switched by 2-position, 3-way pilot valve and external pilot.



Direction of Flow

**\*\*SLC1A logic element.**


With shuttle-selected pilot supply.



Direction of Flow

**\*\*SLC1A logic element.**

External pilot supply and 2-position, 2-way pilot directional valve.



Direction of Flow

CV

Check Valves

SH

Shuttle Valves

LM

Load/Motor Controls

FC

Flow Controls

PC

Pressure Controls

LE

Logic Elements

DC

Directional Controls

SV

Solenoid Valves

PV

Proportional Valves

CE

Coils &amp; Electronics

BC

Bodies &amp; Cavities


TD

Technical Data


DIRECTIONAL CONTROL EXAMPLES

THREE-WAY BRIDGE CIRCUITS


*Circuit 1, with LE101A poppet logic element.*



*Circuit 2, with LE102A spool logic element.*



*Circuit 3, with LE102A spool logic element.*




Required Flow Path	Pilot Pressure Applied To		Available From Circuit		
	PA	PB	1	2	3
	NO	NO	X	X	
	YES	NO	X	X	X

Required Flow Path	Pilot Pressure Applied To		Available From Circuit		
	PA	PB	1	2	3
	NO	YES	X	X	
	NO	YES	X		X


**NOTE:** Pilot pressure must exceed load pressure in order for valve to close.

FOUR-WAY BRIDGE CIRCUITS

*Circuit 1, with LE101A poppet logic elements.*



*Circuit 2, with LE102A spool logic elements.*




Required Flow Path	Pilot Pressure Applied To					Required Flow Path	Pilot Pressure Applied To					Required Flow Path	Pilot Pressure Applied To				
	P1	P2	P3	P4	P5		P1	P2	P3	P4	P5		P1	P2	P3	P4	P5
	YES	YES	YES	YES	YES		YES	NO	NO	YES	YES		YES	NO	YES	NO	YES
	NO	NO	NO	NO	NO		NO	YES	YES	NO	YES		YES	YES	YES	NO	YES
	YES	YES	NO	NO	NO		YES	YES	NO	YES	YES		YES	NO	YES	YES	YES
	NO	NO	YES	YES	NO		NO	YES	YES	YES	YES						
	YES	YES	YES	YES	NO		NO	YES	NO	YES	YES						


**NOTE:** Pilot pressure must exceed load pressure in order for valve to close.

## FLOW CONTROL EXAMPLES


**Pressure compensated priority flow control example.**




**Load sensing priority flow control example with pressure limiting and unloading.**



**Pressure compensated restrictive flow control example.**




**Load sensing priority flow control example with pressure limiter.**




## PRESSURE CONTROL EXAMPLES


**Pressure relief or sequence example with external pilot supply and pilot relief.**




**Pressure reducing example, non-relieving type.**



**Pressure relief or sequence example with internal pilot supply and pilot relief.**



**Pressure reducing-relieving example.**



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data

## General Description

Poppet Type, Bi-Directional, Normally Closed, Pilot to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- Hardened, precision ground parts for durability
- Low leakage design
- All external parts zinc plated
- Port 2 to 1 is the preferred flow path
- "D"-Ring eliminates backup rings

## Specifications

Rated Flow	57 LPM (15 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @ 240 Bar (3500 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.14 kg (0.3 lbs.)
Cavity	C10-3S (See BC Section for more details)

## Ordering Information

**LE101A**

10 Size  
Logic Element





Bias  
Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.


Code	Bias Spring
02	1.7 Bar (25 PSI)
04	3.5 Bar (50 PSI)
05	5.2 Bar (75 PSI)
07	6.9 Bar (100 PSI)
10	10.3 Bar (150 PSI)

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK10-3S
Nitrile Seal	SK10-3S
Fluorocarbon Seal	SK10-3SV




## Dimensions




Millimeters (Inches)

## Performance Curves

Pressure Drop, P2-P1 vs. Flow (Through cartridge only)  
 Hydraulic Oil 150 SSU @ 100F (32cSt)



Pressure Drop, P1-P2 vs. Flow (Through cartridge only)  
 Hydraulic Oil 150 SSU @ 100F (32cSt)



CV

Check Valves

SH

Shuttle Valves

LM

Load/Motor Controls

FC

Flow Controls

PC

Pressure Controls

LE

Logic Elements

DC

Directional Controls

SV

Solenoid Valves

PV

Proportional Valves

CE

Coils & Electronics

BC

Bodies & Cavities

TD

Technical Data

## General Description


Poppet Type, Bi-Directional, Normally Closed, Pilot to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- Hardened, precision ground parts for durability
- Polyurethane seals only
- No backup rings
- Low leakage design
- All external parts zinc plated
- Port 2 to 1 is the preferred flow path



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	189 LPM (50 GPM)
Maximum Inlet Pressure	240 Bar (3500 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @ 240 Bar (3500 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +107°C (Polyurethane, EPS) (-35°F to +225°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.33 kg (0.78 lbs.)
Cavity	C16-3S (See BC Section for more details)



## Dimensions

Millimeters (Inches)



## Ordering Information

<b>16SLC1</b>	-	<b>A</b>	-	
16 Size Logic Element		Poppet Bi-Directional		Bias Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Bias Spring
100	6.9 Bar (100 PSI)
150	10.3 Bar (150 PSI)

Code	Seals
Omit	Polyurethane, EPS

Kit	Part Number
Polyurethane, EPS Seal	WRK-16-3S
Fluorocarbon Seal	WRK-16-3S-W



## General Description


Poppet Type, Bi-Directional, Normally Closed, Pilot to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- Hardened, precision ground parts for durability
- Polyurethane seals only
- No backup rings
- Low leakage design
- All external parts zinc plated
- Port 2 to 1 is the preferred flow path



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	303 LPM (80 GPM)
Maximum Inlet Pressure	240 Bar (3500 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.) @ 240 Bar (3500 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +107°C (Polyurethane, EPS) (-35°F to +225°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.81 kg (1.78 lbs.)
Cavity	C20-3S (See BC Section for more details)



## Dimensions



## Ordering Information

<b>20SLC1</b>	-	<b>A</b>	-	
20 Size Logic Element		Poppet Bi-Directional		Bias Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Bias Spring
100	6.9 Bar (100 PSI)
150	10.3 Bar (150 PSI)

Code	Seals
Omit	Polyurethane, EPS

Kit	Part Number
Polyurethane, EPS Seal	WRK-20-3S
Fluorocarbon Seal	WRK-20-3S-W

## General Description


Spool Type, Normally Closed, Pilot to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Can be used as bleed off style pressure compensated flow regulator when used with restrictor
- Various bias spring pressures available
- 1:1 pilot pressure ratio
- Hardened working parts for maximum durability
- All external parts zinc plated
- "D"-Ring eliminates backup rings



## Performance Curve

**Pressure Drop, vs. Flow (Through cartridge only)**  
**Hydraulic Oil 150 SSU @ 100F (32cSt)**




## Specifications

<b>Rated Flow</b>	57 LPM (15 GPM)
<b>Maximum Inlet Pressure</b>	350 Bar (5000 PSI)
<b>Leakage at 150 SSU (32 cSt)</b>	82 ml/min.@207 Bar (3000 PSI)
<b>Cartridge Material</b>	All parts steel. All operating parts hardened steel.
<b>Operating Temp. Range/Seals</b>	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
<b>Fluid Compatibility/Viscosity</b>	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
<b>Filtration</b>	ISO-4406 18/16/13, SAE Class 4
<b>Approx. Weight</b>	0.02 kg (0.045 lbs.)
<b>Cavity</b>	C10-3S (See BC Section for more details)



## Dimensions



## Ordering Information

**LE102A**

10 Size  
Logic Element



Bias  
Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Bias Spring
01	1.7 Bar (25 PSI)
05	3.5 Bar (50 PSI)
<b>07</b>	<b>6.9 Bar (100 PSI)</b>
<b>10</b>	<b>10.3 Bar (150 PSI)</b>
15	15 Bar (218 PSI)
20	20 Bar (290 PSI)

Code	Seals
<b>Omit</b>	<b>"D-Ring"</b>
Kit	
Part Number	
D-Ring Seal	SK10-3S
Nitrile Seal	SK10-3S
Fluorocarbon Seal	SK10-3SV


## General Description

Spool Type, Normally Closed, Pilot to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features



- High flow capacity
- Used as high flow switching or metering element
- Can be used as bleed off style pressure compensated flow regulator when used with restrictor
- More stable than poppet type
- Various switching pressures available
- 1:1 pilot pressure ratio
- Hardened working parts for maximum durability
- All external parts zinc plated

## Performance Curve (Through cartridge only) Vented Open Pressure Drop vs. Flow 1 to 2




## Specifications

Rated Flow	400 LPM (106 GPM)
Nominal Flow @ 7 Bar (100 PSI)	270 LPM (71 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	82cc/min. (5 cu in/min.) @ 240 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.33 kg (0.78 lbs.)
Cavity	C16-3S (See BC Section for more details)



## Dimensions



## Ordering Information

<b>R06E3</b>		<b>N</b>
16 Size Logic Element	Switching Pressure	Seals

Code	Switching Pressure Non Adjustable Preset
10.0	10.0 Bar (145 PSI)
15.0	15.0 Bar (218 PSI)

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30508N-1
Fluorocarbon Seal	SK30508V-1


## General Description

Spool Type, Normally Closed, Pilot to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features




- High flow capacity
- Can be used as high flow switching or metering element
- Can be used as bleed off style pressure compensated flow regulator when used with restrictor
- Various switching pressures available
- 1:1 pilot pressure ratio
- Hardened working parts for maximum durability
- All external parts zinc plated

## Performance Curve (Through cartridge only) Vented Open Pressure Drop vs. Flow 1 to 2




## Specifications

Rated Flow	500 LPM (132 GPM)
Nominal Flow @ 7 Bar (100 PSI)	340 LPM (90 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	82ml/min. @ 240 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.69 kg (1.52 lbs.)
Cavity	C20-3S (See BC Section for more details)



## Dimensions



## Ordering Information

<b>R08E3</b>		<b>N</b>
20 Size Logic Element	Switching Pressure	Seals

Code	Switching Pressure Non Adjustable Preset
10.0	10.0 Bar (145 PSI)
15.0	15.0 Bar (218 PSI)

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30512N-1
Fluorocarbon Seal	SK30512V-1

## General Description


Spool Type, Normally Closed, Vent to Open Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Can be used as main stage for a pilot operated relief or sequence valve
- Integral pilot flow filter
- Various bias spring pressures available
- 1:1 pilot pressure ratio
- Hardened working parts for maximum durability
- All external parts zinc plated
- "D"-Ring eliminates backup rings



## Performance Curve

**Pressure Drop, vs. Flow (Through cartridge only)**  
**Hydraulic Oil 150 SSU @ 100F (32cSt)**




## Specifications

<b>Rated Flow</b>	57 LPM (15 GPM)
<b>Maximum Inlet Pressure</b>	350 Bar (5000 PSI)
<b>Leakage @ 150 SSU (32 cst)</b>	82 ml/min.@207 Bar (3000 PSI)
<b>Cartridge Material</b>	All parts steel. All operating parts hardened steel.
<b>Operating Temp. Range/Seals</b>	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
<b>Fluid Compatibility/ Viscosity</b>	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
<b>Filtration</b>	ISO-4406 18/16/13, SAE Class 4
<b>Approx. Weight</b>	.14 kg (.30 lbs.)
<b>Cavity</b>	C10-3S (See BC Section for more details)



## Dimensions

Millimeters (Inches)



## Ordering Information

**LE102B**

10 Size  
Logic Element



Bias  
Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Bias Spring
01	1.7 Bar (25 PSI)
05	3.5 Bar (50 PSI)
<b>07</b>	<b>6.9 Bar (100 PSI)</b>
<b>10</b>	<b>10.3 Bar (150 PSI)</b>
15	15 Bar (218 PSI)
20	20 Bar (290 PSI)

Code	Seals
<b>Omit</b>	<b>"D-Ring"</b>

Kit	Part Number
D-Ring Seal	SK10-3S
Nitrile Seal	SK10-3S
Fluorocarbon Seal	SK10-3SV



## General Description


Spool Type, Normally Open, Vent to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Can be used for inline pressure compensated flow control when used with restrictor (refer to application)
- Various bias spring pressures available
- 1:1 pilot pressure ratio
- Hardened working parts for maximum durability
- All external parts zinc plated
- "D"-Ring eliminates backup rings



## Performance Curve

**Pressure Drop, vs. Flow** (Through cartridge only)  
**Hydraulic Oil 150 SSU @ 100F (32cSt)**




## Specifications

<b>Rated Flow</b>	57 LPM (15 GPM)
<b>Maximum Inlet Pressure</b>	350 Bar (5000 PSI)
<b>Leakage at 150 SSU (32 cSt)</b>	82 ml/min. @ 207 Bar (3000 PSI)
<b>Cartridge Material</b>	All parts steel. All operating parts hardened steel.
<b>Operating Temp. Range/Seals</b>	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
<b>Fluid Compatibility/Viscosity</b>	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
<b>Filtration</b>	ISO-4406 18/16/13, SAE Class 4
<b>Approx. Weight</b>	0.14 kg (0.3 lbs.)
<b>Cavity</b>	C10-3S (See BC Section for more details)



## Dimensions



## Ordering Information

**LE103A**

10 Size  
Logic Element



Bias  
Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Bias Spring
01	1.7 Bar (25 PSI)
05	3.5 Bar (50 PSI)
<b>07</b>	<b>6.9 Bar (100 PSI)</b>
<b>10</b>	<b>10.3 Bar (150 PSI)</b>
15	15 Bar (218 PSI)
20	20 Bar (290 PSI)

Code	Seals
Omit	<b>"D-Ring"</b>

Kit	Part Number
D-Ring Seal	SK10-3S
Nitrile Seal	SK10-3S
Fluorocarbon Seal	SK10-3SV

## General Description


Spool Type , Normally Open, Vent to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Can be used for inline pressure compensated flow control when used with restrictor (refer to application)
- More stable than poppet type
- Range of spring ratings available
- 1:1 pilot ratio
- Hardened working parts for maximum durability
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow (Through cartridge only)**




## Specifications

Rated Flow	160 LPM (42 GPM)
Nominal Flow @ 7 Bar (100 PSI)	90 LPM (24 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Leakage at 150 SSU (32 cSt)	125ml/min. @ 100 Bar (1450 PSI)
Switching Pressure	See ordering information
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.37 kg (0.82 lbs.)
Cavity	C16-3S (See BC Section for more details)



## Dimensions



## Ordering Information

<b>R06H3</b>		<b>N</b>
16 Size Logic Element	Switching Pressure	Seals

Code	Switching Pressure Non Adjustable Preset
10.0	10.0 Bar (145 PSI)
15.0	15.0 Bar (218 PSI)

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30508N-1
Fluorocarbon Seal	SK30508V-1



## General Description


Spool Type, Normally Open, Vent to Close Logic Element. For additional information see Technical Tips on pages LE2-LE7.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Can be used as pressure regulator with mainstage controlled remotely by a pilot relief valve or a proportional valve
- Integral pilot flow filter
- Various bias spring pressures available
- 1:1 pilot pressure ratio
- Hardened working parts for maximum durability
- All external parts zinc plated
- "D"-Ring eliminates backup rings



## Performance Curve

**Pressure Drop, vs. Flow** (Through cartridge only)  
**Hydraulic Oil 150 SSU @ 100F (32cSt)**




## Specifications

<b>Rated Flow</b>	57 LPM (15 GPM)
<b>Maximum Inlet Pressure</b>	350 Bar (5000 PSI)
<b>Leakage at 150 SSU (32 cSt)</b>	82 ml/min.@207 Bar (3000 PSI)
<b>Cartridge Material</b>	All parts steel. All operating parts hardened steel.
<b>Operating Temp. Range/Seals</b>	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
<b>Fluid Compatibility/Viscosity</b>	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
<b>Filtration</b>	ISO-4406 18/16/13, SAE Class 4
<b>Approx. Weight</b>	0.14 kg (0.3 lbs.)
<b>Cavity</b>	C10-3S (See BC Section for more details)



## Dimensions



## Ordering Information

**LE103B**

10 Size  
Logic Element





Bias  
Spring

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Bias Spring
01	1.7 Bar (25 PSI)
05	3.5 Bar (50 PSI)
<b>07</b>	<b>6.9 Bar (100 PSI)</b>
<b>10</b>	<b>10.3 Bar (150 PSI)</b>
15	15 Bar (218 PSI)
20	20 Bar (290 PSI)

Code	Seals
<b>Omit</b>	<b>"D-Ring"</b>
Kit	
D-Ring Seal	SK10-3S
Nitrile Seal	SK10-3S
Fluorocarbon Seal	SK10-3SV

Directional Control Valves

	SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
	DH103 .....	C10-4 .....	3 Way, External Pilot, Normally Open, Vent to Atmosphere.....	38/10 .....	240/3500 .....	DC2-DC3
	N5A125 .....	5A.....	3 Way, 2 Position, External Drain, Open Transition.....	160/42 .....	420/6000 .....	DC4
	N5A300 .....	100-1 .....	3 Way, 2 Position, External Drain, Open Transition.....	400/105 .....	420/6000 .....	DC5

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description

3-Way Pilot Operated Spool Valve. The DH103A/B/C Series Valves are used in normally closed or normally open directional control three way circuits requiring remote pilot actuation. The DH103 Series Valves are used to direct flow alternately from either side of a closed loop transmission for cooling or filtering. All external parts are zinc plated.

**Operation** (pressure at port 4 additive to spring)

### DH103A (Normally Open)

- Neutral (Deactivated)  
Port (3) open to port (2), port (4) is blocked.
  - Activated with pilot pressure at port (1):  
Port (3) open to port (4), port (2) blocked.
- Note: There is an air breather vent plug in the end cap to allow for air pressure equalization in the spring chamber

### DH103B (Normally Closed)



- Neutral (Deactivated)  
Port (4) open to port (3), port (2) is blocked.
- Activated with pilot pressure at port (1):  
Port (3) open to port (2), port (4) blocked.

### DH103C (Normally Open)

- Neutral (Deactivated)  
Port (3) open to port (2), port (4) is blocked.
- Activated with pilot pressure at port (1):  
Port (3) open to port (4), port (2) blocked.



## Specifications

Rated Flow	38 LPM (10 GPM)
Maximum Inlet Pressure	345 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	50cc/min. @ 240 Bar (3500 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.17 kg (0.37 lbs.)
Cavity	C10-4 (See BC Section for more details)





"A" SPOOL — DH103A

"B" SPOOL — DH103B




"C" SPOOL — DH103C




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Performance Curve



FLOW DIRECTION	SPOOL NO.		
	A	B	C
SPOOL SHIFTED	3 → 4 c	2 → 3 d	3 → 4 c
SPOOL NEUTRAL	2 → 3 a	3 → 4 b	2 → 3 a

Dimensions    Millimeters (Inches)



Ordering Information

**DH103**

10 Size  
Pilot Operated  
Spool Valve



Spool  
Type



Shifting  
Pressure

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code / Spool Type	
<b>A</b> Normally open 2 position, vent to atmosphere.	
<b>B</b> Normally closed 2 position, internally drain.	
<b>C</b> Normally open, 2 position, internally drain.	

Code	Cracking Pressure
Omit	5.5 Bar (80 PSI)
16	11 Bar (160 PSI)

Code	Seals
Omit	Nitrile

Kit	Part Number
Nitrile Seal	SK10-4
Fluorocarbon Seal	SK10-4V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description


Pilot Operated Directional Valve, 3-Way, 2 Position, External Drain, Open Transition.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Range of spring settings available
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	160 LPM (42 GPM)
Nominal Flow @ 7 Bar (100 PSI)	90 LPM (24 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Pilot Switching Pressure	See ordering information
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.33 kg (0.76 lbs.)
Cavity	5A (See BC Section for more details)



## Dimensions



## Ordering Information

<b>N5A125</b>	—	<b>N</b>
Directional Valve (All Ports Open)		Pilot Switching Pressure Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Switching Pressure
<b>6.9</b>	<b>6.9 Bar (100 PSI) Std.</b>
10.0	10.0 Bar (145 PSI)

Code	Seals
<b>N</b>	<b>Nitrile</b>

Kit	Part Number
Nitrile Seal	SK30103N-1
Fluorocarbon Seal	SK30103V-1

*Order Bodies Separately  
See section BC*

<b>LB10</b>	<b>321</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
321	3/4" SAE (main) 1/4" SAE (aux)

Code	Body Material
S	Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description


Pilot Operated Directional Valve, 3-Way, 2 Position, External Drain, Open Transition.

## Features

- High flow capacity
- Used as high flow switching or metering element
- Range of spring settings available
- All external parts zinc plated



## Performance Curve

**Pressure Drop vs. Flow** (Through cartridge only)




## Specifications

Rated Flow	400 LPM (105 GPM)
Nominal Flow @ 7 Bar (100 PSI)	270 LPM (71 GPM)
Maximum Inlet Pressure	420 Bar (6000 PSI)
Pilot Switching Pressure	See ordering information
Cartridge Material	Steel operating parts hardened steel spool.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	1.00 kg (2.2 lbs.)
Cavity	100-1 (See BC Section for more details)



## Dimensions



## Ordering Information

<b>N5A300</b>	—	<b>N</b>
Directional Valve (All Ports Open)	Pilot Switching Pressure	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

Code	Switching Pressure
6.9	6.9 Bar (100 PSI) Std.
10.0	10.0 Bar (145 PSI)

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30065N-1
Fluorocarbon Seal	SK30065V-1








Order Bodies Separately  
 See section BC

<b>LB10</b>	<b>317</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
317	1-1/4" SAE (main) 3/8" SAE (aux)

Code	Body Material
S	Steel (5000 PSI)



	SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
Technical Tips.....						SV2-SV6
<b>2 WAY POPPET TYPE</b>						
	DSH081	C08-2	2 Position, 2 Way, N.C. or N.O.	30/8	350/5000	SV7-SV8
	DSH101	C10-2	2 Position, 2 Way, N.C. or N.O.	60/15	350/5000	SV9-SV10
	DSH121	C12-2	2 Position, 2 Way, N.C. or N.O.	90/24	350/5000	SV11-SV12
	DSH161	C16-2	2 Position, 2 Way, N.C. or N.O.	150/40	350/5000	SV13-SV14
	DSL201	C20-2	2 Position, 2 Way, N.C. or N.O.	260/70	250/3600	SV15-SV16
<b>2 WAY BI-DIRECTIONAL POPPET TYPE</b>						
	DSL087 (NEW)	C08-2	Bi-Directional Poppet, N.C or N.O.	1.1/3	250/3600	SV17-SV18
	GS02 81	C08-2	Bi-Directional Poppet, N.C.	34/9	350/5000	SV19-SV20
	GS04 81	2R	Bi-Directional Poppet, N.C.	68/18	350/5000	SV21-SV22
	GS06 81	C16-2	Bi-Directional Poppet, N.C.	285/75	350/5000	SV23-SV24
	GS02 86	C08-2	Bi-Directional Poppet, N.O.	34/9	350/5000	SV25-SV26
	GS04 86	2R	Bi-Directional Poppet, N.O.	68/18	350/5000	SV27-SV28
GS06 86	C16-2	Bi-Directional Poppet, N.O.	285/75	350/5000	SV29-SV30	
<b>2 WAY SPOOL TYPE</b>						
	DSH082	C08-2	2 Position, 2 Way	15/4	350/5000	SV31-SV32
	DSH102	C10-2	2 Position, 2 Way	30/8	350/5000	SV33-SV34
<b>3 WAY SPOOL TYPE</b>						
	DSH083	C08-3	2 Position, 3 Way	15/4	350/5000	SV35-SV37
	DSH103	C10-3	2 Position, 3 Way	30/8	350/5000	SV38-SV40
<b>4 WAY, 2 POSITION SPOOL TYPE</b>						
	DSH084	C08-4	2 Position, 4 Way	15/4	350/5000	SV41-SV42
	DSH104	C10-4	2 Position, 4 Way	38/10	350/5000	SV43-SV44
	DSH164	C16-4	2 Position, 4 Way	113/30	350/5000	SV45-SV46
<b>4 WAY, 3 POSITION SPOOL TYPE</b>						
	GS02 51	C08-4	3 Position, 4 Way	17/4.5	350/5000	SV47-SV48
	GS02 53	C08-4	3 Position, 4 Way	15/4	350/5000	SV49-SV50
	GS02 57	C08-4	3 Position, 4 Way	13/3.5	350/5000	SV51-SV52
	GS02 59	C08-4	3 Position, 4 Way	13/3.5	350/5000	SV53-SV54
	DSL105	C10-4	3 Position, 4 Way	26/7	250/3600	SV55-SV56
	GS04 52D	C10-4	3 Position, 4 Way	42/11	350/5000	SV57-SV58
	GS04 54D	C10-4	3 Position, 4 Way	42/11	350/5000	SV59-SV60
	GS04 57D	C10-4	3 Position, 4 Way	42/11	350/5000	SV61-SV62
	GS04 59D	C10-4	3 Position, 4 Way	42/11	350/5000	SV63-SV64

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data



## Technical Tips

### COMMON OPTIONS

As you will see, Parker offers a variety of solenoid valve products. As such, some of the options mentioned below may not be available on all valves. Consult the model coding and dimensions for each valve for more specifics. Here are some of the common options available.


**Seals:** Valves feature a Polyurethane “D”-Ring. The “D”-Ring eliminates the need for backup rings. For more information on the “D”-Ring see the Technical Data section of the catalog. The majority of the products are also available in Nitrile or Fluorocarbon seals. Contact factory for availability. You should always match the seal compatibility to the temperature and fluid being used in your application.

**Coils:** Coils can be ordered as part of the full assembly or separately. Various terminations and voltages are available. For detailed information on the coil options consult the coil section of the catalog. The ordering information for each valve will direct you to the proper coil.

**Manual Overrides:** Many of our solenoid valves are also offered with a manual override. The override allows the user to shift the valve when coil force is not available. They provide a means of shifting the solenoid valve due to a loss of power or a coil failure. Overrides are intended for infrequent usage and are not designed to be used as a primary method of valve actuation.

The most common override option for the 2 Position valves is the push & twist style shown below. With a normally closed valve or a pull style tube, the valve is in normal operation (or de-energized)


when the pin is seated in the slotted groove at the lowest position. To shift the valve manually, the operator pushes down on the knob



**Normally Closed Pull Type Tube**

and twists it counterclockwise. When the pressure is removed from the knob, an internal spring pushes the pin up the slotted groove to the upper position of the override. With a normally open valve, or push style tube, the actuation is reversed. The valve is in the normal position

(or de-energized) when the pin is in the upper position of the override. To shift the valve manually, the operator pushes




**Normally Open Push Type Tube**

## Solenoid Valves

down on the knob and twists is clockwise. Once the pin is seated in the slotted groove, the operator can remove pressure and the valve will stay actuated.

3 Position valves are offered with a Push / Pull style override. This override is not detented. Springs hold the spool of the valve in the center position of the valve. When the knob is pulled, the spool is moved upward simulating the action of the upper coil. When the override is pushed, the spool moves downward simulating the action of the lower coil. When no pressure is applied to the knob, it centers the spool.



**Screens:** 2 way valves can be ordered with a small mesh screen (60 x 60 mesh) placed over the cage of the cartridge valve. This screen is intended for cursory protection of the internal components of the solenoid valve. It should not be used as the primary method of filtration. The mesh catches small pieces of debris that could impede spool or poppet movement. Note that a screen will trap debris from both directions. Thus, any debris coming from the nose of the cartridge would be trapped inside the valve. As such, we recommend that screens be implemented in only applications where hydraulic fluid passes through the cartridge from the side of the cage to the nose. It should also be noted that the pressure drop through the cartridge will be increased slightly due to the small restriction of the mesh. As the screen fills with debris, pressure drop will continue to rise.





## PRODUCT TYPES / APPLICATIONS

### Two Way Poppet Valves

Two way poppet valves are pilot operated, low leakage solenoid actuated valves. Two way poppet valves control the flow of a two way function by blocking flow in one direction (similar to a check valve). They are generally selected due to their low leakage and ability to meet higher flow requirements. Poppet valves are often used on single operation actuators or in unloading functions. They are available in normally closed and normally open types. In addition, free reverse flow and fast response versions are available.

#### Normally Closed Poppet



Normally closed two way poppet valves act as a check valve when de-energized, blocking flow from one direction and allowing restricted free flow in the reverse condition. When energized, the poppet lifts allowing free flow from the side to the nose of the cartridge. Should the application require free flow in both directions, the free reverse flow option should be chosen.



**OPERATION** - The valve pilot is held on its seat by spring force, blocking pilot flow. This allows pressure at the inlet (port 2) to hold the poppet on its seat, thus, preventing flow through the valve (2-1). If the nose of the cartridge (port 1) is pressurized, the pressure will overcome the spring force, pushing the poppet off of its seat, allowing free flow through the cartridge (1-2). When the coil is energized, the valve pilot is pulled off of its seat. This vents the pressure inside the poppet to port 1, creating a pressure imbalance across the main poppet. This differential lifts the poppet allowing flow from the side to nose (2-1). Since poppet valves are piloted operated, a minimum amount of pressure differential (25-50 psi) and flow between ports 2 and 1 must be present to overcome the spring and lift the poppet.

#### Normally Open Poppet

Normally open two way poppet valves, when de-energized, allow free flow from the side (port 2) of the cartridge to the nose (port 1). Flow in the reverse direction is restricted. Should free flow be required in both directions, the free reverse flow option should be specified. Once the coil is energized the normally open poppet valve acts as a check valve, blocking flow from one direction and allowing restricted free flow in the reverse condition.





**OPERATION** - The valve pilot is held off its seat by spring force. Pilot flow is vented to port 1, creating a pressure imbalance that moves the main poppet. This differential lifts the poppet allowing flow from the side to nose (2-1). Since poppet valves are piloted operated, a minimum amount of pressure differential (25-50 psi) between ports 2 and 1 must be present to overcome the spring and lift the poppet. When the coil is energized, the coil force overcomes the spring force to drive the valve pilot and main poppet into their seats, thus blocking flow from port 2-1. If the nose of the cartridge (port 1) is pressurized, the pressure will overcome the spring force and solenoid force, pushing the poppet off of its seat, allowing restricted flow through the cartridge (1-2).

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

**Free Reverse Flow**

The free reverse flow versions are available on both the normally closed and normally open poppet valves. As mentioned above, the operation is the same as the standard poppet valve except flow through the reverse direction is not restricted. The free reverse flow option is only needed if the application requires flow to pass through the cartridge valve from the nose to side (port 1 to port 2).

**Fast Response**



Since poppet valves are pilot operated valves, a few milliseconds are needed to move the pilot and allow the poppet to lift. Should a faster response time be required on normally closed poppet valves, this option can be chosen. The fast response is accomplished by reducing the movement of the pilot. Thus, the flow capacity of the poppet valve is also decreased.

**Two Way Spool Valves**


Two way spool valves are direct acting, fast responding solenoid actuated valves. Like the poppet valves described earlier, they block the flow of a two way function. Unlike two way poppet valves, spool valves block flow from both the side port and the nose port. They do not have the check like function of the poppet valve, thus they are either open or closed. Spool valves are directed operated, so they respond more quickly to coil voltage than poppet valves. Spool valves operate via a sliding spool, thus, some leakage will be present due to the required spool clearance. Spool valves block flow in both directions, but the preferred flow path is still from the side of the cartridge to the nose due to the flow forces acting on the spool. Two way spool valves are available in normally open and normally closed types.

**Normally Closed Spool**

When de-energized, the spool is positioned by the spring force to cover both the side (2) and nose (1) ports of the valve. Thus, no flow is allowed from either direction. Once the coil is energized, the spool shifts exposing a flow path between the two ports. Flow can then be passed through the valve from either direction.

**Normally Open Spool**

When de-energized, the spool is positioned by the spring force so that a flow path between the side (2) and nose (1) ports is exposed, allowing flow through the valve from either direction. Once the coil is energized, the spool shifts to cover both the side (2) and nose (1) ports of the valve. Thus, no flow is allowed from either direction.



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC


Bodies &  
Cavities

TD


Technical  
Data

**Bi-Directional Poppet Valve**

Bi-directional poppet valves combine the dual blocking function of spool valves with the lower leakage capabilities of poppet valves. These valves also have a limited flow capacity compared to standard poppet or spool valves.


**Two Position, Three Way Spool Valve**

Three way spool solenoid valves provide directional control of flow. Each three way valve has a special internal spool which connects two of the three valve ports. When actuated, the spool connects a different combination of valve ports. These valves are often used for raise and lower functions of a single acting cylinder, control of a uni-directional motor, or as a circuit selector.




**OPERATION** - In the de-energized mode, the spool is positioned by spring force. When energized, the coil force directly shifts the spool against the spring, thus changing the flow through the valve. Each spool type can be used as a normally open, normally closed, or selector valve. To explain this we will review the DSL103A which is pictured here. When the valve is de-energized, ports 1 and 2 are open to one another. When energized, ports 1 and 3 are connected.


Thus, if we use port 3 as our pressure port, we have a **normally closed valve**. The pressure port (3) is blocked, while the actuator port (1) is drained to tank (2).



If we use port 2 as our pressure port, we have a **normally open valve**. The pressure port (2) is connected to the actuator port (1), and the tank port (3) is blocked.



If we use port 1 as our pressure port, we have a **selector valve**. The pressure port (1) is either connected to port (2) or port (3). Thus, it is "selecting" which port will get the system pressure and flow.





Note that in all three examples, we were using the same valve. The flow forces acting on the spool change depending on which port is pressurized. Thus, if you will be shifting the three way valve under full flow and pressure, it is important to review the shift limit characteristics for the flow paths you have chosen to be sure the coil has enough force to shift the spool. Various spools are available in this catalog to maximize the flow and pressure capacities for the desired flow function.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

### Two Position, Four Way Spool Valve


Four way spool solenoid valves provide directional control of flow. Each four way valve has a special internal spool which connects some combination of the four valve ports together. When actuated, the spool connects a different combination of valve ports. These valves are often used for the raise / lower function of a double acting cylinder, or as a forward / reverse function of bi-directional motors.



**OPERATION** - In the de-energized mode, the spool is positioned by spring force. When energized, the coil force directly shifts the spool against the spring, thus changing the flow through the valve. Each spool type is customized to provide the flow combination desired. The flow forces acting on the spool change depending on which port is pressurized. Thus, if you will be shifting the four way valve under full flow and pressure, it is important to review the shift limit characteristics for the flow paths you have chosen to ensure the coil has enough force to shift the spool. Various spools are shown in this catalog to maximize the flow and pressure capacities for the desired flow function.

### Three Position, Four Way Spool Valve

Three position, four way spool solenoid valves provide directional control of flow. Each four way valve has a special internal spool which connects some combination of the four ports together. When one coil is actuated, the spool connects a different combination of valve ports. When the other coil is actuated a third combination of valve ports are connected. These valves are often used for the raise / lower function of a double acting cylinder, or as a forward / reverse function of bi-directional motors. The center position can be used to stop the actuator in mid-stroke, or dump the pump flow.



**OPERATION** - In the de-energized mode, the spool is positioned by spring force. When energized, the coil force directly shifts the against the spring, thus changing the flow through the valve. Each spool type is customized to provide the flow combination desired. The flow forces acting on the spool change depending on which port is pressurized. Thus, if you will be shifting the four way valve under full flow and pressure, it is important to review the shift limit characteristics for the flow paths you chosen to ensure the coil has enough force to shift the spool. Various spools are shown in this catalog to maximize the flow and pressure capacities for the desired flow function.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data



## General Description

2-Way Poppet Valves.



For additional information see Technical Tips on pages SV2-SV6.

## Features

- Replaceable, one piece encapsulated, coils with minimal amperage draw
- Variety of coil terminations and voltages
- Variety of manual override options available
- Polyurethane "D"-Ring eliminates need for backup rings
- Spherical poppet for low leakage
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated



## Specifications

Rated Flow	30 LPM (8 GPM)		
Maximum Inlet Pressure	350 Bar (5000 PSI)		
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)		
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).		
Response Time	<b>C, CR</b> <b>N, NR</b>	<b>Energized</b> 50 ms 50 ms	<b>De-Energized</b> 50 ms 40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.		
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)		
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)		
Filtration	ISO 4406 18/16/13, SAE Class 4		
Approx. Weight	.11 kg (.25 lbs.)		
Cavity	C08-2 (See BC Section for more details)		




## Performance Curves

Pressure Drop vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

**DSH081**

08 Size  
Solenoid Valve



Style



Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

*Order Bodies Separately  
See section BC*

Code / Style	
<b>C</b>	Normally Closed Metered reverse flow
<b>CR</b>	Normally Closed Free reverse flow
<b>N</b>	Normally Open Metered reverse flow
<b>NR</b>	Normally Open Free reverse flow

Code	Override Options
<b>Omit</b>	<b>None</b>
T	Push & Twist (N.C. & N.O.)

<b>B08</b>	<b>2</b>	<b>6T</b>
08 size	2-Way Cavity	Port Size

Code	Seals
<b>Omit</b>	<b>"D"-Ring</b>

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V



## General Description

2-Way Poppet Valves.




For additional information see Technical Tips on pages SV2-SV6.

## Features

- Low hysteresis
- Replaceable, one piece encapsulated coils with minimal amperage draw
- Various coil terminations and voltages
- Various manual override options
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated



## Specifications

Rated Flow	60 LPM (15 GPM)		
Maximum Inlet Pressure	350 Bar (5000 PSI)		
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)		
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).		
Response Time	<b>C, CR</b> <b>N, NR</b>	<b>Energized</b> 80 ms 70 ms	<b>De-Energized</b> 150 ms 35 ms
Cartridge Material	All parts steel. All operating parts hardened steel.		
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)		
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)		
Filtration	ISO 4406 18/16/13, SAE Class 4		
Approx. Weight	.20 kg (0.41 lbs.)		
Cavity	C10-2 (See BC Section for more details)		




## Performance Curves

Pressure Drop vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

**DSH101**

10 Size  
Solenoid Valve

Style

Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

*Order Bodies Separately  
See section BC*

Code / Style	
<b>C</b> Normally Closed Metered reverse flow	
<b>CR</b> Normally Closed Free reverse flow	
<b>N</b> Normally Open Metered reverse flow	
<b>NR</b> Normally Open Free reverse flow	

Code	Override Options
Omit	None
T	Push & Twist (N.C. & N.O.)

Code	Seals
Omit	"D"-Ring

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size
Code	Port Size / Body Material			
8T	SAE-8 / Steel (5000 PSI)			

Kit	Part Number
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

## General Description

2-Way Poppet Valves.



For additional information see Technical Tips on pages SV2-SV6.

## Features

- Low hysteresis
- Replaceable, one piece encapsulated coils with minimal amperage draw
- Various coil terminations and voltages
- Various manual override options
- All external parts zinc plated



## Specifications

Rated Flow	90 LPM (24 GPM)		
Maximum Inlet Pressure	350 Bar (5000 PSI)		
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)		
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).		
Response Time	<b>C, CR</b> <b>N, NR</b>	<b>Energized</b> 100 ms 70 ms	<b>De-Energized</b> 150 ms 150 ms
Cartridge Material	All parts steel. All operating parts hardened steel.		
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)		
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)		
Filtration	ISO 4406 18/16/13, SAE Class 4		
Approx. Weight	.29 kg (.65 lbs.)		
Cavity	C12-2 (See BC Section for more details)		







## Performance Curves

Pressure Drop vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

**DSH121**

12 Size  
Solenoid Valve



Style



Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Order Bodies Separately  
See section BC

Code / Style	
<b>C</b>	Normally Closed Metered reverse flow
<b>CR</b>	Normally Closed Free reverse flow
<b>N</b>	Normally Open Metered reverse flow
<b>NR</b>	Normally Open Free reverse flow

Code	Override Options
<b>Omit</b>	<b>None</b>
T	Push & Twist (N.C. & N.O.)

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

<b>B12</b>	<b>2</b>	<b>8T</b>
12 size	2-Way Cavity	Port Size
Code	Port Size / Body Material	
8T	SAE-8 / Steel (5000 PSI)	

Kit	Part Number
Nitrile Seal	SK12-2
Fluorocarbon Seal	SK12-2V

## General Description

2-Way Poppet Valves.



For additional information see Technical Tips on pages SV2-SV6.

## Features

- Replaceable, one piece encapsulated coils with minimal amperage draw
- Various coil terminations and voltages
- Various manual override options
- All external parts zinc plated
- New 350 Bar (5000 PSI) rating



## Specifications

Rated Flow	150 LPM (40 GPM)		
Maximum Inlet Pressure	350 Bar (5000 PSI)		
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)		
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).		
Response Time	<b>C, CR</b> <b>N, NR</b>	<b>Energized</b> 50 ms 45 ms	<b>De-Energized</b> 130 ms 75 ms
Cartridge Material	All parts steel. All operating parts hardened steel.		
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)		
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)		
Filtration	ISO 4406 18/16/13, SAE Class 4		
Approx. Weight	.34 kg (.75 lbs.)		
Cavity	C16-2 (See BC Section for more details)		



## Performance Curves

Pressure Drop vs. Flow (Through cartridge only)



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics


**BC**

Bodies &  
Cavities

**TD**

Technical  
Data

Dimensions    Millimeters (Inches)



Ordering Information

**DSH161**

16 Size  
Solenoid Valve

Style

Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Order Bodies Separately  
See section BC

Code / Style	
<b>C</b>	Normally Closed Metered reverse flow
<b>CR</b>	Normally Closed Free reverse flow
<b>N</b>	Normally Open Metered reverse flow
<b>NR</b>	Normally Open Free reverse flow

Code	Override Options
<b>Omit</b>	<b>None</b>
T	Push & Twist (N.C. & N.O.)

Code	Seals
<b>Omit</b>	<b>Nitrile</b>

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 size		2-Way Cavity		Port Size
Code	Port Size / Body Material			
16T	SAE-16 / Steel (5000 PSI)			

Kit	Part Number
Nitrile Seal	SK16-2
Fluorocarbon Seal	SK16-2V





## General Description

2-Way Poppet Valves.

For additional information see Technical Tips on pages SV2-SV6.

## Features

- Replaceable, one piece encapsulated coils with minimal amperage draw
- Various coil terminations and voltages
- Various manual override options
- All external parts zinc plated
- New 250 Bar (3600 PSI) rating




## Specifications

Rated Flow	260 LPM (70 GPM)		
Maximum Inlet Pressure	250 Bar (3600 PSI)		
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)		
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).		
Response Time	<b>C, CR</b> <b>N, NR</b>	<b>Energized</b> 350 ms 300 ms	<b>De-Energized</b> 160 ms 45 ms
Cartridge Material	All parts steel. All operating parts hardened steel.		
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)		
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)		
Filtration	ISO 4406 18/16/13, SAE Class 4		
Approx. Weight	.34 kg (.75 lbs.)		
Cavity	C20-2 (See BC Section for more details)		





## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)





Dimensions    Millimeters (Inches)



Ordering Information

DSL201

20 Size  
Solenoid Valve



Style



Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Order Bodies Separately  
See section BC

Code / Style	
<b>C</b> Normally Closed Metered reverse flow	
<b>CR</b> Normally Closed Free reverse flow	
<b>N</b> Normally Open Metered reverse flow	
<b>NR</b> Normally Open Free reverse flow	

Code	Override Options
Omit	None
T	Push & Twist (N.C. & N.O.)

Code	Seals
Omit	Nitrile

B20	2	20T
20 size	2-Way Cavity	Port Size

Code	Port Size / Body Material
20T	SAE-20 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK20-2
Fluorocarbon Seal	SK20-2V

## General Description

2-Way Poppet Valves.




For additional information see Technical Tips on pages SV2-SV6.

## Features

- Replaceable, one piece encapsulated, coils with minimal amperage draw
- Variety of coil terminations and voltages
- Polyurethane "D"-Ring eliminates need for backup rings
- Conical poppet for low leakage
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated


## Specifications

Rated Flow	1.1 LPM (0.3 GPM)									
Maximum Input Pressure at Port 1	250 Bar (3600 PSI)									
Leakage at 150 SSU (32 cSt)	5 drops/min. (0.33 cc/min.) @ 250 Bar (3600 PSI)									
Minimum Operating Voltage, CCXXX Coil	85% of rated voltage at 20°C (72°F).									
Response Time	<table><tr><td></td><td><b>Energized</b></td><td><b>De-Energized</b></td></tr><tr><td><b>C</b></td><td>30 ms</td><td>30 ms</td></tr><tr><td><b>N</b></td><td>30 ms</td><td>30 ms</td></tr></table>		<b>Energized</b>	<b>De-Energized</b>	<b>C</b>	30 ms	30 ms	<b>N</b>	30 ms	30 ms
	<b>Energized</b>	<b>De-Energized</b>								
<b>C</b>	30 ms	30 ms								
<b>N</b>	30 ms	30 ms								
Cartridge Material	All parts steel. All operating parts hardened steel.									
Operating Temp. Range/Seals	-37°C to +93°C (“D” ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)									
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)									
Filtration	ISO 4406 18/16/13, SAE Class 4									
Approx. Weight	.11 kg (.25 lbs.)									
Cavity	C08-2 (See BC Section for more details)									




## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

DSL087

08 Size  
Solenoid Valve



Style



Override  
Option



Screens

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.  
**REQUIRES LOW WATT (CCS) Coil**

Code	Style
C	Normally Closed
N	Normally Open

Code	Override Options
Omit	None
M	Push Type with Flush Rod (N.O. Only)

Code	Seals
Omit	D-ring

Code	Screen
Omit	None
S	Screen

Kit	Part Number
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Order Bodies Separately  
See section BC

B08	—	2	—	6T
08 size		2-Way Cavity		Port Size



Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description

2-Way, 2 Position, Normally Closed, Bi-Directional Poppet Valve. For additional information see Technical Tips on pages SV2-SV6.

## Features

- Built-in thermal relief set at 36 Bar (500 PSI) above rated pressure
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Coil is interchangeable with 04 and 06 series poppet valves; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	<b>2 to 1</b> 34 LPM (9 GPM) <b>1 to 2</b> 19 LPM (5 GPM)
Maximum Inlet Pressure	<b>81</b> 350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	<b>Open</b> 40 ms <b>Close</b> 40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.14 kg (.31 lbs.)
Cavity	C08-2 (See BC Section for more details)

## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS02</b>	<b>81</b>		<b>0</b>	<b>N</b>
08 Size Solenoid Valve	Style Normally Closed	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
81	High Pressure ('SP' Coil)

Code	Override Options
0	None
1	Detented

Code	Screen
0	None

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30088N-1
Fluorocarbon Seal	SK30088V-1




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

2-Way, 2 Position, Normally Closed, Bi-Directional Poppet Valve. For additional information see Technical Tips on pages SV2-SV6.

## Features

- Built-in thermal relief set at 36 Bar (500 PSI) above rated pressure
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Coil is interchangeable with 02 and 06 series poppet valves; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	<b>2 to 1</b> 68 LPM (18 GPM) <b>1 to 2</b> 46 LPM (12 GPM)
Maximum Inlet Pressure	<b>81</b> 350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	See Performance Curves
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.17 kg (.37 lbs.)
Cavity	2R (See BC Section for more details)

## Performance Curves


### Pressure Drop vs. Flow (Through cartridge only)



### Response Time vs. Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS04</b>	<b>81</b>		<b>0</b>	<b>N</b>
10 Size Solenoid Valve	Style Normally Closed	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
81	High Pressure ('SP' Coil)

Code	Override Options
0	None
2	Non-Detented

Code	Screen
0	None

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>BW14</b>	-	<b>2</b>	-	<b>8T</b>
14 size		2-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30113N-1
Fluorocarbon Seal	SK30113V-1

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data





## General Description

2-Way, 2 Position, Normally Closed, Bi-Directional Poppet Valve. For additional information see Technical Tips on pages SV2-SV6.

## Features

- Built-in thermal relief set at 36 Bar (500 PSI) above rated pressure
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Coil is interchangeable with 02 and 04 series poppet valves; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	285 LPM (75 GPM)
Maximum Inlet Pressure	<b>81</b> 350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	9 drops/min. (.58 cc/min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	See Performance Curves
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	0.4 kg (.88 lbs.)
Cavity	C16-2 (See BC Section for more details)

## Performance Curves


### Pressure Drop vs. Flow (Through cartridge only)



### Response Time vs. Flow



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS06</b>	<b>81</b>		<b>0</b>	<b>N</b>
16 Size Solenoid Valve	Style Normally Closed	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
81	High Pressure ('SP' Coil)

Code	Override Options
0	None
2	Non-Detented

Code	Screen
0	None

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 size		2-Way Cavity		Port Size

Code	Port Size / Body Material
16T	SAE-16 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30089N-1
Fluorocarbon Seal	SK30089V-1



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

2-Way, 2 Position, Normally Open, Bi-Directional Poppet Valve. For additional information see Technical Tips on pages SV2-SV6.

## Features

- Built-in thermal relief set at 36 Bar (500 PSI) above rated pressure
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Coil is interchangeable with 04 and 06 series poppet valves; Symmetrical coil can be reversed without affecting performance.




## Specifications



Rated Flow	<b>2 to 1</b> 34 LPM (9 GPM) <b>1 to 2</b> 19 LPM (5 GPM)
Maximum Inlet Pressure	<b>86</b> 350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	<b>Open</b> 40 ms <b>Close</b> 40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.14 kg (.31 lbs.)
Cavity	C08-2 (See BC Section for more details)

## Performance Curve

Pressure Drop vs. Flow (Through cartridge only)



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS02</b>	<b>86</b>		<b>0</b>	<b>N</b>
08 Size Solenoid Valve	Style Normally Open	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
86	High Pressure ('SP' Coil)

Code	Override Options
0	None
1	Manual Override

Code	Screen
0	None

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30088N-1
Fluorocarbon Seal	SK30088V-1




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

2-Way, 2 Position, Normally Open, Bi-Directional Poppet Valve. For additional information see Technical Tips on pages SV2-SV6.

## Features

- Built-in thermal relief set at 36 Bar (500 PSI) above rated pressure
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Coil is interchangeable with 02 and 06 series poppet valves; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	<b>2 to 1</b> 68 LPM (18 GPM) <b>1 to 2</b> 46 LPM (12 GPM)
Maximum Inlet Pressure	<b>86</b> 350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	See Performance Curves
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4404 18/16/13, SAE Class 4
Approx. Weight	.17 kg (.37 lbs.)
Cavity	2R (See BC Section for more details)

## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)




### Response Time vs. Flow



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>GS04</b>	<b>86</b>		<b>0</b>	<b>N</b>
10 Size Solenoid Valve	Style Normally Open	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
86	High Pressure ('SP' Coil)

Code	Screen
0	None

Code	Override Options
0	None
1	Manual Override

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>BW14</b>	<b>2</b>	<b>8T</b>
14 size	2-Way Cavity	Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30113N-1
Fluorocarbon Seal	SK30113V-1



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

2-Way, 2 Position, Normally Open, Bi-Directional Poppet Valve. For additional information see Technical Tips on pages SV2-SV6.

## Features

- Built-in thermal relief set at 36 Bar (500 PSI) above rated pressure
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Coil is interchangeable with 02 and 04 series poppet valves; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	285 LPM (75 GPM)
Maximum Inlet Pressure	<b>86</b> 350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	5 drops/min. (.33 cc/min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	See Performance Curves
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	0.4 kg (.88 lbs.)
Cavity	C16-2 (See BC Section for more details)

## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)




### Response Time vs. Flow





Dimensions    Millimeters (Inches)



Ordering Information

<b>GS06</b>	<b>86</b>		<b>0</b>	<b>N</b>
16 Size Solenoid Valve	Style Normally Open	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
86	High Pressure ('SP' Coil)

Code	Screen
0	None

Code	Override Options
0	None
1	Manual Override

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 size		2-Way Cavity		Port Size

Code	Port Size / Body Material
16T	SAE-16 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30089N-1
Fluorocarbon Seal	SK30089V-1



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

2-Way Spool Valves.



For additional information see Technical Tips on pages SV2-SV6.

## Features

- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One-piece encapsulated coil with minimal amperage draw
- Manual overrides, seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated


## Specifications

Rated Flow	<b>C</b> - 15.0 LPM (4 GPM) <b>N</b> - 8.4 LPM (2.8 GPM)									
Maximum Inlet Pressure	350 Bar (5000 PSI)									
Leakage at 150 SSU (32 cSt)	160 cc/min. (10 in <sup>3</sup> /min.) at 350 Bar (5000 PSI)									
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).									
Response Time	<table><tr><td></td><td><b>Energized</b></td><td><b>De-Energized</b></td></tr><tr><td><b>C</b></td><td>40 ms</td><td>40 ms</td></tr><tr><td><b>N</b></td><td>40 ms</td><td>40 ms</td></tr></table>		<b>Energized</b>	<b>De-Energized</b>	<b>C</b>	40 ms	40 ms	<b>N</b>	40 ms	40 ms
	<b>Energized</b>	<b>De-Energized</b>								
<b>C</b>	40 ms	40 ms								
<b>N</b>	40 ms	40 ms								
Cartridge Material	All parts steel. All operating parts hardened steel.									
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)									
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)									
Filtration	ISO 4406 18/16/13, SAE Class 4									
Approx. Weight	.11 kg (.25 lbs.)									
Cavity	C08-2 (See BC Section for more details)									




## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)






### Shift Limit Characteristics (Min. Operating Voltage)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**DSH082**

08 Size  
Solenoid Valve



Style



Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code / Style	
<b>C</b>	Normally Closed
<b>N</b>	Normally Open

Code	Override Options
<b>Omit</b>	<b>None</b>
T	Push & Twist* (N.C. & N.O.)

\*Requires Super Coil.

Code	Seals
<b>Omit</b>	<b>"D"-Ring</b>

Kit	Part Number
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V

Order Bodies Separately  
See section BC

<b>B08</b>	<b>2</b>	<b>6T</b>
08 size	2-Way Cavity	Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description




2-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features

- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One-piece encapsulated coil with minimal amperage draw
- Manual overrides, seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated


## Specifications

Rated Flow	<b>C</b> - 30 LPM (8.0 GPM) <b>N</b> - 19 LPM (5.0 GPM)									
Maximum Inlet Pressure	350 Bar (5000 PSI)									
Leakage at 150 SSU (32 cSt)	160 cc/min. (10 in <sup>3</sup> /min.)									
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).									
Response Time	<table><tr><td></td><td><b>Energized</b></td><td><b>De-Energized</b></td></tr><tr><td><b>C</b></td><td>30 ms</td><td>20 ms</td></tr><tr><td><b>N</b></td><td>50 ms</td><td>25 ms</td></tr></table>		<b>Energized</b>	<b>De-Energized</b>	<b>C</b>	30 ms	20 ms	<b>N</b>	50 ms	25 ms
	<b>Energized</b>	<b>De-Energized</b>								
<b>C</b>	30 ms	20 ms								
<b>N</b>	50 ms	25 ms								
Cartridge Material	All parts steel. All operating parts hardened steel.									
Operating Temp. Range/Seals	-37°C to +93°C (“D”-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)									
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)									
Filtration	ISO 4406 18/16/13, SAE Class 4									
Approx. Weight	.18 kg (.40 lbs.)									
Cavity	C10-2 (See BC Section for more details)									




## Performance Curves


Pressure Drop vs. Flow (Through cartridge only)



Shift Limit Characteristics (Min. Operating Voltage)



Dimensions    Millimeters (Inches)



Ordering Information

**DSH102**

10 Size  
Solenoid Valve

Style

Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code / Style
<b>C</b> Normally Closed
<b>N</b> Normally Open

Code	Override Options
<b>Omit</b>	<b>None</b>
T	Push & Twist* (N.C. & N.O.)

Code	Seals
<b>Omit</b>	<b>"D"-Ring</b>

Kit	Part Number
D-Ring Seal	SK10-2
Nitrile Seal	SK10-2
Fluorocarbon Seal	SK10-2V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 size		2-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description



3-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features

- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One piece encapsulated coils with minimal amperage draw
- Manual overrides, seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated


## Specifications

Rated Flow	<b>DSH083A</b>	
	N.O.	11.3 LPM (3.0 GPM)
	N.C.	7.5 LPM (2.0 GPM)
	Selector	7.5 LPM (2.0 GPM)
	<b>DSH083B</b>	
	N.C.	15.0 LPM (4.0 GPM)
Maximum Inlet Pressure	Selector	15.0 LPM (4.0 GPM)
	<b>DSH083N</b>	
	N.O.	11.3 LPM (3.0 GPM)
	Selector	15.0 LPM (4.0 GPM)
Leakage at 150 SSU (32 cSt)	160 cc/min. (10 in <sup>3</sup> /min.) at 350 Bar (5000 PSI) DSH083B - 250 cc/min. (15 in <sup>3</sup> /min.) DSH083N - 250 cc/min. (15 in <sup>3</sup> /min.)	
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).	
Response Time	50 ms	
Cartridge Material	All parts steel. All operating parts hardened steel.	
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)	
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)	
Filtration	ISO 4406 18/16/13, SAE Class 4	
Approx. Weight	.13 kg (.28 lbs.)	
Cavity	C08-3 (See BC Section for more details)	




## Construction/Symbols


### DSH083A



### DSH083B





### DSH083N



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**Dimensions** Millimeters (Inches)



**Ordering Information**

**DSH083**

08 Size  
Solenoid Valve



Style



Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
A	
B	
N	

Code	Override Options
Omit	None
T	Push & Twist* (N.C. & N.O.)

\*Requires Super Coil.

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK08-3
Nitrile Seal	SK08-3
Fluorocarbon Seal	SK08-3V


Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size


Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)




**Pressure Drop vs. Flow (Through cartridge only)**




**Shift Limit Characteristics (Min. Operating Voltage)**




**Pressure Drop vs. Flow (Through cartridge only)**




**Shift Limit Characteristics (Min. Operating Voltage)**



**Pressure Drop vs. Flow (Through cartridge only)**



**Shift Limit Characteristics (Min. Operating Voltage)**



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics

**BC**

Bodies &  
Cavities

**TD**

Technical  
Data

## General Description


3-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features

- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One-piece encapsulated coil with minimal amperage draw
- Manual overrides, seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated


## Specifications

Rated Flow	<b>DSH103A</b>	
	N.O.	17.0 LPM (4.5 GPM)
	N.C.	15.0 LPM (4.0 GPM)
	Selector	15.0 LPM (4.0 GPM)
	<b>DSH103B</b>	
	N.C.	30.0 LPM (8.0 GPM)
	<b>DSH103N</b>	
	N.O.	15.0 LPM (4.0 GPM)
	N.C.	15.0 LPM (4.0 GPM)
	Selector	30.0 LPM (8.0 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)	
Leakage at 150 SSU (32 cSt)	160 cc/min. (10 in <sup>3</sup> /min.) DSH103B - 250 cc/min. (15 in <sup>3</sup> /min.) DSH103N - 250 cc/min. (15 in <sup>3</sup> /min.)	
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).	
Response Time	50 ms to 100 ms	
Cartridge Material	All parts steel. All operating parts hardened steel.	
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)	
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)	
Filtration	ISO 4406 18/16/13, SAE Class 4	
Approx. Weight	.19 kg (.42 lbs.)	
Cavity	C10-3 (See BC Section for more details)	




## Construction/Symbols


**DSH103A**



**DSH103B**




**DSH103N**




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data


Dimensions    Millimeters (Inches)



Ordering Information




**DSH103**  
10 Size Solenoid Valve

  
Style

  
Override Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style
A	
B	
N	

Code	Override Options
Omit	None
T	Push & Twist (N.C. & N.O.)

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK10-3
Nitrile Seal	SK10-3
Fluorocarbon Seal	SK10-3V


Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 size		3-Way Cavity		Port Size


Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

<b>CV</b> Check Valves
<b>SH</b> Shuttle Valves
<b>LM</b> Load/Motor Controls
<b>FC</b> Flow Controls
<b>PC</b> Pressure Controls
<b>LE</b> Logic Elements
<b>DC</b> Directional Controls
<b>SV</b> Solenoid Valves
<b>PV</b> Proportional Valves
<b>CE</b> Coils & Electronics
<b>BC</b> Bodies & Cavities
<b>TD</b> Technical Data


**Pressure Drop vs. Flow (Through cartridge only)**




**Shift Limit Characteristics (Min. Operating Voltage)**




**Pressure Drop vs. Flow (Through cartridge only)**




**Shift Limit Characteristics (Min. Operating Voltage)**



**Pressure Drop vs. Flow (Through cartridge only)**



**Shift Limit Characteristics (Min. Operating Voltage)**



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**

Coils &  
Electronics

**BC**

Bodies &  
Cavities

**TD**

Technical  
Data

## General Description

4-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features


- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One-piece encapsulated coil with minimal amperage draw
- Manual overrides, seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated

## Specifications



Rated Flow	11-15 LPM (3-4 GPM) See Shift Limit Characteristics
Max. Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min. (10 in <sup>3</sup> /min.) at 350 Bar (5000 PSI) DSH084B - 240 cc/min. (15 in <sup>3</sup> /min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	Energized - 50 ms De-energized - 30 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.13 kg (.29 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Curve Selection Chart

SPOOL CODE	NEUTRAL					SHIFTED				
	4 to 1	3 to 2	2 to 1	3 to 1	3 to 4	4 to 1	3 to 2	2 to 1	3 to 1	3 to 4
B	4	3	—	—	—	—	—	2	—	4
E1	—	—	—	—	—	—	—	2	—	3
M9	—	—	3	—	1	—	—	—	4	—




DSH084B




DSH084B

## Performance Curves


Pressure Drop vs. Flow (Through cartridge only)



Shift Limit Characteristics (Min. Operating Voltage)



Dimensions    Millimeters (Inches)



Ordering Information

**DSH084**

08 Size  
Solenoid Valve

Style

Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
B	
E1	
M9	

Code	Override Options
Omit	None
T	Push & Twist*

\*Requires Super Coil.

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK08-4
Nitrile Seal	SK08-4
Fluorocarbon Seal	SK08-4V

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>4</b>	—	<b>6T</b>
08 size		4-Way Cavity		Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

## General Description


4-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features


- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One-piece encapsulated coil with minimal amperage draw
- Manual overrides, seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Polyurethane "D"-Ring eliminates need for backup rings
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated

## Specifications

Rated Flow	25 - 38 LPM (6.5 - 10 GPM) See Shift Limit Characteristics
Maximum Inlet Pressure	350 Bar (5000 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min (10 in <sup>3</sup> /min) DSH104B - 320 cc/min (19.5 in <sup>3</sup> /min)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	Energized - 30 - 60 ms De-energized - 30 - 60 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.20 kg (.44 lbs.)
Cavity	C10-4 (See BC Section for more details)




DSH104B




DSH104B

## Performance Curves

Pressure Drop vs. Flow (Through cartridge only)




Shift Limit Characteristics (Min. Operating Voltage)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



Dimensions    Millimeters (Inches)



Ordering Information

**DSH104**

10 Size  
Solenoid Valve



Style



Override  
Option

Code	Style
B	
E1	
N	

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Override Options
Omit	None
T	Push & Twist

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK10-4
Nitrile Seal	SK10-4
Fluorocarbon Seal	SK10-4V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size
Code	Port Size / Body Material			
8T	SAE-8 / Steel (5000 PSI)			

## General Description

4-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features




- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- One-piece encapsulated coil with minimal amperage draw
- Seal variations and other options available
- No dynamic seals
- Variety of coil terminations
- Nylon inserted jam-nut provides secure holding in high vibration applications
- All external parts zinc plated

## Application Note

This valve is a pilot operated spool type valve. It does not require a separate pilot supply, but does require that the work port pressure or the inlet pressure is 40-60 psi higher than port 1. In an open flowing condition, with zero load and low flow, it will require a 4-6 gpm flow to create internal pilot pressure to shift. If load pressure or system pressure is 40-60 psi higher than tank, the valve will shift. Ultimately, the valve shifts based upon pressure differential from port 3 to port 1 of 40-60 psi.


## Specifications

Rated Flow	113 LPM (30 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank (port 1)	210 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	350 cc/min (21 in <sup>3</sup> /min) De-Energ. 5.6 LPM (1.5 GPM) Energized Pilot Flow @ 207 Bar (3000 PSI)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	Pull In - 600 ms Drop Out - 130 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.59 kg (1.3 lbs.)
Cavity	C16-4 (See BC Section for more details)




## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)




### Pressure Drop vs. Flow (Through cartridge only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**DSH164**

16 Size  
Solenoid Valve



Style

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
H	
HR	

Code	Seals
Omit	Nitrile

Kit	Part Number
Nitrile Seal	SK16-4
Fluorocarbon Seal	SK16-4V

Order Bodies Separately  
See section BC

<b>B16</b>	—	<b>4</b>	—	<b>16T</b>
16 size		4-Way Cavity		Port Size




Code	Port Size / Body Material
16T	SAE-16 / Steel (5000 PSI)

## General Description

4-Way, 3 Position, Closed Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Designed to operate double acting cylinders, pilot circuits and bi-directional motors, etc.
- High flow capacity with reduced space requirements
- High pressure capability to 350 Bar (5000 PSI)
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Manual override available




## Specifications


Rated Flow	<b>High Flow/Pressure ('SP' Coil)</b> 17 LPM (4.5 GPM)
Maximum Inlet Pressure	<b>'SP' Coil</b> 350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/ 16/13, SAE Class 4
Approx. Weight	.18 kg (.40 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Performance Curves


### Pressure Drop vs. Flow (Through cartridge only)



### Operating Limits (Measured at 75% of Nominal Current)



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS02</b>	<b>51</b>		<b>0</b>	<b>N</b>
08 Size Solenoid Valve	Style	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
51	High Flow and Pressure ('SP' Coil)

Code	Override Options
0	None
1	Manual Override

Code	Screen
0	Not Available

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30078N-1
Fluorocarbon Seal	SK30078V-1

Order Bodies Separately  
See section BC

<b>B08</b>	<b>4</b>	<b>6T</b>
08 size	4-Way Cavity	Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

4-Way, 3 Position, Floating Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Designed to operate double acting cylinders, pilot circuits and bi-directional motors, etc.
- High flow capacity with reduced space requirements
- High pressure capability to 350 Bar (5000 PSI)
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Manual override available




## Specifications


Rated Flow	<b>High Flow/Pressure ('SP' Coil)</b> 15 LPM (4.0 GPM)
Maximum Inlet Pressure	<b>'SP' Coil</b> 350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.18 kg (.40 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Performance Curves


### Pressure Drop vs. Flow (Through cartridge only)



### Operating Limits (Measured at 75% of Nominal Current)



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS02</b>	<b>53</b>		<b>0</b>	<b>N</b>
08 Size Solenoid Valve	Style	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
53	High Flow and Pressure ('SP' Coil)

Code	Override Options
0	None
1	Manual Override

Code	Screen
0	Not Available

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30078N-1
Fluorocarbon Seal	SK30078V-1

Order Bodies Separately  
See section BC

<b>B08</b>	<b>4</b>	<b>6T</b>
08 size	4-Way Cavity	Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data






## General Description

4-Way, 3 Position, Tandem Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Designed to operate double acting cylinders, pilot circuits and bi-directional motors, etc.
- High flow capacity with reduced space requirements
- High pressure capability
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Manual override available




## Specifications


Rated Flow	13 LPM (3.5 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.18 kg (.40 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)




### Operating Limits (Measured at 75% of Nominal Current)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>GS02</b>	<b>57</b>		<b>0</b>	<b>N</b>
08 Size Solenoid Valve	Style	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
57	High Flow ('SP' Coil)

Code	Screen
0	Not Available

Code	Override Options
0	None
1	Manual Override

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30078N-1
Fluorocarbon Seal	SK30078V-1

Order Bodies Separately  
See section BC

<b>B08</b>	<b>4</b>	<b>6T</b>
08 size	4-Way Cavity	Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

4-Way, 3 Position, Open Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Designed to operate double acting cylinders, pilot circuits and bi-directional motors, etc.
- High flow capacity with reduced space requirements
- High pressure capability
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Manual override available




## Specifications


Rated Flow	13 LPM (3.5 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.18 kg (.40 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)




### Operating Limits (Measured at 75% of Nominal Current)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>GS02</b>	<b>59</b>		<b>0</b>	<b>N</b>
08 Size Solenoid Valve	Style	Override Option	Screen	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
59	High Flow ('SP' Coil)

Code	Screen
0	Not Available

Code	Override Options
0	None
1	Manual Override

Code	Seals
N	Nitrile

Kit	Part Number
Nitrile Seal	SK30078N-1
Fluorocarbon Seal	SK30078V-1

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>4</b>	—	<b>6T</b>
08 size		4-Way Cavity		Port Size

Code	Port Size / Body Material
6T	SAE-6 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

4-Way Spool Valves. For additional information see Technical Tips on pages SV2-SV6.

## Features

- High flow capacity with reduced space requirements
- Standard valve bodies and common cavities
- Replaceable, one piece encapsulated coils with minimal amperage draw
- Manual overrides, seal variations and other options available
- Oil immersed armature solenoid, no dynamic seals
- Variety of coil terminations and voltages
- Polyurethane "D"-Ring

## Specifications



Rated Flow	<b>C2, C9</b> 19 LPM (5 GPM) <b>C1, C4</b> 26 LPM (7 GPM)
Maximum Inlet Pressure	250 Bar (3600 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min. (10 in <sup>3</sup> /min.)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	40 - 150 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.29 kg (.64 lbs.)
Cavity	C10-4

## Curve Selection Chart

SPOOL CODE	SPOOL SHIFTED				SPOOL CENTERED		
	3 to 2	3 to 4	2 to 1	4 to 1	3 to 1	2 to 1	4 to 1
C1	2	2	4	4	—	—	—
C2	1	1	2	2	5	4	3
C4	2	2	5	5	—	4	4
C9	1	1	2	2	5	—	—




DSL105C1




DSL105C1

## Performance Curves

Pressure Drop vs. Flow (Through cartridge only)




Shift Limit Characteristics (Min. Operating Voltage)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions      Millimeters (Inches)



Ordering Information

**DSL105**

10 Size  
Solenoid Valve



Style



Override  
Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style
C1	
C2	
C4	
C9	

Code	Override Options
Omit	None

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK10-4
Nitrile Seal	SK10-4
Fluorocarbon Seal	SK10-4V

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

4-Way, 3 Position, Closed Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Four way closed center valve designed to operate double acting cylinders and bi-directional motors, etc.
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	42 LPM (11 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min @ 210 Bar (3000 PSI)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	<b>Open</b> 30-60 ms <b>Close</b> 20-40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.26 kg (.58 lbs.)
Cavity	C10-4 (See BC Section for more details)

## Performance Curves

**Pressure Drop vs. Flow Energized - GS045250ND**  
 (Through cartridge only)




**Operating Limits (Measured at 75% of Nominal Current)**





Dimensions    Millimeters (Inches)



Ordering Information

<b>GS04</b>	<b>52</b>		<b>0</b>	<b>N</b>	<b>D</b>
10 Size Solenoid Valve	Style	Override Option	Screen	Seals	Design Level

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style
52	High Flow and Pressure ('SP' Coil)

Code	Screen
0	None (Contact factory for OEM requirements)

Code	Override Options
0	None
5	Standard - Center Detent only, Latch Operated, Push and Pull (*40 nt/9 lbs.)

Code	Seals
N	Nitrile

Code	Design Level
D	Industry Common Cavity

\*Force to push at 210 Bar (3000 PSI). Less to Pull.

Kit	Part Number
Nitrile Seal	SK30506N-1
Fluorocarbon Seal	SK30506V-1

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

4-Way, 3 Position, Floating Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Four way floating center valve designed to operate double acting cylinders and bi-directional motors, etc.
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	42 LPM (11 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min @ 210 Bar (3000 PSI)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	<b>Open</b> 30-60 ms <b>Close</b> 20-40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.26 kg (.58 lbs.)
Cavity	C10-4 (See BC Section for more details)

## Performance Curves

### Pressure Drop vs. Flow Energized - GS045450ND (Through cartridge only)




### Operating Limits (Measured at 75% of Nominal Current)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**Dimensions** Millimeters (Inches)



**Ordering Information**

<b>GS04</b>	<b>54</b>		<b>0</b>	<b>N</b>	<b>D</b>
10 Size Solenoid Valve	Style	Override Option	Screen	Seals	Design Level

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style
54	High Flow and Pressure ('SP' Coil)

Code	Screen
0	None (Contact factory for OEM requirements)

Code	Override Options
0	None
5	Standard - Center Detent only, Latch Operated, Push and Pull (*40 nt/9 lbs.)

Code	Seals
N	Nitrile

Code	Design Level
D	Industry Common Cavity

\*Force to push at 210 Bar (3000 PSI). Less to Pull.

Kit	Part Number
Nitrile Seal	SK30506N-1
Fluorocarbon Seal	SK30506V-1

Order Bodies Separately  
 See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size




Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description

4-Way, 3 Position, Tandem Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Four way tandem center valve designed to operate double acting cylinders and bi-directional motors, etc.
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	42 LPM (11 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min @ 210 Bar (3000 PSI)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	<b>Open</b> 30-60 ms <b>Close</b> 20-40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.26 kg (.58 lbs.)
Cavity	C10-4 (See BC Section for more details)

## Performance Curves

### Pressure Drop vs. Flow (Through cartridge only)




### Operating Limits (Measured at 75% of Nominal Current)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>GS04</b>	<b>57</b>		<b>0</b>	<b>N</b>	<b>D</b>
10 Size Solenoid Valve	Style	Override Option	Screen	Seals	Design Level

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style
57	High Flow and Pressure ('SP' Coil)

Code	Screen
0	None (Contact factory for OEM requirements)

Code	Override Options
0	None
5	Standard - Center Detent only, Latch Operated, Push and Pull (*40 nt/9 lbs.)

Code	Seals
N	Nitrile

Code	Design Level
D	Industry Common Cavity

\*Force to push at 210 Bar (3000 PSI). Less to Pull.

Kit	Part Number
Nitrile Seal	SK30506N-1
Fluorocarbon Seal	SK30506V-1

Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)




<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

4-Way, 3 Position, Open Center Spool Valve.  
 For additional information see Technical Tips on pages SV2-SV6.

## Features

- Four way open center valve designed to operate double acting cylinders and bi-directional motors, etc.
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.




## Specifications


Rated Flow	42 LPM (11 GPM)
Maximum Inlet Pressure	350 Bar (5000 PSI)
Maximum Tank Pressure	210 Bar (3000 PSI)
Leakage at 150 SSU (32 cSt)	160 cc/min @ 210 Bar (3000 PSI)
Minimum Operating Voltage	85% of rated voltage at 20°C (72°F).
Response Time	<b>Open</b> 30-60 ms <b>Close</b> 20-40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO 4406 18/16/13, SAE Class 4
Approx. Weight	.26 kg (.58 lbs.)
Cavity	C10-4 (See BC Section for more details)

## Performance Curves


### Pressure Drop vs. Flow (Through cartridge only)



### Operating Limits (Measured at 75% of Nominal Current)



Dimensions    Millimeters (Inches)



Ordering Information

<b>GS04</b>	<b>59</b>		<b>0</b>	<b>N</b>	<b>D</b>
10 Size Solenoid Valve	Style	Override Option	Screen	Seals	Design Level

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style
59	High Flow and Pressure ('SP' Coil)

Code	Screen
0	None (Contact factory for OEM requirements)

Code	Override Options
0	None
5	Standard - Center Detent only, Latch Operated, Push and Pull (*40 nt/9 lbs.)

Code	Seals
N	Nitrile

Code	Design Level
D	Industry Common Cavity

\*Force to push at 210 Bar (3000 PSI). Less to Pull.

Kit	Part Number
Nitrile Seal	SK30506N-1
Fluorocarbon Seal	SK30506V-1









Order Bodies Separately  
See section BC

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Port Size / Body Material
8T	SAE-8 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



SERIES	CAVITY	DESCRIPTION	FLOW LPM/GPM	PRESSURE BAR/PSI	PAGE NO.
Technical Tips.....PV2-PV5					
<div></div> <div><b>PRESSURE RELIEVING</b> AP02B2YP ..... C08-2 .....Increase Pressure/Increase Current .....5.3/1.4 ..... 350/5000 .....PV6-PV7 AP04G2YP ..... C10-2 .....Increase Pressure/Increase Current .....95/25 ..... 350/5000 .....PV8-PV9</div> <div></div> <div>AP02B2YR ..... C08-2 .....Decrease Pressure/Increase Current .....5.3/1.4 ..... 350/5000 .....PV10-PV11 AP04G2YR ..... C10-2 .....Decrease Pressure/Increase Current .....95/25 ..... 350/5000 .....PV12-PV13</div>					
<div></div> <div><b>PRESSURE REDUCING</b> EPR083R ..... C08-3L .....Pressure Reducing/Relieving Valve.....22.7/6 ..... 345/5000 .....PV14-PV15 EPR111C ..... C10-3L .....Pressure Reducing/Relieving Valve.....37.5/10 ..... 350/5000 .....PV16-PV17</div>					
<div></div> <div><b>FLOW CONTROLS, 2-WAY</b> JP02C 21 ..... C08-3 .....Flow Control, N.C. ....23/6 ..... 210/3000 .....PV18-PV19 JP04C 21 ..... 3X.....Flow Control, N.C. ....36/9.5 ..... 210/3000 .....PV20-PV21</div> <div></div> <div>JP02P 21 ..... C08-3 .....Flow Control, N.O. ....19/5 ..... 210/3000 .....PV22-PV23</div>					
<div></div> <div><b>FLOW CONTROLS, 3-WAY</b> JP04C 31 ..... 4C.....Priority Flow Control, N.C. ....30/8 ..... 210/3000 .....PV24-PV25</div>					
<div></div> <div><b>DIRECTIONAL CONTROL</b> GP02 51 ..... C08-4 .....4 Way, 3 Pos - Closed Center .....21/5.5 ..... 350/5000 .....PV26-PV27 GP02 52 ..... C08-4 .....4 Way, 3 Pos - Closed Center .....17/4.5 ..... 350/5000 .....PV26-PV27  GP02 53.....C08-4.....4 Way, 3 Pos - Float Center.....17/4.5.....350/5000.....PV28-PV29 GP02 54.....C08-4.....4 Way, 3 Pos - Float Center.....17/4.5.....350/5000.....PV28-PV29</div> <div></div> <div>DSP105C1 ..... C10-4 .....4 Way, 3 Pos - Closed Center .....32/8.5 ..... 210/3000 .....PV30-PV32 DSP105C4 ..... C10-4 .....4 Way, 3 Pos - Float Center .....32/8.5 ..... 210/3000 .....PV30-PV32</div>					

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## INTRODUCTION

This technical tips section is designed to help familiarize you with the Parker line of Proportional Valves. In this section we present common options, technical terms, as well as a brief synopsis of the operation and applications of the various products offered in this section. The intent of this section is to help you in selecting the best products for your application.

## COMMON OPTIONS

As you will see, Parker offers a variety of Proportional Valve products. As such, some of the options mentioned below may not be available on all valves. Consult the model coding and dimensions for each valve for specifics. Here are some of the common options available.

**Seals:** Valves are provided with either a 4301 Polyurethane “D”-Ring, Nitrile, or Fluorocarbon Seals. The “D”-Ring eliminates the need for backup rings. You should match the seal compatibility to the temperature and fluid being used in your application.

**Overrides:** Overrides are standard on many of the Parker proportional valves. The override is generally a push type that is flush with the end of the tube. Consult the individual catalog pages for more details.

## TECHNICAL TERMS

To help in applying our proportional valve line of product, we have listed some technical terms below, as well as some helpful hints in applying our valves.

**Ohm's Law:** Electrical current is generated as a result of the relationship between input voltage and the resistance to the flow of electrical current. It is represented in equation form by  $I = V/R$  (or  $V=IR$ ), where  $I$  is current,  $V$  is voltage and  $R$  is resistance. This is an important relationship to remember when dealing with any electrically operated valves. Proportional valves allow varying control of flow or pressure, dependant on the current signal provided. As coils heat up, their resistance rises. This means a higher voltage must be available to maintain the same amount of pressure or flow. Thus, the application needs to be designed such that the full on position is about 70% of the initial current draw. On the individual catalog pages a maximum control current is specified to help in applying our proportional valves.

**PWM:** Pulse Width Modulation (PWM) is the preferred signal for controlling electrical current. PWM is on / off voltage in a square wave form. The percent “on” time or duty cycle provides the average voltage. The valve driver adjusts the duty cycle to obtain current control. We recommend valve drivers with current control for optimum performance. PWM signals also usually provide dither for the proportional valve. Dither is a

small back and forth movement of the valve spool around its set position. This rapid movement reduces the friction of the valve and leads to faster, more accurate response.

**PWM Frequency:** The frequency of a PWM signal is the rate at which the signal is turned on and off. Parker's analog proportional valves are designed to work with low frequency responses between 100-400 Hz. The performance curves on our catalog pages were performed with a PWM signal at 200 Hz.

**Hysteresis:** Due to various factors, the performance of a proportional valve will show a slightly different performance when the current signal is increasing than it will when the signal is being decreased. This difference is usually expressed as a percentage of total input change and is referred to as the hysteresis of the valve.

**Deadband:** Cracking or deadband refers to the amount of the control signal that is needed to produce any movement of the spool. Thus, a 20% deadband means that 20% of the control signal is needed before the spool will move.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data


## PRODUCT TYPES / APPLICATIONS

Proportional valves are nothing more than electrically adjustable hydraulic valves. They give the operator nearly infinite adjustment control and flexibility. Parker Hannifin offers various types of proportional flow control, pressure reducing, and relief valves.

### Proportional Flow Control Valve


Proportional flow control valves provide pseudo pressure compensation and are used on systems requiring variable electronic control of flow. They allow the operator to vary the control signal to accelerate or decelerate an actuator. A compensator valve can be added to the circuit for enhanced compensation. Some typical applications would include the hoist control for a lift, or the speed control for a winch circuit. Parker offers both normally closed and normally open versions of proportional flow controls.

#### Normally Closed Proportional Flow Control




**OPERATION** - With the solenoid coil de-energized, the spool is held in a closed position by the spring force. When the solenoid coil is energized, the amperage of the signal moves the spool into an open position.

The spool is held in this position by a balance between spring force and electrical force. As the current increases, the spools opens further; allowing more flow. As the current decreases, the spool begins closing; allowing less flow. Pseudo compensation is obtained by the pressure drop across the orifices in the spool.




#### Normally Open Proportional Flow Control





**OPERATION** - With the solenoid coil de-energized, the spool is held in an open position by spring force; allowing full flow to pass. As the solenoid coil is energized, the spool begins to move away from a full open position;

allowing less flow to pass. Once a full electronic signal is given, the spool is held in a closed position; allowing no flow to pass. As the electronic signal is then reduced, the spool begins to open; allowing flow to pass again. Once a constant electronic signal is given, the spool is held in that position by a balance between electronic force and spring force. Pseudo compensation is obtained by the pressure drop across the orifices in the spool.



#### Proportional Priority Bypass Flow Control

The proportional priority bypass flow controls allow electronic control of the flow setting for the priority flow circuit. The priority flow remains constant regardless of changes in load or pressure. The excess inlet flow is diverted or bypassed to tank. The bypass port must not have any restrictions or performance will be hindered.



**OPERATION** - Flow enters the valve through port 3. With the coil de-energized, flow is bypassed to port 2. When the coil is energized, the internal orifice is increased allowing pressure compensated flow to the priority port (port 4). The excess flow is bypassed to port 2. As input current is increased, the priority flow increases and the bypass flow decreases. As the current is decreased, priority flow decreases and bypass flow is increased.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD



Technical  
Data

**Normally Closed Proportional Pressure Reducing / Relieving Valve**

Normally Closed Proportional Pressure Reducing/Relieving Valves are used to electronically reduce the inlet pressure to one leg of a hydraulic circuit. In addition these valves act as a relief valve, relieving any shocks or surges that occur between its regulating port and the actuator. Pilot operated are generally slower on response due to the two stage performance, but can have a reduced pressure as high as 3000 psi.

**Pilot Operated**

**OPERATION** - With the solenoid coil de-energized, the pilot dart is held open by the spring force. This allows the main spool to close and restricts flow from going from the inlet (2) port to the regulated port (1). As the electronic signal is applied to the coil, the pilot dart is moved towards the pilot seat restricting pilot flow. This restriction raises the effective pressure inside the chamber between the spool and the pilot seat, allowing the spool to travel away from the pilot seat to a position where the pressure at inlet (2) is connected to the regulated pressure port (1). At this point, reduced pressure becomes a function of the electronic signal. As long as the electronic signal is constant, the reduced pressure at the regulated pressure port (2) will remain fixed regardless of any changes in inlet flow or inlet pressure. As the electronic signal increases or decreases, the reduced pressure at port (1) will change with respect to the change in the electronic signal.



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities


TD

Technical  
Data

**Normally Closed****Proportional Relief Valve**

Normally closed proportional relief valves are used to electronically control the system pressure.

These valves are ideal for circuits with varying system pressures demands. A small flow pilot version of the normally closed proportional relief is also offered for piloting a larger logic element or vented relief valve. The normally closed relief defaults to a maximum pressure setting (i.e. 3000 psi) when there is no current applied.




**OPERATION** - With the solenoid coil de-energized, the pilot dart is held closed by the spring. As current is applied to the coil, the pilot dart is moved creating less restriction of the pilot flow. As this restriction is reduced with the increasing current, the pressure setting also decreases. Once a constant electronic signal is given, the pilot dart is held in a given position, holding the pressure setting. This is maintained by the balance between the electronic spring force and the inlet pressure.

**Normally Open****Proportional Relief Valve**

Normally open proportional relief valves are used to electronically control the system pressure.

These valves are ideal for circuits with varying system pressure demands. A small flow pilot version of the normally open proportional relief is also offered for piloting a larger logic element or vented relief valve. The normally open relief defaults to minimum system pressure (i.e. 150 psi) when there is no current applied. Normally closed versions are also available upon request.



**OPERATION** - With the solenoid coil de-energized, the pilot dart is held open by the spring. This allows the main spool to open at minimum pressure 10.4 Bar (150 psi). As current is applied to the coil, the pilot dart is moved towards the pilot seat restricting pilot flow. This restriction raises the effective pressure setting of the valve. Once a constant electronic signal is given, the pilot dart is held in a given position, holding the pressure setting. This is maintained by a balance between electronic spring force and inlet pressure. As the electronic signal is reduced, the pilot dart is moved away from the pilot seat. This lowers the effective pressure setting of the valve.




CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## General Description

Proportional Relief Valve. Increasing Pressure With Increasing Current. For additional information see Technical Tips on pages PV2-PV5.

## Features

- Analog Proportional Relief Valve regulates pressure proportionally to the solenoid current
- Direct acting poppet design
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.





## Specifications


Rated Flow (At 70 PSI ΔP)	<b>21C</b>	3.0 LPM (0.8 GPM)
	<b>35C</b>	1.3 LPM (.35 GPM)
Max. Pressure At Port 1 @ 75% Input Current	<b>21C</b>	210 Bar (3000 PSI)
	<b>35C</b>	350 Bar (5000 PSI)
Port 2 Pressure Limit	103 Bar (1000 PSI)	
Hysteresis @ 200 Hz PWM	5%	
Cracking Pressure	<b>21C</b>	0.21 Bar (3 PSI)
	<b>35C</b>	0.35 Bar (5 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.	
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)	
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)	
Filtration	ISO-4406 18/16/13, SAE Class 4	
Approx. Weight	0.06 kg (0.14 lbs.)	
Cavity	C08-2 (See BC Section for more details)	

## Performance Curves

### ▲ PWM Current Regulator Recommended



Dimensions    Millimeters (Inches)



Ordering Information

AP02B2YP

08 Size  
Proportional  
Relief Valve

Max Relief  
Setting

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Max Relief Setting
21C	210 Bar (3000 PSI)
35C	350 Bar (5000 PSI)

Code	Seals
Omit	"D"-Ring

Order Bodies Separately  
See section BC

B08	—	2	—	6T
08 size		2-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V






## General Description

Proportional Relief Valve. Increasing Pressure With Increasing Current. For additional information see Technical Tips on pages PV2-PV5.

## Features

- Pilot operated spool-type design fits industry common cavity (10-2)
- Relieving pressure output is proportional to DC current input
- Precise setting of factory preset pressure in energized mode
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.





## Specifications

Rated Flow (At 300 PSI $\Delta P$ ) When Coil is Fully De-Energized	95 LPM (25 GPM)
Factory Set Relief Pressure When Coil De-Energized Measured at 45 LPM (12 GPM)	<b>21C</b> 210 Bar (3000 PSI) <b>35C</b> 350 Bar (5000 PSI)
Port 2 Pressure Limit	103 Bar (1000 PSI)
Hysteresis @ 200 Hz PWM	< 7% of Maximum Pressure Setting
Response Time At 75% of Nominal Voltage Change (Measured To 90% of Press. Change)	<b>To Unload</b> 10ms <b>To Load</b> <b>21C</b> 60 ms <b>35C</b> 80 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.14 kg (0.31 lbs.)
Cavity	C10-2 (See BC Section for more details)


## Performance Curves

### ▲ PWM Current Regulator Recommended



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**AP04G2YP**    **Max Relief Setting**    **N**    **Seals**

10 Size Proportional Relief Valve

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Max Relief Setting
21C	210 Bar (3000 PSI)
35C	350 Bar (5000 PSI)

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

**B10** – **2** – **8T**

10 size    2-Way Cavity    Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30503N-1
Fluorocarbon Seal	SK30503V-1





<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description

Proportional Relief Valve. Decreasing Pressure With Increasing Current. For additional information see Technical Tips on pages PV2-PV5.

## Features

- Analog Proportional Relief Valve regulates pressure proportionally to the input solenoid current
- Direct acting poppet design
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.





## Specifications


Rated Flow (At 70 PSI ΔP)	<b>21A</b> 3.0 LPM (0.8 GPM) <b>35A</b> 1.3 LPM (.35 GPM)
Factory Set Relief Pressure When De-Energized (±5% -Std. ±2% - Low Variation)	<b>21A</b> 210 Bar (3000 PSI) <b>35A</b> 350 Bar (5000 PSI)
Port 2 Pressure Limit	103 Bar (1000 PSI)
Hysteresis @ 200 Hz PWM	< 10%
Cracking Pressure	<b>21C</b> 0.21 Bar (3 PSI) <b>35C</b> 0.35 Bar (5 PSI)
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.09 kg (0.19 lbs.)
Cavity	C08-2 (See BC Section for more details)

## Performance Curves

### ▲ PWM Current Regulator Recommended



Dimensions    Millimeters (Inches)



Ordering Information

<b>AP02B2YR</b>		<b>L</b>
08 Size Proportional Relief Valve	Max Relief Setting	Low Variation Now Standard

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Max Relief Setting
21A	210 Bar (3000 PSI)
35A	350 Bar (5000 PSI)

Code	Seals
Omit	"D"-Ring

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>2</b>	—	<b>6T</b>
08 size		2-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
D-Ring Seal	SK08-2
Nitrile Seal	SK08-2
Fluorocarbon Seal	SK08-2V



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description




Proportional Relief Valve. Decreasing Pressure With Increasing Current. For additional information see Technical Tips on pages PV2-PV5.

## Features

- Pilot operated spool-type design
- Precise setting of factory preset pressure in de-energized mode
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.



## Specifications

Rated Flow (At 300 PSI ΔP) When Coil is Fully Energized	95 LPM (25 GPM)
Factory Set Relief Pressure When Coil De-Energized Measured at 45 LPM (12 GPM)	<b>21C</b> 210 Bar (3000 PSI) <b>35C</b> 350 Bar (5000 PSI)
Port 2 Pressure Limit	103 Bar (1000 PSI)
Hysteresis @ 200 Hz PWM	< 7% of Maximum Pressure Setting
Response Time At 75% of Nominal Voltage Change (Measured To 90% of Press. Change)	<b>To Unload</b> 45ms <b>To Load</b> 25 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.14 kg (0.30 lbs.)
Cavity	C10-2 (See BC Section for more details)




## Performance Curves

### ▲ PWM Current Regulator Recommended



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

**AP04G2YR**  
10 Size  
Proportional  
Relief Valve

☐  
Max Relief  
Setting

**N**  
Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Max Relief Setting
21C	210 Bar (3000 PSI)
35C	350 Bar (5000 PSI)

Code	Seals
N	Nitrile

Order Bodies Separately  
See section BC

**B10**  
10 size

**2**  
2-Way  
Cavity

**8T**  
Port  
Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30503N-1
Fluorocarbon Seal	SK30503V-1

<b>CV</b> Check Valves
<b>SH</b> Shuttle Valves
<b>LM</b> Load/Motor Controls
<b>FC</b> Flow Controls
<b>PC</b> Pressure Controls
<b>LE</b> Logic Elements
<b>DC</b> Directional Controls
<b>SV</b> Solenoid Valves
<b>PV</b> Proportional Valves
<b>CE</b> Coils & Electronics
<b>BC</b> Bodies & Cavities
<b>TD</b> Technical Data

## General Description


Pilot Operated, Pressure Increasing with Current Proportional Pressure Reducing/ Relieving Valve. For additional information see Technical Tips on pages PV2-PV5.

## Features

- Low hysteresis
- High flow capacity
- 400 Hz PWM signal preferred
- No dynamic seals
- Screw style manual override standard
- Polyurethane "D"-ring eliminates the need for back-up rings

## Specifications

Rated Flow	22.7 LPM (6 GPM)
Max. Input Press. At Port 1	345 Bar (5000 PSI)
Max. Internal Leakage De-energised	230 cc/min (14 in <sup>3</sup> /min)
Hysteresis @ 400 Hz PWM	4% with 30% to 50% duty cycle
Power Consumption	8.4 Watts at max. reduced pressure
Frequency	200-600 Hz (PWM)
Continuous Duty Control Current	12VDC .730A    24VDC .365A
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile Buna-N) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/ Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.25 kg (0.55 lbs.) With coil
Cavity	C08-3L (See BC Section for more details)






(3) Tank  
 (2) Inlet  
 (1) Reduced Pressure

## Performance Curves

### Current Regulator PWM Recommended


#### Regulated Pressure vs. Flow (Through Cartridge Only)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



**Dimensions**    Millimeters (Inches)



**Ordering Information**

**EPR083**

08 Size  
Proportional  
Valve

**R**

Style



Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Coil Short Proportional (SW7L series), for ordering information.

Code	Coil Type
R	Pilot operated increasing "rising" pressure

Code	Pressure Range (Output)
20	138 Bar (2000 PSI)
40	276 Bar (4000 PSI)

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK08-3
Nitrile Seal	SK08-3
Fluorocarbon Seal	SK08-3V

*Order Bodies Separately  
See section BC*

<b>B08</b>	—	<b>3L</b>	—	<b>8T</b>
08 size		3-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

## General Description



Pilot Operated, Normally Closed, Proportional Pressure Reducing/Relieving Valve. For additional information see Technical Tips on pages PV2-PV5.

## Features

- High flow capacity
- Low hysteresis
- 400 Hz PWM signal preferred
- No dynamic seals
- Polyurethane "D"-Ring eliminates need for backup rings




## Specifications

Rated Flow	37.5 LPM (10 GPM)
Maximum Input Pressure at Port 2	350 Bar (5000 PSI)
Maximum Internal Leakage	0.5 LPM (0.13 GPM) @ 20.7 Bar (300 PSI) 0.95 LPM (0.25 GPM) @ 207 Bar (3000 PSI)
Hysteresis @ 400 Hz PWM	4% with 60% duty cycle
Power Consumption	9 watts at max. reduced pressure
Frequency	200-600 Hz (PWM)
Maximum Control Current	<b>12 VDC</b> .90A <b>24 VDC</b> .45A
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.59 kg (1.3 lbs.)
Cavity	C10-3L (See BC Section for more details)




## Performance Curves

### ▲ PWM Current Regulator Recommended



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**Dimensions**    Millimeters (Inches)



**Ordering Information**

**EPR111**  
11 Size  
Proportional  
Red./Rel. Valve

**C**  
Style

Pressure  
Range

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style
C	Normally Closed, Pilot Operated

Code	Seals
Omit	"D"-Ring

Code	Pressure Range
10	68.9 Bar (1000 PSI)
20	138 Bar (2000 PSI)
30	207 Bar (3000 PSI)

Order Bodies Separately  
See section BC

**B10**  
10 size

**3**  
3-Way  
Cavity

**8T**  
Port  
Size

Code	Porting / Body Material
8T	SAE-8 / Steel (5000 PSI)

Kit	Part Number
D-Ring Seal	SK10-3L
Nitrile Seal	SK10-3LN
Fluorocarbon Seal	SK10-3LV

<b>CV</b> Check Valves
<b>SH</b> Shuttle Valves
<b>LM</b> Load/Motor Controls
<b>FC</b> Flow Controls
<b>PC</b> Pressure Controls
<b>LE</b> Logic Elements
<b>DC</b> Directional Controls
<b>SV</b> Solenoid Valves
<b>PV</b> Proportional Valves
<b>CE</b> Coils & Electronics
<b>BC</b> Bodies & Cavities
<b>TD</b> Technical Data

## General Description




2 Way, Normally Closed, Proportional Flow Regulator Valve. Pressure Compensated. For additional information see Technical Tips on pages PV2-PV5.

## Features

- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Nonmagnetic spool and housing assembly
- Factory-adjusted low variation option (Model "L") is available for applications where low variation of flow from valve to valve is essential at a given current.

## Specifications


Rated Flow	<b>20</b> 7.5 LPM (2 GPM) Low Flow ('SS' Coil) <b>21</b> 15 LPM (4 GPM) Standard ('SS' Coil) <b>21</b> 23 LPM (6 GPM) High Flow ('SP' Coil)
Maximum Input Pressure at Port 3	210 Bar (3000 PSI)
Minimum Pressure Differential	<b>20</b> 10.3 Bar (150 PSI) Low Flow <b>21</b> 13.8 Bar (200 PSI) Standard <b>21</b> 20.7 Bar (300 PSI) High Flow
Maximum Internal Leakage	570 cc (35 cu. in.) @ 210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	<10% (Low Flow and Standard) <3% (High Flow)
Cracking Pressure	25% of Input Signal
Variation of Flow @ 35% of Rated Current	<b>Model "L"</b> ±7% Of Rated Flow
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.17 lbs.)
Cavity	C08-3 (See BC Section for more details)




## Performance Curves

### ▲ PWM Current Regulator Recommended


#### Flow vs. Input Current



#### Flow Regulation (Measured 75% of Rated Current)




#### Pressure Drop vs. Flow



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>JP02C</b>				<b>N</b>	<b>L</b>
08 Size Proportional Valve	Style	Override Option	Filter Screen	Seals	Flow Variation

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style (Maximum Regulated Flow)
20	Low Flow ('SS' Coil) 7.5 LPM (2 GPM)
21	Standard ('SS' Coil) 15 LPM (4 GPM)
21	High Flow ('SP' Coil) 23 LPM (6 GPM)

Code	Override Option
0	Not Required
5	Infinite Control M.O.

Code	Filter Screen
0	Not Available
1	60 Mesh Screen on Inlet Port

Code	Seals
<b>N</b>	<b>Nitrile</b>

Code	Flow Variation
L	Low Variation (±7% of Rated Flow)

Kit	Part Number
Nitrile Seal	SK30105N-1
Fluorocarbon Seal	SK30105V-1

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description



2 Way, Normally Closed, Proportional Flow Regulator Valve. Pressure Compensated.  
 For additional information see Technical Tips on pages PV2-PV5.

## Features

- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Nonmagnetic spool and housing assembly
- Factory-adjusted low variation option (Model "L") is available for applications where low variation of flow from valve to valve is essential at a given current.

## Specifications


Rated Flow	<b>21</b> 30 LPM (8 GPM) Standard ('SS' Coil) <b>21</b> 36 LPM (9.5 GPM) High Flow ('SP' Coil)
Maximum Input Pressure at Port 2	210 Bar (3000 PSI)
Minimum Pressure Differential	<b>21</b> 13.8 Bar (200 PSI) Standard <b>21</b> 20.7 Bar (300 PSI) High Flow
Maximum Internal Leakage	780 cc (46 cu. in.) @ 210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	7%
Cracking Pressure	25% of Input Signal
Variation of Flow @ 35% of Rated Current	<b>Model "L"</b> ±7% Of Rated Flow
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.13 kg (0.28 lbs.)
Cavity	3X (See BC Section for more details)




## Performance Curves

### ▲ PWM Current Regulator Recommended


#### Flow vs. Input Signal



#### Flow Regulation (Measured 75% of Rated Current)




#### Pressure Drop vs. Flow



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>JP04C</b>	<b>21</b>			<b>N</b>	<b>L</b>
10 Size Proportional Valve	Style	Override Option	Filter Screen	Seals	Flow Variation

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style (Maximum Regulated Flow)
21	Standard ('SS' Coil) 30 LPM (8 GPM)
21	High Flow ('SP' Coil) 36 LPM (9.5 GPM)

Code	Override Option
0	Not Required
5	Infinite Control M.O.

Code	Filter Screen
0	Not Available
1	60 Mesh Screen on Port 2

Code	Seals
<b>N</b>	<b>Nitrile</b>

Code	Flow Variation
L	Low Variation (±7% of Rated Flow)

Kit	Part Number
Nitrile Seal	SK30106N-1
Fluorocarbon Seal	SK30106V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>553</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
553	1/2" SAE

Code	Body Material
S	Steel (5000 PSI)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data



## General Description




2 Way, Normally Open, Proportional Flow Regulator Valve. Pressure Compensated.  
 For additional information see Technical Tips on pages PV2-PV5.

## Features

- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Nonmagnetic spool and housing assembly
- Factory-adjusted low variation option (Model "L") is available for applications where low variation of flow from valve to valve is essential at a given current.

## Specifications


Rated Flow	<b>20</b> 9.5 LPM (2.5 GPM) Standard ('SS' Coil) <b>21</b> 19 LPM (5 GPM) High Flow ('SP' Coil)
Maximum Input Pressure at Port 2	210 Bar (3000 PSI)
Minimum Pressure Differential	<b>20</b> 10.3 Bar (150 PSI) Standard <b>21</b> 20.7 Bar (300 PSI) High Flow
Maximum Internal Leakage	570 cc (35 cu. in.) @ 210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	<3%
Cracking Pressure	25% of Input Signal
Variation of Flow @ 35% of Rated Current	<b>Model "L"</b> ±7% Of Rated Flow
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.08 kg (0.17 lbs.)
Cavity	C08-3 (See BC Section for more details)




## Performance Curves

### ▲ PWM Current Regulator Recommended


#### Flow vs. Input Current



#### Flow Regulation (Measured 75% of Rated Current)




#### Pressure Drop vs. Flow



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>JP02P</b>				<b>N</b>	<b>L</b>
08 Size Proportional Valve	Style	Override Option	Filter Screen	Seals	Flow Variation

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style (Maximum Regulated Flow)
20	Standard ('SS' Coil) 9.5 LPM (2.5 GPM)
21	High Flow ('SP' Coil) 19 LPM (5 GPM)

Code	Override Option
0	Not Required
5	Infinite Control M.O.

Code	Filter Screen
0	Not Available
1	60 Mesh Screen on Port 2

Code	Seals
<b>N</b>	<b>Nitrile</b>

Code	Flow Variation
L	Low Variation (±7% of Rated Flow)

Kit	Part Number
Nitrile Seal	SK30105N-1
Fluorocarbon Seal	SK30105V-1

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 size		3-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)



<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## General Description



3 Way, Normally Closed, Proportional Flow Regulator Valve. Pressure Compensated. For additional information see Technical Tips on pages PV2-PV5.

## Features


- Analog proportional pressure compensated flow control valve regulates flow proportionally to the input solenoid current
- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- Nonmagnetic spool and housing assembly
- Factory-adjusted low variation option (Model "L") is available for applications where low variation of flow from valve to valve is essential at a given current.

## Specifications

Rated Inlet Flow	60 LPM (16 GPM)
Rated Regulated Flow	<b>31</b> 26 LPM (7 GPM) Standard ('SS' Coil) <b>31</b> 30 LPM (8 GPM) High Flow ('SP' Coil)
Maximum Input Pressure at Port 3	210 Bar (3000 PSI)
Minimum Pressure Differential	<b>31</b> 13.8 Bar (200 PSI) Standard <b>31</b> 20.7 Bar (300 PSI) High Flow
Maximum Internal Leakage	780 cc (46 cu. in.) @ 210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	7%
Opening Point	<b>Standard</b> 21% of Nominal Amperage <b>High Flow</b> 17% of Nominal Amperage
Variation of Opening Point	<b>Model "L"</b> ±20% of Amperage
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.14 kg (0.31 lbs.)
Cavity	4C (See BC Section for more details)




\*Always connect Port (1) to Port (4) through .039" orifice.




## Performance Curves

### ▲ PWM Current Regulator Recommended


#### Pressure Compensation of Regulated Flow (Port 4)



#### Regulated Flow vs. Input Current Stabilized



#### Pressure Drop vs. Flow at Coil Fully Energized



**CV**

Check Valves

**SH**

Shuttle Valves

**LM**

Load/Motor Controls

**FC**

Flow Controls

**PC**

Pressure Controls

**LE**

Logic Elements

**DC**

Directional Controls

**SV**

Solenoid Valves

**PV**

Proportional Valves

**CE**

Coils & Electronics


**BC**

Bodies & Cavities

**TD**

Technical Data

Dimensions    Millimeters (Inches)



Ordering Information

<b>JP04C</b>	<b>31</b>		<b>0</b>	<b>N</b>	<b>L</b>
10 Size Proportional Valve	Style	Override Option	Filter Screen	Seals	Flow Variation

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Super-Coil (CA series), for ordering information.

Code	Style (Maximum Regulated Flow)
31	Standard ('SS' Coil) 26 LPM (7 GPM)
31	High Flow ('SP' Coil) 30 LPM (8 GPM)

Code	Override Option
0	Not Required
5	Screw Adjust (Infinite Control)

Code	Filter Screen
0	Not Available

Code	Seals
<b>N</b>	<b>Nitrile</b>

Code	Flow Variation
L	Low Variation (±7% of Rated Flow)

Kit	Part Number
Nitrile Seal	SK30082N-1
Fluorocarbon Seal	SK30082V-1

Order Bodies Separately  
See section BC

<b>LB10</b>	<b>562</b>	<b>S</b>
Line Body	Porting	Body Material

Code	Porting
562	1/2" SAE Steel (5000 PSI)

## General Description

4 Way, 3 Position, Proportional Directional Control Valve. Closed Center Spool. For additional information see Technical Tips on pages PV2-PV5.

## Features



- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.

## Specifications

Operating Pressure	<b>Ports 2, 3 and 4</b> 350 Bar (5000 PSI) <b>Port 1</b> 210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	<6%
Cracking Flow	25% to 30% of Input Signal
Variation of Flow	±15% @ 75% of Nominal Current and Constant ΔP Maintained by Pressure Compensator
Port to Port Leakage	10 cu. in/min @ 3000 PSI
<b>Step Response Time at 75% of Amps</b>	On 50 ms Off 40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.15 kg (0.34 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Typical Performance


SPOOL TYPE AND FLOW	RATED FLOW AT 75% OF NOMINAL CURRENT LPM - (GPM)		SUPER COIL TYPE		Compensator ΔP Bar (PSI)
	'a' SOLENOID PUSH P to A, B to T	'b' SOLENOID PULL P to B, A to T	PUSH	PULL	
51 Standard	13.3 - (3.5)	17 - (4.5)	SP	SP	15 (220)
	11.4 - (3.0)	15.2 - (4.0)	SS	SS	15 (220)
52 High Flow	21 - (5.5)	17 - (4.5)	SP	SP	20 (290)
	17.4 - (4.5)	13 - (3.5)	SP	SP	15 (220)




## Performance Curves

### ▲ PWM Current Regulator Recommended


51L With 5 Bar, 75 PSI Compensator  
 51 With 15 Bar, 220 PSI Compensator and SS Coil



52 With 20 Bar, 290 PSI Compensator and SP Coil




### Flow vs. Load



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

**Dimensions** Millimeters (Inches)



**Ordering Information**

<b>GP02</b>			<b>N</b>
08 Size Proportional Valve	Style	Override Option	Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style - Floating Center (Flow Pressure and Performance)
51	Standard
52	High Flow

Code	Override Option
0	Not Required
1	Manual Override

Code	Seals
N	Nitrile

Order Bodies Separately  
 See section BC

<b>B08</b>	—	<b>4</b>	—	<b>6T</b>
08 size		4-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30078N-1
Fluorocarbon Seal	SK30078V-1



## General Description

4 Way, 3 Position, Proportional Directional Control Valve. Floating Center Spool. For additional information see Technical Tips on pages PV2-PV5.

## Features



- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.

## Specifications

Operating Pressure	<b>Ports 2, 3 and 4</b> 350 Bar (5000 PSI) <b>Port 1</b> 210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	<6%
Cracking Flow	25% to 30% of Input Signal
Variation of Flow	±15% @ 75% of Nominal Current and Constant ΔP Maintained by Pressure Compensator
Port to Port Leakage	10 cu. in/min @ 3000 PSI
<b>Step Response Time at 75% of Amps</b>	On 50 ms Off 40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.15 kg (0.34 lbs.)
Cavity	C08-4 (See BC Section for more details)

## Typical Performance


SPOOL TYPE AND FLOW	RATED FLOW AT 75% OF NOMINAL CURRENT LPM - (GPM)		SUPER COIL TYPE		Compensator ΔP Bar (PSI)
	'a' SOLENOID PUSH P to A, B to T	'b' SOLENOID PULL P to B, A to T	PUSH	PULL	
53 Standard	14 - (3.8)	15 - (4.0)	SP	SP	10 (150)
	9 - (2.5)	10 - (2.7)	SS	SS	5 (75)
54 High Flow	17 - (4.5)	19 - (5.0)	SP	SP	20 (290)
	15 - (4.0)	15 - (4.0)	SS	SS	15 (220)




## Performance Curves

### ▲ PWM Current Regulator Recommended


53 and 53L With 5 Bar, 75 PSI Compensator and SS Coil



54 With 20 Bar, 290 PSI Compensator and SP Coil




### Flow vs. Load




CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data



Dimensions    Millimeters (Inches)



Sample Application Circuit (Floating Center)



Ordering Information



**GP02**  
08 Size  
Proportional  
Valve

Style

Override  
Option

Seals

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 1/2" Super-Coil (CC series), for ordering information.

Code	Style - Floating Center (Flow Pressure and Performance)
53	Standard
54	High Flow

Code	Seals
N	Nitrile

Code	Override Option
Omit	Not Required
1	Manual Override

Order Bodies Separately  
See section BC

<b>B08</b>	—	<b>4</b>	—	<b>6T</b>
08 size		4-Way Cavity		Port Size

Code	Porting / Body Material
6T	SAE-6 / Steel (5000 PSI)

Kit	Part Number
Nitrile Seal	SK30078N-1
Fluorocarbon Seal	SK30078V-1



## General Description



4 Way, 3 Position, Proportional Directional Control Valve. Closed Center or Floating Center Spool.  
 For additional information see Technical Tips on pages PV2-PV5.

## Features



- One piece cartridge housing ensures internal concentricity
- Coil: Waterproof, hermetically sealed, requires no O'Rings; Symmetrical coil can be reversed without affecting performance.
- All external parts zinc plated

## Specifications


Operating Pressure	210 Bar (3000 PSI)
Hysteresis @ 100 Hz PWM	<6%
Cracking Flow	25% to 30% of Input Signal
Variation of Flow	±15% @ 75% of Nominal Current and Constant ΔP Maintained by Pressure Compensator
Port to Port Leakage	10 cu. in. @ 3000 PSI
Step Response Time at 75% of Amps	On 50 ms Off 40 ms
Cartridge Material	All parts steel. All operating parts hardened steel.
Operating Temp. Range/Seals	-37°C to +93°C ("D"-Ring) (-35°F to +200°F) -34°C to +121°C (Nitrile) (-30°F to +250°F) -26°C to +204°C (Fluorocarbon) (-15°F to +400°F)
Fluid Compatibility/Viscosity	Mineral-based or synthetic with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt)
Filtration	ISO-4406 18/16/13, SAE Class 4
Approx. Weight	0.28 kg (0.57 lbs.)
Cavity	C10-4 (See BC Section for more details)



## Sample Application Circuit



Dimensions    Millimeters (Inches)



Ordering Information

<b>DSP105</b>		
10 Size Proportional Valve	Style	Override Option

**Highlighted** represents preferred options that offer the shortest lead times. Other options may be available, but at extended lead times.

**Coil(s) sold separately.** Please see section CE of this catalog, 5/8" Coil (CA series), for ordering information.

Code	Style
C1	
C4	

Code	Override Options
Omit	None
M	Push/Pull

Code	Seals
Omit	"D"-Ring

Kit	Part Number
D-Ring Seal	SK10-4
Nitrile Seal	SK10-4
Fluorocarbon Seal	SK10-4V

Order Bodies Separately  
See section BC


<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 size		4-Way Cavity		Port Size

Code	Porting / Body Material
8T	SAE-6 / Steel (5000 PSI)


<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**▲ PWM Current Regulator Recommended**


**C1 With 15 Bar, 220 PSI Compensator and SP Coil**




**C4 With 15 Bar, 220 PSI Compensator and SP Coil**




**Pressure Compensation Pull Coil  
 Inlet to Work Port**



**Pressure Compensation Push Coil  
 Inlet to Work Port**



**C1 Spool Port 3 to 4**



**CV**

Check  
Valves

**SH**

Shuttle  
Valves

**LM**

Load/Motor  
Controls

**FC**

Flow  
Controls

**PC**

Pressure  
Controls

**LE**

Logic  
Elements

**DC**

Directional  
Controls

**SV**

Solenoid  
Valves

**PV**

Proportional  
Valves

**CE**


Coils &  
Electronics

**BC**

Bodies &  
Cavities

**TD**

Technical  
Data

SERIES	DESCRIPTION	PAGE NO.
Technical Tips.....		CE2-CE3
	<b>SUPER COILS</b>	
CC .....	1/2" Solenoid Tubes .....	CE4-CE5
CA.....	5/8" Solenoid Tubes .....	CE6-CE7
SW7L.....	1/2" Solenoid Tube - Short.....	CE8- CE9

<b>CV</b> Check Valves
<b>SH</b> Shuttle Valves
<b>LM</b> Load/Motor Controls
<b>FC</b> Flow Controls
<b>PC</b> Pressure Controls
<b>LE</b> Logic Elements
<b>DC</b> Directional Controls
<b>SV</b> Solenoid Valves
<b>PV</b> Proportional Valves
<b>CE</b> Coils & Electronics
<b>BC</b> Bodies & Cavities
<b>TD</b> Technical Data

## INTRODUCTION

This technical tips section is designed to help familiarize you with the Parker line of Coils. In this section we highlight the features and discuss some of the available options.

We also use this section to present some common terminology related to coil and coil technology.

## COMMON OPTIONS

Below are some of the common options to the Super Coil product offering.

**Continuous Duty:** Parker's standard line of coils are rated for continuous duty operation. This means the coil can be left on continuously without fear of the magnet wire insulation breakdown, when used in standard climate conditions.

The Super Coils are made of a high quality Class N magnet wire. This Class N rating signifies the internal wires are rated to 200°C (392°F).

Continuous duty does not mean the coil will have the same amount of power after hours of operation as it had at initial actuation. Coils do heat up during use. This internal heat rise increases the resistance of the coil and thus, decreases the current ( $V = IR$ ). The performance curves presented on the solenoid valve pages are based on a coil at room temperature and 85% of voltage. Thus, when using a valve in continuous duty applications, you may need to derate the performance.


In short, the continuous duty rating signifies that while the coil will get hot during use and resistance will increase, it will not generate enough heat to damage the coil.

**Terminations:** Parker offers a wide variety of coil terminations for all coils to meet the demands of your application. Over the years, the dual lead wire and dual spade offerings have been popular due to their ease of installation and availability. In the past few years, the demand for more secure termination connections has increased.

In addition, the integral connectors reduce cost and improve integrity by reducing the number of connections. As such, the DIN, and Integral Deutsch have increased in popularity.

If you do not find your desired coil termination in our catalog, contact your factory sales representative.

**Current Types:** Both direct current (DC) and alternating current (AC) versions are available for the Parker line of coils. The AC versions are essentially DC coils with a full wave rectifier integrally molded into the coil. The rectifiers are rated for voltage peaks up to 1000 volts maximum. For voltage transients greater than 1000 volts, a Harris Thyrector is recommended. The AC coils operate at 50/60 cycles (Hz). Since the AC versions are rectified DC coils, there is no inrush current like with "true" AC coils. It also means DC coils and AC coils are interchangeable.



**Voltages:** Parker has a wide selection of coils available to meet your needs. Most coil terminations are available with our standard voltages of 12, 24 Volts DC and 115 Volts AC. Contact your Parker representative should your application call for voltages other than our standard offering.

**Wattages:** Parker offers a variety of coil wattages to meet the demands of your application. However, when using Parker valves, please note that all performance curves/values are based on using the higher watt coil. Selecting a lower watt coil could possibly de-rate the performance of the valve. Contact your Parker representative should your application call for wattages other than our standard offering.

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC


Bodies &  
Cavities

TD

Technical  
Data

## Technical Tips

**Diodes:** The Parker Coils can be ordered with a diode molded internally. The Super Coil (HSZN termination) uses a Zener Diode that is not polarity sensitive. Other Super Coil terminations that can be available with a IN5627 diode are polarity sensitive. Diodes are sometimes used to protect sensitive, downstream electrical components from potential surges from the coil. By internally molding the diode into the coil, you can reduce the assembly time and cost associated with externally wiring a diode. One should be careful not to switch the polarity (“+” and “-” terminals), when wiring a coil with an internal diode. If these terminals are switched, the first time voltage is applied to the coil; the short circuit will destroy the diode and render the coil use-less.




Parker coils with diodes have “+” and “-” molded near the termination outlet to help identify polarity.

## Coils and Electronics

**DIN Connectors:** Parker does offer connectors for use with the DIN style coils. As shown below, the DIN connectors are available in both rectified and non-rectified forms. The cable gland versions can be ordered for type PG9 or PG11.


### Cable Gland

Type	Non-Rectified	Rectified
PG9	710549-00	712126-01
PG11	710549-01	712126-00




### Conduit

Rectified
712704-00



### Conduit

Non-Rectified
710549-02



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data





## Features

- Integral Deutsch connector coil exceeds IP69K standards
- Integral Deutsch connector coil thermal shock dunk test rated
- Universal 50/60 Hz operation
- Waterproof coil hermetically sealed, requires no O-rings or waterproofing kits
- External plated steel flux-carrying band (unlike encapsulated band) enables coil to withstand severe thermal shocks without cracking
- Symmetrical coil can be reversed without affecting performance

## Specifications

<b>Coil Type</b>	<b>S</b> Standard <b>P</b> Puissant
<b>Nominal Wattage</b> (See Ordering Information For Exact Wattage)	<b>S</b> 14 Watts <b>P</b> 19 Watts
<b>Duty Cycle</b>	Continuous @ 100% voltage
<b>Magnetic Wire Insulation Class</b>	'N' Rated at 200°C (392°F)
<b>Temperature Range</b>	-40°C to +200°C (-40°F to +392°F)
<b>Temperature Rise At Nominal Voltage And Natural Ventilation</b>	<b>S</b> 75°C (135°F) <b>P</b> 95°C (172°F)
<b>Dielectric Strength Maximum Current Leakage (Amps)</b>	.0005 In dry lab condition at 1000V AC for 30 seconds .001 After being immersed in 23°C (77°F) water with waterproof connector for 24 hours at 500V AC
<b>Encapsulating Material</b>	Glass filled rynite
<b>Color Identification On The Terminal Boss</b>	<b>S</b> Black Ring <b>P</b> Red Ring
<b>Weight</b>	0.20 kg (0.44 lbs.)

## AC Coil Assembly



## Ordering Information

<b>CC</b>			
Super Coil 1/2" I.D.	Wattage	Voltage	Termination
<b>Code</b>	<b>Wattage</b>		
<b>S</b>	Standard		
<b>P</b>	Puissant		

Code	Voltage	Watts		Amps		Ohms**	
		S	P	S	P	S	P
012*	12 VDC	14	19	1.15	1.58	10.43	7.58
024*	24 VDC	14	19	0.58	0.79	41.74	30.30
115*	115 VAC	16	19	0.17	0.20	680	576

\*Standard Voltages

\*\*Resistance  $\pm 10\%$  at 68°F




Code	Termination
*D	DIN 43650 (AC or DC, Supplied without DIN Connector)
*HSN	Integral Deutsch with Anti-vibration ring (DC Only)
*HSZN	Integral Deutsch with Anti-vibration ring and Zener Diode (DC Only) *Zener Diode for use with on/off solenoid valves and not recommended for proportional valves.

### \*UL Listed

**Note:** Additional voltages and other terminals may be available. For details please consult factory.

DIN Female Mating Connector: See page CE3  
 Deutsch Mating Connector: # DT06-2S

Terminal Styles and Dimensions



- NOTES:**
1. The standard A.C. coil includes a molded-in full wave rectifier rated for 800 peak reverse voltage.
  2. All P Puissant (high wattage) coils use a red ring as an indication marker on the terminal boss.



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data



## Features

- Integral Deutsch connector coil exceeds IP69K standards
- Integral Deutsch connector coil thermal shock dunk test rated
- Universal 50/60 Hz operation
- Coil hermetically sealed, requires no O-rings or waterproofing kits
- External plated steel flux-carrying band (unlike encapsulated band) enables coil to withstand severe thermal shocks without cracking
- Symmetrical coil can be reversed without affecting performance

## Specifications

<b>Coil Type</b>	<b>S</b> Standard <b>P</b> Puissant
<b>Nominal Wattage</b> (See Ordering Information For Exact Wattage)	<b>S</b> 18 Watts <b>P</b> 28 Watts
<b>Duty Cycle</b>	Continuous @ 100% voltage
<b>Magnetic Wire Insulation Class</b>	'N' Rated at 200°C (392°F)
<b>Temperature Range</b>	-40°C to +200°C (-40°F to +392°F)
<b>Temperature Rise At Nominal Voltage And Natural Ventilation</b>	<b>S</b> 75°C (135°F) <b>P</b> 95°C (172°F)
<b>Dielectric Strength Maximum Current Leakage (Amps)</b>	.0005 In dry lab condition at 1000V AC for 30 seconds .001 After being immersed in 23°C (77°F) water with waterproof connector for 24 hours at 500V AC
<b>Encapsulating Material</b>	Glass filled rynite
<b>Color Identification On The Terminal Boss</b>	<b>S</b> Black Ring <b>P</b> Red Ring
<b>Weight</b>	0.29 kg (0.64 lbs.)

## AC Coil Assembly



## Ordering Information

<b>CA</b>			
Super Coil 5/8" I.D.	Wattage	Voltage	Termination

Code	Wattage
<b>S</b>	Standard
<b>P</b>	Puissant

Code	Voltage	Watts		Amps		Ohms**	
		S	P	S	P	S	P
<b>012*</b>	12 VDC	18	28	1.50	2.33	8.00	5.14
<b>024*</b>	24 VDC	18	28	0.75	1.17	32.0	20.6
<b>115*</b>	115 VAC	18	28	0.20	0.26	554	417

\*Standard Voltages

\*\*Resistance  $\pm 10\%$  at 68°F

Code	Termination
<b>*D</b>	DIN 43650 (AC or DC, Supplied without DIN Connector)
<b>*HSN</b>	Integral Deutsch with Anti-vibration ring (DC Only)
<b>*HSZN</b>	Integral Deutsch with Anti-vibration ring and Zener Diode (DC Only) *Zener Diode for use with on/off solenoid valves and not recommended for proportional valves.




### \*UL Listed

**Note:** Additional voltages and other terminals may be available.  
For details please consult factory.

DIN Female Mating Connector: See page CE3  
 Deutsch Mating Connector: # DT06-2S

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

Terminal Styles and Dimensions



NOTES:


1. The standard A.C. coil includes a molded-in full wave rectifier rated for 800 peak reverse voltage.
2. All P Puissant (high wattage) coils use a red ring as an indication marker on the terminal boss. (No ring on Integral Deutsch connector).



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## Features

- For utilization on EPR083R product only
- Integral Deutsch connector coil exceeds IP69K standards
- Integral Deutsch connector coil thermal shock dunk test rated
- Coil hermetically sealed, requires no O-rings or waterproofing kits
- Coil shell is zinc plated, low carbon steel
- Symmetrical coil can be reversed without affecting performance



## Ordering Information

**SW7**

1/2" I.D.

**L**

Wattage  
14W

Termination

Voltage

## Specifications

<b>Nominal Wattage</b>	<b>L</b> 14 Watts
<b>Duty Cycle</b>	Continuous @ 100% voltage
<b>Lead Wire</b>	<b>(12 VDC)</b> 22 gauge 24" long <b>(24 VDC)</b> 22 gauge 24" long
<b>Magnetic Wire Insulation Class</b>	'N' Rated at 200°C (392°F)
<b>Temperature Range</b>	-40°C to +200°C (-40°F to +392°F)
<b>Encapsulating</b>	Glass-Filled Polyethylene Material Terephthalate (PET)
<b>Weight</b>	0.29 kg (0.64 lbs.)

Code	Wattage
L	Standard, 14W

Code	Termination
H	Integral Deutsch
W	Double Lead

Code	Voltage				
	Volts	Watts (Ref)	Amps (Ref)	Ohms* (Ref)	Lead Wire** Color
D012	12VDC	14.2	1.2	10.1	Red
D024	24VDC	14.5	0.6	39.6	Blue

\*Resistance  $\pm 5\%$  at 68°F



\*Applicable to W Double Lead Termination

**Note:** Additional voltages and other terminals may be available.  
For details please consult factory.


Deutsch Mating Connector: # DT06-2S

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data


Terminal Styles and Dimensions



H - Integral Deutsch



W - Double Lead



718164 - Wire connector assembly with 36" leads for Super Coils with Integral Deutsch connectors.



CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

SERIES	DESCRIPTION	BODY NO.	PAGE NO.
Technical Tips .....			BC2-BC3
<b>PARKER STANDARD BODIES AND CAVITIES</b>			
C04-3 .....	04 Size, 3 Way .....	B04-3-*	BC4
C08-2 .....	08 Size, 2 Way .....	B08-2-*	BC5
C08-3 .....	08 Size, 3 Way .....	B08-3-*	BC6
C08-3L .....	08 Size, 3 Way, Long .....	B08-3L-*	BC7
C08-4 .....	08 Size, 4 Way .....	B08-4-*	BC8
C10-2 .....	10 Size, 2 Way .....	B10-2-*	BC9
C10-3 .....	10 Size, 3 Way .....	B10-3-*	BC10
C10-3L .....	10 Size, 3 Way, Long .....	B10-3L-*	BC11
C10-3S .....	10 Size, 3 Way, Short .....	B10-3S-*	BC12
C10-4 .....	10 Size, 4 Way .....	B10-4-*	BC13
C12-2 .....	12 Size, 2 Way .....	B12-2-*	BC14
C12-3 .....	12 Size, 3 Way .....	B12-3-*	BC15
C16-2 .....	16 Size, 2 Way .....	B16-2-*	BC16
C16-3 .....	16 Size, 3 Way .....	B16-3-*	BC17
C16-3S .....	16 Size, 3 Way, Short .....	B16-3S-*	BC18
C16-4 .....	16 Size, 4 Way .....	B16-4-*	BC19
C20-2 .....	20 Size, 2 Way .....	B20-2-*	BC20
C20-3S .....	20 Size, 3 Way, Short .....	B20-3S-*	BC21
<b>COUNTERBALANCE CAVITIES AND BODIES</b>			
MHC-010 .....	Single and Dual Counterbalance Bodies .....	MHC-010-*	BC22
<b>PILOT PISTON CAVITIES</b>			
10 Size .....	10 Size Cavity for Dual Check and Pilot Piston .....		BC23
<b>SPECIAL BODIES AND CAVITIES</b>			
CAVOW-2 .....	2 Port .....	LB10795S .....	BC24
CAVSW-3 .....	3 Port .....	LB10815S .....	BC25
CAVT11A .....	3 Port .....	LB10825S .....	BC26
2C .....	2 Port .....	LB10212S .....	BC27
2R .....	2 Port .....	LB10543S .....	BC28
2U .....	2 Port .....	LB10220S .....	BC29
3A .....	3 Port .....	LB10066S .....	BC30
3C .....	3 Port .....	LB10069S .....	BC31
3K .....	3 Port .....	LB10089S .....	BC32
3M .....	3 Port .....	LB10078S .....	BC33
3X .....	3 Port .....	LB10553S .....	BC34
4C .....	4 Port .....	LB10562S .....	BC35
5A .....	5 Port .....	LB10321S .....	BC36
53-1 .....	3 Port .....	LB10318S .....	BC37
68-1 .....	3 Port .....	LB10253S .....	BC38
100-1 .....	5 Port .....	LB10317S .....	BC39

CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC

Bodies &  
Cavities

TD

Technical  
Data



## INTRODUCTION

This Technical Tips section is split into two parts; Standard Line Bodies and Cavities. In the standard line bodies section, we highlight the features and options of our standard offering of line bodies. In the cavity section we discuss “common” cavities.

The Technical Tips are provided to help you become more familiar with Parker Hannifin’s line of product and assist you in applying our product.

## STANDARD LINE BODIES

Parker offers standard line bodies for each valve and cavity size. Below are some of the features of Parker’s standard line bodies.

### Zinc Coating

Steel bodies are coated with zinc providing protection from salt spray.

### Common Cavity

Allows single body to be used for a number of functions.

### Various Port Sizes

Each body has a variety of port sizes and types available.

### Slotted Mounting Holes

Allows several bodies to be stacked together and held by one set of bolts.

### Aluminum and Steel Bodies

Light weight aluminum bodies are available for low pressure applications. Durable steel bodies are available for higher pressures.

### Clear Anodized

Aluminum bodies are thin coated with a clear anodize providing corrosion resistance.

## COMMON OPTIONS & FEATURES

**Aluminum vs. Steel:** Parker offers standard line bodies in both aluminum and steel. Aluminum bodies are most often used for general applications. Parker’s aluminum bodies are coated with a clear anodize to provide a corrosion resistant protection. Aluminum bodies should never be used in applications above 210 bar (3000 psi.) Steel bodies are more durable and

heavier than aluminum bodies. They are ideal for applications with elevated pressures or where rugged construction is desired. Steel bodies are suitable for applications up to 350 bar (5000 psi.) Parker’s steel bodies are coated with zinc providing corrosion resistance. Zinc even provides the steel body many hours of protection from salt spray.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data


COMMON OPTIONS & FEATURES (Cont.)

**Pressure Drop:** The pressure drop through a line body is fairly minimal. Each catalog page shows a pressure drop curve. This should be added to the pressure drop through the cartridge when trying to estimate total pressure drop for a function.


**Porting:** Parker offers a variety of port sizes and types for each line body. While NPT or pipe ports were once very popular and are still offered, we recommend SAE ports for new applications. SAE ports and fittings provide a more secure connection than pipe ports.

“If using an HY15-3502 or an older catalog, note we have re-numbered the ports on our 3-way line bodies” In the past, three way bodies were numbered with the nose being port 1, the middle port labeled (3), and the

top port labeled (2). Over the years, this has caused some confusion, so we have relabeled the ports sequentially from the bottom. For identification, the current design will be marked with a Parker symbol like the one shown.



Previous Design



Current Design

CAVITIES

The hole that the cartridge valve is screwed into is called a cavity. Many cartridge producers manufacture valves that fit a “common” cavity. With a “common” cavity, a valve theoretically could be removed from a cavity and replaced by another manufacturer’s product. One should be careful though to check cross drill ports and thread depths when pursuing this activity. While it is true that many manufacturer’s products fit inside another’s cavity, the cross drills sometimes expose an o-ring to pressure, causing the o-ring to be extruded.

**Valve / Cavity Compatibility Chart:** Through acquisition, Parker Hannifin has accumulated a number of manufacturers with “common” cavities. To accommodate all of our product lines, you will find a chart like the one shown on this page on each catalog page. The purpose of this chart is to help identify if a valve from one acquisition can be replaced by a Parker valve, or another acquisition valve. The valves are designated by the columns of the chart and the cavities by the rows. If you have an existing cavity, you find it on the chart and follow across to see which valves you may put in the cavity. For instance, using the chart below, let’s say you have an existing manifold in which you had manufactured a FPS cavity (maybe you were using a SV2A-10). By finding the row labeled FPS and following across, you find that you could use the FPS product, or a CEC product of the same size in this cavity. A Parker or Waterman valve will not fit in this cavity without modifying the cavity.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS				
	CEC				


CV	Check Valves
SH	Shuttle Valves
LM	Load/Motor Controls
FC	Flow Controls
PC	Pressure Controls
LE	Logic Elements
DC	Directional Controls
SV	Solenoid Valves
PV	Proportional Valves
CE	Coils & Electronics
BC	Bodies & Cavities
TD	Technical Data

## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS				
	CEC				

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B04</b>	—	<b>3</b>	—	<b>4T</b>
04 Size		3-Way Cavity		Port Size

Code	Port Size / Material
4T	SAE-4 Steel

Weight: .10 kg (.23 lbs.)

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X	X	X
	Waterman	X	X	X	X
	FPS	X	X	X	X
	CEC	X	X	X	X

Hydraulic Oil 150 SSU @ 100°F (32 cSt)

Flow (Q)	Flow (LPM)	Flow (GPM)	Pressure Drop (PSI)	Pressure Drop (Bar)
0	0	0	0	0
10	7.5	2	20	1.4
20	15	4	40	2.8
30	22.5	6	60	4.1
40	30	8	80	5.5
50	37.5	10	100	6.9

3/4  
16UNF-2B  
Ø (.002) B

Ø 30.18  
(1.188)

Ø 17.55 (.691)  
Ø 17.37 (.684)

Ø 20.71 (.816)  
Ø 20.59 (.811)

2.92 (.115)  
2.54 (.100)  
.79 (.031) Max.

14.27 (.562)  
14.02 (.552)

Ø 7.9 (.312) Max.

1.59 (.063) R.

45°

30°

63°

15° 63°

.25 (.010) R. Max.

14.40 (.567)  
14.15 (.557)

19.18 (.755)  
18.92 (.745)  
28.58 (1.125) Min.

Ø 11.11 (.438) Max.

Ø 12.75 (.502)  
Ø 12.70 (.500)

Ø (.002) A  
-B-




Diagram illustrating the connection between components: **B08** (08 Size) — **2** (2-Way Cavity) — **6T** (Port Size).

Code	Port Size
6T	SAE - 6/Steel (5000PSI)


**Weight:** .11 kg (.25 lbs.)

## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS			X	X
	CEC			X	X

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B08</b>	—	<b>3</b>	—	<b>6T</b>
08 Size		3-Way Cavity		Port Size

Code	Port Size
6T	SAE - 6/Steel (5000PSI)

Weight: .27 kg (.60 lbs.)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X			
	Waterman				
	FPS				
	CEC				

Technical drawing of a mechanical part, showing a side view and a cross-section.

**Side View Dimensions:**

- Overall length: 54.10 [2.130]
- Top surface features:
  - 42.60 [1.677]
  - 42.34 [1.667]
  - 31.62 [1.245]
  - 31.37 [1.235]
  - 14.10 [0.555]
  - 13.84 [0.545]
  - 2.92 [0.115]
  - 2.54 [0.100]
  - .79 [0.031] Max.
- Bottom surface features:
  - Ø30.18 [1.188]
  - Ø20.73 [0.816]
  - 20.59 [0.811]
  - 15°
  - 63
  - 45°
  - 63
  - Ø17.53 [0.690]
  - 17.37 [0.684]
  - 17.40 [0.685]
  - 17.15 [0.675]
  - 14.30 [0.563]
  - 28.42 [1.119]
  - 28.17 [1.109]
  - Ø5.56 [0.219] Max.
  - Ø15.93 [0.627]
  - 15.87 [0.625]
- Surface finish symbols:
  - 3/4 16UNF-2B [0.002] A
  - [0.002] A
  - [0.001] B
  - A-
- Other features:
  - R1.60 [0.063] Typ.
  - Ø5.56 [0.219] Max.
  - R.25 [0.010]
  - R.13 [0.005]
  - Ø5.56 [0.219] Max.

**Cross-section Dimensions:**

- Top surface features:
  - 11.1 [0.44]
  - 7.1 [0.28]
  - 28.3 [1.11]
  - 50.8 [2.00]
- Internal features:
  - C08-3L Cavity
  - 57.2 [2.25]
  - 28.6 [1.13]
  - 14.0 [0.55]
  - .8 [0.03]
  - 42.5 [1.67]
  - 76.2 [3.00]
  - R3.6 [0.14]
  - 47.6 [1.88]
  - 4.8 [0.19]
- Bottom surface features:
  - 25.4 [1.00]
  - 12.7 [0.50]

**B08** — **3L** — **6T**  
08 Size 3-Way Long Cavity Port Size

Code	Port Size
6T	SAE - 6/Steel (5000PSI)

**Weight:** .68 kg (1.5 lbs.)


## Technical Data

## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS			X	
	CEC				

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B08</b>	—	<b>4</b>	—	<b>6T</b>
08 Size		4-Way Cavity		Port Size

Code	Port Size
6T	SAE - 6/Steel (5000PSI)

Weight: .45 kg (1.0 lbs.)

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data




## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS			X	X
	CEC			X	X

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B10</b>	—	<b>2</b>	—	<b>8T</b>
10 Size		2-Way Cavity		Port Size

Code	Port Size
8T	SAE - 8/Steel (5000PSI)

Weight: .45 kg (1.0 lbs.)


CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X	X	X
	Waterman	X	X	X	X
	FPS	X	X	X	X
	CEC	X	X	X	X

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B10</b>	—	<b>3</b>	—	<b>8T</b>
10 Size		3-Way Cavity		Port Size

Code	Port Size
8T	SAE - 8/Steel (5000PSI)


Weight: .77 kg (1.7 lbs.)

## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X	X	
	Waterman	X	X	X	
	FPS	X	X	X	
	CEC				

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B10</b>	—	<b>3L</b>	—	<b>8T</b>
10 Size		3-Way Long Cavity		Port Size

Code	Port Size
8T	SAE - 8/Steel (5000PSI)

**Weight:** .77 kg (1.7 lbs.)

<b>CV</b>	Check Valves
<b>SH</b>	Shuttle Valves
<b>LM</b>	Load/Motor Controls
<b>FC</b>	Flow Controls
<b>PC</b>	Pressure Controls
<b>LE</b>	Logic Elements
<b>DC</b>	Directional Controls
<b>SV</b>	Solenoid Valves
<b>PV</b>	Proportional Valves
<b>CE</b>	Coils & Electronics
<b>BC</b>	Bodies & Cavities
<b>TD</b>	Technical Data


## Valve/Cavity Compatibility

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker				
	Waterman				
	FPS			X	X
	CEC			X	X


## Performance Curve

### Pressure Drop vs. Flow



## Dimensions

Millimeters (Inches)



## Ordering Information

<b>B10</b>	—	<b>3S</b>	—	<b>8T</b>
10 Size		3-Way Short Cavity		Port Size

Code	Port Size
8T	SAE - 8/Steel (5000PSI)

Weight: .77 kg (1.7 lbs.)


**\*Please be advised that this is a non-core line body.**  
 Additional lead-time and/or pricing requirements may exist when ordering.

## Valve/Cavity Compatibility

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X	X	X
	Waterman	X	X	X	X
	FPS	X	X	X	X
	CEC	X	X	X	X


## Performance Curve Pressure Drop vs. Flow



### NOTE:

When machining for use with DF102P, Ports 1 and 4 must be connected in the manifold/block.

## Dimensions



## Ordering Information

<b>B10</b>	—	<b>4</b>	—	<b>8T</b>
10 Size		4-Way Cavity		Port Size

Code	Port Size
8T	SAE - 8/Steel (5000PSI)

Weight: .90 kg (2.0 lbs.)


<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS				
	CEC				X

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B12</b>	—	<b>2</b>	—	<b>12T</b>
12 Size		2-Way Cavity		Port Size

Code	Port Size
12T	SAE - 12/Steel (5000PSI)

Weight: .45 kg (1.0 lbs.)

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAPVITY	Parker	X	X		
	Waterman	X	X		
	FPS				
	CEC				X

Hydraulic Oil 150 SSU @ 100°F (32 cSt)

Flow (Q)	Pressure Drop ( $\Delta P$ )
0	0
19 LPM (5 GPM)	~10 PSI
38 LPM (10 GPM)	~20 PSI
57 LPM (15 GPM)	~30 PSI
76 LPM (20 GPM)	~40 PSI
95 LPM (25 GPM)	~50 PSI
114 LPM (30 GPM)	~80 PSI

A diagram showing three boxes connected by horizontal lines. The first box contains 'B12' with '12 Size' below it. The second box contains '3' with '3-Way Cavity' below it. The third box contains '12T' with 'Port Size' below it.

Code	Port Size
12T	SAE - 12/Steel (5000PSI)

**Weight:** 2.0 kg (4.5 lbs.)

Technical Data	TD
Bodies & Cavities	BC
Coils & Electronics	CE
Proportional Valves	PV
Solenoid Valves	SV
Directional Controls	DC
Logic Elements	LE
Pressure Controls	PC
Flow Controls	FC
Load/Motor Controls	LM
Shuttle Valves	SH
Check Valves	CV




## Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS			X	X
	CEC			X	X

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B16</b>	—	<b>2</b>	—	<b>16T</b>
16 Size		2-Way Cavity		Port Size

Code	Port Size
16T	SAE - 16/Steel (5000PSI)

Weight: 1.5 kg (3.4 lbs.)


CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS			X	X
	CEC			X	X

## Performance Curve

### Pressure Drop vs. Flow




## Ordering Information

**B16** — **3** — **16T**  
 16 Size      3-Way Cavity      Port Size

Code	Port Size
16T	SAE - 16/Steel (5000PSI)

**Weight:** 3.0 kg (6.5 lbs.)

## Dimensions Millimeters (Inches)

**CV**

## Check Valves

SH

## Shuttle Valves

LM

### Load/Motor Controls

**FC**

## Flow Controls

PC

### Pressure Controls

LE

## Logic Elements

**DC**

### Directional Controls

SV

## Solenoid Valves

**PV**

### Proportional valves

**CE**

**oils &  
electronics**

BC

## Bodies & Cavities

**TD**

## Technical Data

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X	X	X
	Waterman	X	X	X	X
	FPS	X	X	X	X
	CEC	X	X	X	X

Hydraulic Oil 150 SSU @ 100°F (32 cSt)

Flow Rate (Q)	Pressure Drop ( $\Delta P$ )
0 LPM / 0 GPM	0 PSI / 0 Bar
15 LPM / 57 GPM	14 PSI / 0.97 Bar
30 LPM / 114 GPM	28 PSI / 1.94 Bar
45 LPM / 171 GPM	42 PSI / 2.91 Bar
60 LPM / 228 GPM	56 PSI / 3.88 Bar

Diagram illustrating the relationship between the three types of cavities:

- B16** (16 Size)
- 3S** (3-Way Short Cavity)
- 16T** (Port Size)

Code	Port Size
16T	SAE - 16/Steel (5000PSI)

**Weight:** 2.4 kg (5.4 lbs.)


## Technical Data

## Valve/Cavity Compatibility

For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X		
	Waterman	X	X		
	FPS			X	X
	CEC			X	X

## Dimensions Millimeters (Inches)



## Ordering Information

<b>B16</b>	—	<b>4</b>	—	<b>16T</b>
16 Size		4-Way Cavity		Port Size

Code	Port Size
16T	SAE - 16/Steel (5000PSI)

Weight: 3.75 kg (8.125 lbs.)


<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

## Valve/Cavity Compatibility



For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker	X	X	X	X
	Waterman	X	X	X	X
	FPS	X	X	X	X
	CEC	X	X	X	X

## Performance Curve Pressure Drop vs. Flow



## Dimensions



## Ordering Information

<b>B20</b>	—	<b>2</b>	—	<b>20T</b>
20 Size		2-Way Cavity		Port Size

Code	Port Size
20T	SAE - 20/Steel (5000PSI)

Weight: 6.3 kg (14 lbs.)


CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

### Valve/Cavity Compatibility


For additional information see Technical Tips on pages BC2-BC3.

		VALVE			
		Parker	Waterman	FPS	CEC
CAVITY	Parker				
	Waterman				
	FPS				
	CEC				X

### Performance Curve Pressure Drop vs. Flow



### Dimensions



### Ordering Information

<b>B20</b>	—	<b>3S</b>	—	<b>20T</b>
20 Size		3-Way Short Cavity		Port Size

Code	Port Size
20T	SAE - 20/Steel (5000PSI)

Weight: 10.8 kg (22.2 lbs.)

**\*Please be advised that this is a non-core line body.**  
 Additional lead-time and/or pricing requirements may exist when ordering.


## Valve/Cavity Compatibility

For additional information see Technical Tips on pages BC2-BC3.


		VALVE	
		MHC-010	2-N-4*-10
CAVITY	MHC-010	X	X
	2-N-4*-10	X	X

## Dimensions Millimeters (Inches)

### CDD-1010



### Single Body



## Ordering Information

<b>MHC</b>	—	<b>010</b>	—	<b>A</b>	—	<b>53</b>
Counterbalance Cartridge Valve		Nominal Flow Rating		Body Type		Port Size

Code	Body Type
A	Single

Code	Port Size
53	SAE-10 through port

**Weight:** Single 1.1 kg (2.25 lbs.)

**\*Please be advised that this is a non-core line body.**  
**Additional lead-time and/or pricing requirements may exist when ordering.**




Dimensions    Millimeters (Inches)

10 Size Cavity for Dual  
Check and Pilot Piston

For Check Valves Use 2  
CVH103P\*\*

For Pilot Piston Use  
717917      No Seal



CV

Check  
Valves

SH

Shuttle  
Valves

LM

Load/Motor  
Controls

FC

Flow  
Controls

PC

Pressure  
Controls

LE

Logic  
Elements

DC

Directional  
Controls

SV

Solenoid  
Valves

PV

Proportional  
Valves

CE

Coils &  
Electronics

BC


Bodies &  
Cavities

TD

Technical  
Data

Technical Data	TD	Bodies & Cavities	BC	Coils & Electronics	CE	Proportional Valves	PV	Solenoid Valves	SV	Directional Controls	DC	Logic Elements	LE	Pressure Controls	PC	Flow Controls	FC	Load/Motor Controls	LM	Shuttle Valves	SH	Check Valves	CV
-------------------	----	-------------------	----	---------------------	----	---------------------	----	-----------------	----	----------------------	----	----------------	----	-------------------	----	---------------	----	---------------------	----	----------------	----	--------------	----

Millimeters (Inches)



<b>LB10</b>	<b>795</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
795	1/4 SAE


Code	Body Material
S	Steel

**\*Please be advised that this is a non-core line body.  
Additional lead-time and/or pricing requirements may exist when ordering.**

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>815</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
815	1/4 SAE


Code	Body Material
S	Steel

\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>825</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
825	1/4 SAE

Code	Body Material
S	Steel

\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

**CV**

## Check Valves



## LM

## Load/Motor Controls


FC

## Pressure Controls

LE

For additional information see Technical Tips on pages BC2-BC3.

**Dimensions**  
 Millimeters (Inches)



**Ordering Information**

<b>BW14</b>	—	<b>2</b>	—	<b>8T</b>
2R		2-Way Cavity		Port Size/ Body Material

Code	Body Material
8T	SAE - 8/Steel (5000PSI)

\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

**CV**

## Check Valves



## Shuttle Valves

LM

## Load/Motor Controls

FC


## Flow Controls



For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>066</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
066	SAE16


Code	Body Material
S	Steel

**\*Please be advised that this is a non-core line body.**  
**Additional lead-time and/or pricing requirements may exist when ordering.**

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

**Dimensions**  
 Millimeters (Inches)



**Ordering Information**

<b>LB10</b>	<b>069</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
069	1 SAE (Main) 1/4 SAE (Aux)

Code	Body Material
S	Steel

\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

**CV**  
Check Valves

**SH**  
Shuttle Valves

**LM**  
Load/Motor Controls

**FC**  
Flow Controls

**PC**  
Pressure Controls

**LE**  
Logic Elements

**DC**  
Directional Controls

**SV**  
Solenoid Valves

**PV**  
Proportional Valves

**CE**  
Coils & Electronics


**BC**  
Bodies & Cavities

**TD**  
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>089</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
089	1 SAE (Main) 1/4 SAE (Aux)


Code	Body Material
S	Steel

**\*Please be advised that this is a non-core line body.**  
**Additional lead-time and/or pricing requirements may exist when ordering.**

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>078</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
078	1 SAE (Main) 1/4 SAE (Aux)

Code	Body Material
S	Steel


\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>553</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
553	1/2 SAE

Code	Body Material
S	Steel


\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>562</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
562	1/2 SAE


Code	Body Material
S	Steel

\*Please be advised that this is a non-core line body.  
 Additional lead-time and/or pricing requirements may exist when ordering.

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>321</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
321	3/4 SAE (Main) 1/4 SAE (Aux)

Code	Body Material
S	Steel


**\*Please be advised that this is a non-core line body.**  
**Additional lead-time and/or pricing requirements may exist when ordering.**



For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>318</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
318	3/8 SAE (Main) 1/4 SAE (Aux)

Code	Body Material
S	Steel


**\*Please be advised that this is a non-core line body.**  
**Additional lead-time and/or pricing requirements may exist when ordering.**

<b>CV</b>
Check Valves
<b>SH</b>
Shuttle Valves
<b>LM</b>
Load/Motor Controls
<b>FC</b>
Flow Controls
<b>PC</b>
Pressure Controls
<b>LE</b>
Logic Elements
<b>DC</b>
Directional Controls
<b>SV</b>
Solenoid Valves
<b>PV</b>
Proportional Valves
<b>CE</b>
Coils & Electronics
<b>BC</b>
Bodies & Cavities
<b>TD</b>
Technical Data

For additional information see Technical Tips on pages BC2-BC3.

## Dimensions

Millimeters (Inches)



## Ordering Information

<b>LB10</b>	<b>253</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Port Size
253	1-1/4 SAE (Main) 3/8 SAE (Aux)

Code	Body Material
S	Steel

**\*Please be advised that this is a non-core line body.**  
**Additional lead-time and/or pricing requirements may exist when ordering.**

Technical Data	TD	Bodies & Cavities	BC	Coils & Electronics	CE	Proportional Valves	PV	Solenoid Valves	SV	Directional Controls	DC	Logic Elements	LE	Pressure Controls	PC	Flow Controls	FC	Load/Motor Controls	LM	Shuttle Valves	SH	Check Valves	CV
-------------------	----	-------------------	----	---------------------	----	---------------------	----	-----------------	----	----------------------	----	----------------	----	-------------------	----	---------------	----	---------------------	----	----------------	----	--------------	----

[illegible]

<b>LB10</b>	<b>317</b>	<b>S</b>
Line Body	Port Size	Body Material

Code	Body Material
S	Steel



DESCRIPTION	PAGE NO.
Basic Hydraulic Formulas.....	TD2
Ratings and Testing .....	TD2
Temperature Ratings.....	TD2
Viscosity .....	TD2
Pressure Ratings.....	TD2
Thermal Shock .....	TD2
Service and Components .....	TD2
Limitations in Use .....	TD2
Seal Material Selection .....	TD3
Hydraulic Fluids .....	TD4
Hydraulic Filtration.....	TD4
Application of Product.....	TD4

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data



## INTRODUCTION

In this section you will find a variety of technical information pertinent to general hydraulics as well as cartridge valve technology.

## HYDRAULIC FORMULAS

Below are a few of the common hydraulic formulas to assist you in calculating the requirements for your system:

$$\text{Voltage} = \text{Current} \times \text{Resistance}$$

$$\text{Flow} = \text{Volume} \div \text{Unit of Time}$$

$$\text{Pressure} = \text{Force} \div \text{Area}$$

$$\text{Horsepower} = \text{Flow} \times \text{Pressure} \div (1714 \times \text{Efficiency})$$

$$\text{Hydraulic power (kW)} = \frac{\Delta p \text{ (Bar)} \times \text{flow rate (LPM)}}{600}$$

where  $\Delta p$  = pressure drop

$$\text{Hydraulic power (HP)} = \frac{\Delta p \text{ (PSI)} \times \text{flow rate (GPM)}}{1714}$$

## RATINGS & TESTING

All Parker cartridge valve products have been performance tested with the results shown on the individual valve catalog pages. The performance data shown represents typical operation characteristics of the product. In addition, our valves are endurance tested. Validation is conducted by testing or similarity in designs.

**Note:** Not every cartridge option is endurance tested. In other words, one three way spool is endurance tested, and the others are assumed by similarity.

## TEMPERATURE RATINGS

Product operating limits are broadly in the range -30°C to 150°C (-20°F to 300°F) but satisfactory operation within the specification may not be accomplished. Leakage and response will be affected when used at temperature extremes and it is the user's responsibility to determine acceptability at these levels.

Seals used in these products generally have the following temperature limitations:

<b>Nitrile (Buna N)</b>	-34°C to 121°C (-30°F to 250°F)
<b>Fluorocarbon</b>	-26°C to 204°C (-15°F to 400°F)
<b>Hytrel</b>	-54°C to 135°C (-65°F to 275°F)
<b>GTPFE</b>	-30°C to 150°C (-20°F to 300°F)
<b>4301 Polyurethane</b>	-37°C to 93°C (-35°F to 200°F)

## VISCOSITY

Catalog data is from tests conducted on mineral oil at a viscosity of 32 cSt (150 SSU) using an ISO 32 fluid at 100 degrees F.

Product should ideally be used at viscosities in the range of 15 to 50 cSt (80 to 230 SSU).

Product will perform with reduced efficiency in the ranges, 5 to 15 cSt (42 to 80 SSU) and 50 to 500 cSt (230 to 2300 SSU). These extreme conditions must be evaluated by the user to establish suitability of the product's performance.

## PRESSURE RATINGS

Unless otherwise stated, all Parker cartridges have a continuous duty pressure rating as shown in the catalog. All pressure ratings are based on the cartridge valve only. Exposure to elevated pressures may affect the performance and fatigue life of the product. The material chosen for the body or carrier may affect the pressure rating we recommend. Parker does not recommend the use of cartridge valves in aluminum bodies at pressures above 207 bar (3000 psi).

## THERMAL SHOCK

It is unreasonable to expect product to withstand rapid temperature changes - this could affect both performance and life and care should be taken to protect the product from such situations.

## SERVICE & COMPONENTS

One of the advantages of integrated hydraulic circuits is their serviceability. Should a valve need to be replaced for any reason, a user only needs to unscrew the valve from the manifold and screw the replacement into the cavity. As such, there are few replacement parts available for the Parker cartridge products. As with any hydraulic system, the operator should bleed off any trapped pressure and consult machine service manuals prior to service. Parker does not offer any service parts for internal components, but external components such as coils, knobs, and seals are available.

## LIMITATIONS IN USE

Parker cartridge valves are designed for a wide variety of industrial and mobile applications. Despite their flexibility, Parker Hannifin does not recommend or support the use of our cartridge valves in any on-highway or aerospace applications. We also do not recommend our products for use in the transport of explosive products or in hazardous environments.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

## SEAL MATERIAL SELECTION

You should match the seal compatibility to the temperature and fluid being used in your application. Parker offers three seal materials to meet your application requirements. Parker's standard material is a 4301 Polyurethane RESILON™ material "D"-Ring. We also offer Fluorocarbon and Nitrile seals. A brief synopsis of each seal material is given below to help you choose the best seal for your application.


### "D"-Ring (4301 Polyurethane RESILON™ Material)

The "D"-Ring is the standard seal material on the Winner's Circle threaded cartridge valves. The "D"-Ring is molded of a special 4301 Polyurethane RESILON™. Polyurethane materials exhibit better wear resistance and tensile strength than standard Nitrile or Fluorocarbon material. In addition, it has an excellent resistance to compression set. This increased strength eliminates the need for back-rings and simplifies installation.

The 4301 compound is a Parker exclusive material designed to prevent hydrolysis at high temperatures.

Thus, the "D"-Ring outperforms standard polyurethane o-rings, especially when using high water content fluids at elevated temperatures. The "D"-Ring is compatible with most water-glycol, water/oil emulsions, and high grade petroleum based hydraulic fluids at temperatures between -37°C to +93°C (-35°F to +200°F)

The unique shape of the Parker "D"-Ring also provides a variety of design advantages. The seal is molded into a "D" shape where the seal is higher in the middle and lower on the ends. This prevents the seal edge from folding over on a corner inside the manifold during installation. In addition, this design has a minimal lip, thus, friction is reduced. Another unique feature of the "D"-Ring is its symmetrical design, resulting in no performance degradation from the reverse direction, or worry of backward installation. The "D"-Ring is also equipped with "pressure pedestals" to reduce the effects of "blow-by" common in reverse cycling. The pressure pedestals increase the sealing capability of the "D"-Ring, by reducing the radial pressure forces that compress the sealing face of the o-ring. The drawing below depicts the shape and highlights the features.



### Nitrile

Nitrile o-rings are also compatible with most water-glycol, water/oil emulsions, and high grade petroleum based hydraulic fluids. Parker only recommends Nitrile o-rings for temperatures between -34°C to +121°C (-30°F to +250°F). Nitrile o-rings do require a full back-up ring, or two half back-ups.

### Fluorocarbon

Fluorocarbon o-rings are compatible with most phosphate ester fluids and phosphate ester blends. Parker only recommends Fluorocarbon seals for temperatures between -26°C to +204°C (-15°F to +400°F). Fluorocarbon o-rings do require a full back-up ring, or two half back-ups.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data

**HYDRAULIC FLUIDS**

Parker recommends using top-quality mineral based or synthetic hydraulic fluids with lubricating properties at viscosities of 45 to 2000 SSU (6 to 420 cSt) at 38°C (100°F). The absolute viscosity range 80 to 1000 SSU (16 to 220 cSt.). Fluids should have high anti-wear characteristics and be treated to protect against oxidation.

**HYDRAULIC FILTRATION**

Hydraulic systems that include Parker valves should be carefully protected against fluid contamination. The proper cleanliness level for Parker cartridge valves should be maintained at an ISO cleanliness level of 18/16/13.

75% of all system failures are a direct result of contamination. Contamination interferes with four functions of hydraulic fluids.

1. To act as an energy transmission medium.
2. To lubricate internal moving parts of components.
3. To act a heat transfer medium.
4. To seal clearances between moving components.

A properly selected filter will provide adequate protection and reduce operating cost. This is achieved by increasing the expected life of the valves and reducing the cost of maintenance and repairs. Operation will be smoother and more precise.

There is no direct correlation between using a specific ISO cleanliness classification. Numerous other variables should be considered such as particulate ingress, actual flow through filters, and filter location.

A number of interrelated system factors combine to determine proper media and filter combinations. To accurately determine which combination is ideal for your system, all these factors need to be accounted for. With the development of filtration sizing software such as Parker inPHorm, this information can be used to compute the optimal selection. In many instances the information available may be limited. In these cases, "rules of thumb" based on empirical data and proven examples are applied to get an initial starting point.

**APPLICATION OF PRODUCT**

**CAUTION** - It is important to note that the Parker Hydraulic Cartridge Systems Division makes a variety of valves, many of which fit into the same cavity. However, their functionality may differ considerably from one valve type to another. Accordingly fit interchangeability does not necessarily mean form or function interchangeability. Users should ensure that the appropriate valve is installed in the cavity by cross checking the part number stamped on the valve with that published in approved service literature or in the installation drawing.

CV
Check Valves
SH
Shuttle Valves
LM
Load/Motor Controls
FC
Flow Controls
PC
Pressure Controls
LE
Logic Elements
DC
Directional Controls
SV
Solenoid Valves
PV
Proportional Valves
CE
Coils & Electronics
BC
Bodies & Cavities
TD
Technical Data



# Parker Hannifin - Hydraulic Valve Systems and Mobile Systems Division - Europe

Parker HVS and MSDE Divisions are leaders in the cartridge valve and custom manifold industry, serving both the mobile and industrial machine markets.

Our team of application engineers and manufacturers consistently challenge valve standards to achieve the most efficient and flexible designs. They work hard to provide the highest level of customer satisfaction and support. Discover how Parker HVS and MSDE can be the ONE source for all your hydraulic cartridge and manifold needs.

Have questions? Visit us at [www.parker.com](http://www.parker.com)

Parker Hannifin Corporation  
**Hydraulic Valve Systems**  
520 Ternes Avenue  
Elyria, Ohio 44036-4026  
United States  
Ph: (440) 366 5100  
[hvd.support@support.parker.com](mailto:hvd.support@support.parker.com)  
[www.parker.com/hvs](http://www.parker.com/hvs)

Parker Hannifin Corporation  
**Mobile Hydraulic Systems  
Division Europe**  
Parker Hannifin Manufacturing LTD  
Blacknell Lane - Crewkerne  
TA18 8LL  
UK  
Tel: +44 (0) 01460 271800  
[MSDE.Crewkerne.ProductSupport@support.parker.com](mailto:MSDE.Crewkerne.ProductSupport@support.parker.com)  
[www.parker.com/msde](http://www.parker.com/msde)

Parker Hannifin Corporation  
**Corporate Headquarters**  
6035 Parkland Blvd  
Cleveland, OH 44124  
USA  
Tel: 216-896-3000  
Fax: 216-896-4000

For information, please contact Parker toll free at 1-800-C-PARKER (1-800-272-7537).  
Outside of North America contact us via Freephone at 00800 27 27 5374.

